Fide Symbol-ICTEE - GO

## TOWER ALGAECIDE 20

ACTIVE INGREDIENTS

Poly (oxyethylene (din	nethylimin <mark>o)</mark> ethy	tem
(dimethylimino) ethylene dichloride, .		20.0°0
INERT INGREDIENTS	• • • • · · · ·	80.0
Weight per gallon	•••••••	8.69 lbs.

Weight of active ingredient	per !b	1.74 lb
-----------------------------	--------	---------

## CAUTION

Causes irritation of skin and eyes. Avoid contact with skin, eyes, or clothing.

KEEP OUT OF THE REACH OF CHILDREN

See other precautions on side panel

EPA Reg. No 10088-39 EPA Est. No. 10088 WI 1

Net Contents.

Dec 9:1974 10038-39

## APPLICATION

TOWER ALGAECIDE 20 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 2.9 to 7.3 fluid ounces of TOWER ALGAECIDE 20 per 1000 gallons of water to provide a concentration of 24 to 60 parts per million of TOWER ALGAE-CIDE 20 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slog additions c<sup>c</sup> 0.73 to 7.3 fluid ounces of TOWER ALGAECIDE 20 per 1000 gallons of water (6 to 60) parts per million of TOWER ALGAECIDE 20 should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the slump of water cooling towers.

## CAUTION

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, prinds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

Distributed by-