

NATIONAL'S ZEOLITE ALGAEICIDE NP-40L

**A Non-foaming treatment to control Algae, Fungi and Bacterial Slime
in recirculating commercial and industrial Water Cooling Towers.**

Active Ingredients: Poly (oxyethylene (dimethyliminio) ethylene (dimethyliminio)
ethylene dichloride) 10.0%
Inert Ingredients: 90.0%

DIRECTION FOR USE

It is recommended that the system be thoroughly cleaned, drained, flushed and refilled with fresh water prior to regular treatment with NP-40L. Badly fouled systems must be cleaned before treatment is begun.

Initial Dose: Add 1-2 quarts of NP-40L for each 5,000 gallons of water in the system (provides 5-10 ppm actives). Add treatment directly to the sump of Water Cooling Towers. Repeat until control is achieved.

Maintenance Dose: Add 1/2 pint to 2 quarts of NP-40L for each 5,000 gallons of water (1-10 ppm actives) every 2-5 days or as needed.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

NATIONAL CHEMICAL

DIVISION OF

EPA Reg. No. 10133-5

SELIG CHEMICAL INDUSTRIES Net Contents

Atlanta, Georgia 30336

ACCEPTED