

ANTIFOULING PACIFIC (7609)

ACTIVE INGREDIENTS:

(Cuprous oxide) 60%

INERT INGREDIENTS: 40%

100% by weight

DANGER: KEEP OUT OF REACH OF CHILDREN.

HEMPEL'S ANTIFOULING PACIFIC is for equatorial waters and is used as an antifouling finish on steel ships' bottoms from keel to light load line. It is composed of a soluble resinous matrix and cuprous oxide which is a poisonous substance.

APPLICATION INSTRUCTIONS: Thoroughly stir and apply 1-2 coats over HEMPEL'S PLATIN PRIMER or HEMPADUR TAR EPOXY. Allow a 3-5 hour drying time between coats of Hempel's Antifouling Pacific. If thinner is required, use Hempel's Thinner 823 at a ratio not to exceed 2% for brush application and 5% for spray application.

REMARKS: The ship may be floated when the finish is dry to touch (3-5 hours). Store in a cool-dry place away from heat, sunlight and open flame.

CLEANING EQUIPMENT: Brushes, rollers and spray equipment should be promptly cleaned with Hempel's Thinner 823.

WARNING: COMBUSTIBLE

Harmful or fatal if swallowed. Call physician immediately. Contains petroleum distillates. Do not induce vomiting. Keep away from heat, open flame and pilot lights. Use with adequate ventilation, avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use.

NON-WARRANTY: We guarantee the quality of this product and its conforming to our standard specifications, as published. However, as the use of the material is not under our control, we expressly disclaim any responsibility for its use, handling, storage, results obtained, injury, or indirect or consequential damage of any nature whatsoever, however caused.

CAUTION: Do not contaminate water by cleaning of equipment, or disposal of waste.

CONTAINER DISPOSAL: Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

USDA REG. NO. 102-0-3

2976—IDEAL

THINNER 823 0000