

ANTIFOULING TROPIC (7644)

ACTIVE INGREDIENTS:

Tributyltin Fluoride	5.80%
Bis(Tributyltin) Oxide	.86%

INERT INGREDIENTS:

93.34%

100.00% by weight

DANGER: KEEP OUT OF REACH OF CHILDREN.

HEMPEL'S ANTIFOULING TROPIC is a modified soluble matrix antifouling paint containing a highly active organic poison for prevention of marine growth. Recommended for steel ship's bottoms from keel to the deep load line.

APPLICATION INSTRUCTION: Stir thoroughly and apply 1 coat of HEMPEL'S ANTIFOULING TROPIC over HEMPEL'S PLATIN PRIMER 1000, 1005, HEMPADUR 1513, or HEMFA-TEX PRIMER. If thinning is required, use HEMPEL'S THINNER 808 not in excess of 2% for brush application or 5% for spray application, by volume.

REMARKS: The ship may be floated when the finish is dry to touch. There is no maximum interval for undocking.

CLEANING EQUIPMENT: Brushes, roller and spray equipment should be promptly cleaned with HEMPEL'S THINNER 808.

WARNING: FLAMMABLE

Keep away from heat, sparks, and open flame. Keep container closed. Use with adequate ventilation. Causes severe eye damage. Do not get in eyes, on skin or on clothing. Wear goggles and face shield when handling. In case of contact with eyes, flush with plenty of water for 15 minutes. Call physician immediately. Wash skin with soap and water. Wash all contaminated clothing with soap and water before reuse. Store in cool, dry place away from heat, sunlight and open flame. Harmful or fatal if swallowed. Contains petroleum distillates. Do not induce vomiting. Close container tightly after use.

NON-WARRANTY: We guarantee the quality of this product and its conformity to our standard specifications published. However, as the use of the product is beyond our control, no guarantee, expressed or implied is made as to the effect, of such or the results to be obtained, if not used in accordance with directions of established safe practices. The buyer must assume all responsibilities, including injury or damage, resulting from its use or its combination with other materials.

CAUTION: Do not contaminate water by cleaning of equipment, or disposal of waste.

CONTAINER DISPOSAL: Do not reuse empty container, destroy it by perforation or crushing, bury or discard in a safe place.

EPA REG. NO. 10090-B

