

ACCEPTED

UNDER THE SUPERVISION OF
ENGINEER IN CHARGE
NAVY

ANTIFOULING DYNAMIC (7628)

ACTIVE INGREDIENTS:

(Cuprous Oxide) 64.7%

INERT INGREDIENTS: 35.3%

100.0% by weight

DANGER: KEEP OUT OF REACH OF CHILDREN.

HEMPEL'S ANTIFOULING DYNAMIC is a soluble matrix anti-fouling paint containing a highly active inorganic poison for prevention of marine growth. Recommended for steel ships bottoms from keel to the deep load line.

APPLICATION INSTRUCTIONS: Stir thoroughly and apply 1-2 coats of HEMPEL'S ANTIFOULING DYNAMIC. Allow 1 hour drying time between coats. A sealer coat is required if used over Tar Epoxy. If thinning is required use HEMPEL'S THINNER 846 not in excess of 5% for spray application, by volume.

REMARKS: The ship may be floated when the finish is dry to touch. When renewing the antifouling coat, the old coat should be sealed off with a recommended sealer coat even if it may appear sound and intact.

CLEANING EQUIPMENT: Brushes, roller and spray equipment should be promptly cleaned with HEMPEL'S THINNER 846.

WARNING: FLAMMABLE

Keep away from heat, sparks, and open flame. Keep container closed. Use with adequate ventilation. Causes severe eye damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield when handling. In case of contact with eyes, flush with plenty of water for 15 minutes. Wash skin with soap and water. Store in cool, dry place away from heat, sunlight and open flame. Harmful or fatal if swallowed. Call physician immediately. Do not induce vomiting. Close container tightly after use.

NON-WARRANTY: We guarantee the quality of this product and its conforming to our standard specifications as published. However, as the use of the product is beyond our control, no guarantee, expressed or implied is made as to the effects of such or the results to be obtained, if not used in accordance with directions or established safe practices. The buyer must assume all responsibilities, including injury or damage, resulting from its misuse as such, or in combination with other materials.

CAUTION: Do not contaminate water by cleaning of equipment, or disposal of waste.

CONTAINER DISPOSAL: Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

EPA REG. NO. 10250-10

ANTIFOULING DYNAMIC (7628)