ANTIFOULING OCEANIC (0733)

ACTIVE INGREDIENTS:	
(Tributyltin Fluoride)	6.6%
INERT INGREDIENTS:	93.4%
	100.0% by weight

DANGER: KEEP OUT OF REACH OF CHILDREN.

HEMPEL'S ANTIFOULING OCEANIC is an advanced antifouling paint with an [illegible] chlorinated rubber binder containing highly active organic poison for prevention of marine growth. Recommended for steel ship's bottoms from keel to the deep load line.

APPLICATION INSTRUCTIONS: Stir thoroughly and apply 1 [illegible] coat of HEMPEL'S ANTIFOULING OCEANIC over HEMPATEX PRIMER 4637 or HEMPADUR 1512. May also be applied by spray gun over HEMPEL'S PLATIN PRIMER. Allow at least one hour drying time between coats of HEMPEL'S ANTIFOULING OCEANIC at 20°C 68°F. Drying time will be proportionally longer at lower temperatures. If thinning is required for brush, roller, conventional spray or airless spray application use HEMPEL'S THINNER No. 608.

REMARKS: The ship may be floated when final coat of paint is dry to touch usually within 2 hours. [illegible] exposure to the atmosphere will not affect the properties of HEMPEL'S ANTIFOULING OCEANIC.

CLEANING EQUIPMENT: [illegible] and [illegible] should be primed, [illegible] with HEMPEL'S THINNER No. 608.

WARNING: FLAMMABLE

Keep away from heat, [illegible] and open flame. Keep container closed. Use with adequate ventilation. Causes [illegible] Do not [illegible] Avoid exposure to spray mist. Wash [illegible] handling. In case of contact with [illegible] with plenty of water [illegible] Store in cool, dry place [illegible] Do not [illegible] and spar varnish, other use.

NON-WARRANTY. [illegible]

CAUTION. [illegible]

CONTAINER DISPOSAL. [illegible]

EPA REG. NO. [illegible]

ACCEPT