

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeve cotton shirt, long pants, and hat. Causes irreversible eye damage. May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, mist & dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating or smoking. Use adequate ventilation. While spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash hands before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water.

PHYSICAL CHEMICAL HAZARDS

*** FLAMMABLE ***

Keep away from heat and open flame. Store in a cool dry place away from sunlight. Close container tightly after use.

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed herein we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever however caused. HEMPEL'S only obligation shall be to replace such quantity of product proved to be defective.

HEMPEL'S ANTIFOULING NAUTIC 7680 is an advanced self-polishing organotin formula for the prevention of barnacles, algae, and other sessile marine fouling organisms. Recommended for the underwater surfaces of steel vessels operated in all global coastal and oceanic trading waters.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT

RESTRICTED USE PESTICIDE

Due to Toxicity to Aquatic Organisms including Shellfish: For Sale only to certified commercial applicators and for use only by certified commercial applicators or by persons under the direct supervision of an on-site (at the work site) certified commercial applicator.

HEMPEL'S

ANTIFOULING NAUTIC®

7680-5128 RED

ACTIVE INGREDIENTS

TRIBUTYL TIN METHACRYLATE (AS A POLYMER)	4.04
BIS(TRIBUTYL TIN) OXIDE	0.95
TRIPHENYL TIN FLUORIDE	7.60

INERT INGREDIENTS

87.41

TOTAL METALLIC TIN 4.30% BY WEIGHT

100.00

CONTAINS PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN
DANGER

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

*** SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS ***

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR SALE TO USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL

MADE IN U.S.A. AND SOLD BY

HEMPEL COATINGS (USA), INC.
Curie Avenue, Wallington, NJ 07057
ESTABLISHMENT NO. 10250 N.J.
EPA REGISTRATION NO. 10250-14
NET CONTENTS: 5 U.S. GALLONS

DIRECTIONS FOR USE

APPLICATION INSTRUCTIONS: Stir thoroughly and apply to dry surface with a temperature above the dew point. A HEMPANYL TAR 1628 or according to specifications. Film mass and number of coats depend upon hull condition, pattern, and extended service life. Allow at least 8 time between coats of NAUTIC 7680 at 20C/68F. Dry time be proportionally longer at lower temperatures. If th required for brush, roller, conventional spray or air cation, use HEMPEL'S THINNER No. 0808. Equipment should promptly cleaned with THINNER No. 0808 after use. A s be floated when the final coat of paint is dry for 12 Prolonged exposure to the atmosphere will not affect properties of NAUTIC 7680. It is unlawful to use thi on nonaluminum hulled vessels less than 82 feet (25 m length) (on deck), except for the outboard motor or lo unit of such vessel. Users must comply with all appl requirements.

PRACTICAL TREATMENT

IF SWALLOWED: Drink large quantities of water.
NOTE TO PHYSICIAN: Probable mucosal damage may contr the use of gastric lavage.
IF IN EYES: Flush with plenty of water. Get medical
IF ON SKIN: Wash with plenty of soap and water. Get attention if irritation persists.
IF INHALED: Remove victim to fresh air. If not breath artificial respiration (mouth-to-mouth). Get m

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food or feed by storage or Open dumping is prohibited.

PESTICIDE DISPOSAL

Paint chips, spent abrasives, and any other waste mate removal of old paint must be disposed of in a sanitary (or, if required by Federal, State or local regulation as a hazardous waste). If possible, use all of the co application according to label instructions. Manage ex rinsate, and other application wastes in accordance wi State, and local requirements. Consult your State pes Environmental control agency, nearest EPA Regional Off RCRA/Superfund Hotline (800)424-9346 for waste dispos CONTAINER DISPOSAL

Triple rinse container if intended for recycling or re- ing. Empty paint containers with small amounts of dri- must be disposed of in a sanitary landfill (or, if req- Federal, State, or local regulations, handled as a hazi- waste).