Precautionary Stateme "Hazards to Humans and Domestic Animals"

DANGER. Corrosive causes irreversible eye damage and corrosive to skin. May be fatal if swallowed Wash thoroughly with soap and water after handling and before eating or smoking.

Wear complete impervious protective clothing including rubber gloves, protective suit and a full-face air-supplied pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly U.S. Bureau of Mines), and by the National Institute for Occupational Safety and Health under provisions of 30 CFR 11. Painters and other workers in the immediate vicinity must wear full protective clothing.

Women of child-bearing age should not be exposed to paint residue during application of this product

Environmental Hazards

Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

Physical Chemical Hazards

FLAMMABLE

Keep container closed. Use with adequate ventilation. Store in cool dry place away from heat, sunlight, and open flame. Close container tightly after use. Keep away from heat, and open flame.

This labeling must be in the presession of the user at the time of pesticide application. While all PEMPEL products are developed and manufactured with the utmost care, we offer the control ducts with one express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than as directed hereon, we expressly disclaim any responsibility for its use, handling, charge, result obtained injury or indirect or consequential damages of any nature whatsoever however caused.

It is guaranteed that this product conforms with formulae tested and approved by PEMPET Central Laboratory. ProMeter, our only only nation shall be to replace such quantity of product proved to be defective.

THERE ARE NO IMPLIED WARRANTIES OF MERCHAN-TABILITY OR OF UITNESS FOR A PARTICULAR PUR-POSE FOR THIS PRODUCT.

HEST DOCUMENT NAME AND TO

HEMPEL'S

ANTIFOULING NAUTIC 7680 - 1221 GRAY

ACTIVE INGREDIENTS

TRIBUTYLTIN METHACRYLATE (as part of a Polymer) 10250 - 14

TRIBUTYLTIN OXIDE

BEST DOCUMENT AVAILABL

TRIPHENYLTIN FLUORIDE

INERT INGREDIENTS // TOTAL METALLIC TIN 5.5% BY WEIGHT

WEIGHT PCT.

1/0250-14 4.04%

1/0250-14 4.04%

1/0250-14 4.04%

1/0250-14 4.04%

1/0250-14 100.00

THIS PRODUCT CONTAINS 12.5 .BS. OF PAINT PER GALLON

r

DANGER

Practical Treatment

IF IN EYES: flush with water for 15 minutes. Get medical attention immediately

IF ON SKIN: wash with plenty of soap and water and get medical attention

IF SWALLOWED; unink promptly a large quantity of milk-egg whites-gelatin solution or, if these are not available drink large quantities of water. Avoid alcohol. Get medical attention.

See side panel for additional precautionary statement

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR SALE TO. USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL.

MADE IN U.S.A. by

HEMPEL'S MARINE PAINTS, INC.

65 Broadway, New York, N.Y. 10006 ESTABLISHMENT NO - 10250 N.J EPA File Symbol 10250 Ru

NET CONTENTS: 5 U.S. GALLONS

HEMPEL'S

ANTIFOULING NAUTIC 7680 - 1221 GRAY

BUTYLTIN METHACRYLATE (as part of a Polymer) 10050 - 14
BUTYLTIN OXIDE

PHENYLTIN FLUORIDE

AL METALLIC TIN-5.5% BY WEIGHT

WEIGHT PCT.

1/0250 - 14 4.04%

95
7.60

7.41

THIS PRODUCT CONTAINS 12.5 .BS. OF PAINT PER GALLON

DANGER

Practical Treatment

IF IN EYES: flush with water for 15 minutes. Get medical attention immediately

IF ON SKIN: wash with plenty of soap and water and get medical attention

IF SWALLOWED: drink promptly a large quantity of milk-egg whites gelatin solution or if these are not available drink large quantities of water. Avoid alcohol. Get medical attention

See side panel for additional precautionary statement

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR SALE TO. USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL.

MADE IN U.S.A. by

HEMPEL'S MARINE PAINTS, INC.

65 Broadway, New York, N.Y. 10006 ESTABLISHMENT NO - 10250 N.J EPA File Symbol 10250-Bu

NET CONTENTS: 5 U.S. GALLONS

HEMPEL'S ANTIFOULING NAUTIC — — ese are advanced antifouling paints containing an organotin polymer binder to prevent marine growth. Recommended for steel ship's bottoms from keel to the deep load line.

Direction for Use

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

APPLICATION INSTRUCTIONS: stir thoroughly and apply NAUTIC ANTIFOULING over FEMPANYL TAR 1628 or according to specification. Allow at least 4 hr drying time between coats of NAUTIC ANTIFOULING at 20°C 68°F. Drying time will be proportionally longer at lower temperatures. If thinning is required for brush roller conventional spray or airless spray application, use HEMPEL 3 ThINNER NO. 808.

REMARKS: The strip may be floated when final coat of paint is dry for 12 hours. Prolonged exposure to the atmosphere will not affect the properties of NAUTIC ANTIFOULTING.

CLEANING EQUIPMENT: Brushes rollers and spray equipment should be promptly cleaned with HEMPEL'S THINNER NO. 808

STORAGE AND DISPOSAL

· (4)

PROHIBITIONS

DO NOT CONTAMINATE WATER FOOD OR FEED BY STORAGE OR DISPOSAL OPEN DUMPING IS PROFIBITED

PESTICIDE DISPOSAL

PESTICIDE SPRAY MIXTURE OF RINSE WATER THAT CANNOT BE USED ACCORDING TO LABEL INSTRUCTIONS MUST BE DISPOSED OF ACCORDING TO FEDERAL OR APPROVED STATE PROCEDURES UNDER SUBTITLE C OF THE RESOURCE CONSERVATION AND RECOVERY ACT

CONTAINER DISPOSAL

TRIPLE RINSE (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING. OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES

GENERAL

CONSULT FEDERAL STATE OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

SOUTHWENT AVAILABLE