



10-50-14 PM31 1062

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, D.C. 20460

OFFICE OF  
PESTICIDES AND TOXIC SUBSTANCES

Mr. Michael Bentkjaer  
Hempel Coatings (USA), Inc.  
6901 Cavalcade  
Houston, Texas 77028

SEP 18 1989

Re: Antifouling Nautic 7680-1221 Aray  
EPA Reg. No. 10250-14

Dear Mr. Bentkjaer:

This is in response to the above subject matter. The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable provided that you transpose the Restricted Use block and the Statement of Practical Treatment. The Restricted use block must appear on the front panel. The Statement of Practical Treatment should appear ~~on~~ <sup>below</sup> the Directions for use section, not within it.

Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your lease for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

Should you have any further questions, please contact Veronica Dutch (703) 557-7404.

Sincerely,

A handwritten signature in cursive script that reads "John H. Lee".

John H. Lee  
Product Manager 31  
Antimicrobial Program  
Registration Division

## PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER** Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeve cotton shirt, long pants, and hat. Causes irreversible eye damage. May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, mist & dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating or smoking. Use adequate ventilation. While spraying paint on sanding coat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash hands before reuse. Users must comply with all applicable OSHA requirements.

### ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. During and after removal and/or application of new TBT paint, methods must be employed which are designed to prevent release of TBT paint into aquatic environment. Following removal of old TBT paint and/or application of new TBT paint, all paint chips and spent abrasives, paint containers, unused paint, and any other waste products from paint removal or application must be disposed of in a sanitary landfill.

### PHYSICAL CHEMICAL HAZARDS

\*\*\* FLAMMABLE \*\*\*

Keep away from heat and open flame. Store in a cool, dry place away from heat, sunlight and open flame. Close container tightly after use. Keep container closed. Store in a cool dry place away from heat.

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed hereon we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever however caused. HEMPEL'S only obligation shall be to replace such quantity of product proved to be defective.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT.

# HEMPEL

## ANTIFOULING NAUTICAL

### 7680-1221 GR

### ACTIVE INGREDIENTS

TRIBUTYL TIN METHACRYLATE (AS PART OF A POLYMER)  
BIS(TRIBUTYL TIN) OXIDE  
TRIPHENYL TIN FLUORIDE

### INERT INGREDIENTS

TOTAL METALLIC TIN 4.30% BY WEIGHT

CONTAINS PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN

**DANGER**

### PRACTICAL TREATMENT

IF SWALLOWED Drink large quantities of water

\*\*\*\*\*

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate gastric lavage

\*\*\*\*\*

IF IN EYES Flush with plenty of water. Get medical attention

IF ON SKIN Wash with plenty of soap and water. Get medical attention if irritation persists

IF INHALED Remove victim to fresh air. If not breathing, artificial respiration (mouth-to-mouth). Get medical attention

\*\*\* SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS \*\*\*

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL

MADE IN U.S.A. AND SOLD BY

HEMPEL COATINGS (USA), INC.

Curie Avenue, Wallington, NJ 07712

ESTABLISHMENT NO. 10250 N.J.

EPA REGISTRATION NO. 10250-14

NET CONTENTS 5 U.S. GALLONS