

<p align="center"><b>U.S. ENVIRONMENTAL PROTECTION AGENCY</b>  <b>OFFICE OF PESTICIDES PROGRAMS</b>  <b>REGISTRATION DIVISION (73-767)</b>  <b>WASHINGTON, DC 20460</b></p> <p><b>NOTICE OF PESTICIDE:</b> <input type="checkbox"/> REGISTRATION  <input checked="" type="checkbox"/> Reregistration  <i>(Under the Federal Insecticide, Fungicide,  and Rodenticide Act, as amended)</i></p>	<p><b>EPA REGISTRATION</b>  10250-40</p> <p><b>DATE OF ISSUANCE</b>  <b>JUN 8 1989</b></p> <p><b>NAME OF PESTICIDE PRODUCT</b>  Hempel's Antifouling Coating  76-02-511-1003</p>
<p><b>NAME AND ADDRESS OF REGISTRANT (Include ZIP code)</b></p> <div style="border: 1px solid black; padding: 10px; margin: 10px auto; width: 80%;"> <p>Hempel Coatings (USA), Inc.  Foot of Currier Avenue  P.O. Box 3279  Washington, NJ 07057</p> </div>	
<p><b>NOTE:</b> Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p>	
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> <li>1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.</li> <li>2. Before you release the product for shipment bearing the approved labeling submit an amended Confidential Statement of Formula for your product which demonstrates that your product is within certified limits for TBT release rate which places it within the release rate limit imposed by the Organotin Antifouling Paint Control Act (OAPCA) of 1988. Your product was certified as being within the OAPCA limit by the Agency in its letter dated <u>June 6, 1989</u>.</li> <li>3. Submit acceptable prototype specifications and materials for a certification and training program for the use/disposal/and removal of TBT antifouling paints and paint wastes within 180 days from the date of your application for conditional registration. Your application was dated December 10, 1988. The prototype specifications and materials must be submitted by January 20, 1990. The minimum elements to be addressed in the certification and training program are identified in the Agency's Notice at 53 FR 39038.</li> </ol>	
<div style="border: 2px solid black; padding: 5px; text-align: center; margin: 10px auto; width: 200px;"> <b>BEST AVAILABLE COPY</b> </div>	
<p><input type="checkbox"/> ATTACHMENT IS APPLICABLE</p>	
<p><b>SIGNATURE OF APPROVING OFFICIAL</b></p>	<p><b>DATE</b></p>

4. Make the labeling changes listed below before you release the product for shipment bearing the approved label:

a. On the front panel:

- 1) Add the phrase "EPA Registration No. 10250-40."
- 2) Move the "Restricted Use" statement "Restricted Use . . . effective March 1, 1990" from the second paragraph right panel to the top center of the front panel. See item (9a) of "The Label" enclosure.
- 3) Delete the line above the inert ingredient percentage.

b. On the right panel:

- 1) Move the sentence "Users must comply with all applicable OSHA requirements" from the first paragraph left panel to immediately following the sentence "It is unlawful . . . such vessel."
- 2) Move the statement "During . . . sanitary landfill" from the second paragraph left panel to immediately following the "Users must comply with all applicable OSHA requirements" sentence.

c. In the left panel:

- The correct "Physical and Chemical Hazards" statement for a 79 °F flashpoint is "Flammable. Keep away from heat and open flame." The sentences "Close container tightly after use," "Keep container closed," "Store in a cool dry place away from sunlight" may be retained. However, delete the sentence "Use with adequate ventilation" because it appears in the first precautionary statements paragraph.

d. In the first paragraph:

- 1) Replace the sentence "Causes irreversible eye damage" with the sentence "Causes eye irritation."
- 2) Delete the sentence "Remove contaminated clothing, and wash hands before reuse."

5. Submit one (1) copy of your final printed labeling before you release the product for shipment bearing the approved labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product bearing label approved as part of your conditional

3/4

-3-

registration constitutes acceptance of these conditions. All products must bear such a label.

A stamped copy of the label is enclosed for your records. In order to be acceptable, your label must also bear the language as indicated in the changes listed at item 4 above.



John H. Lee  
Product Manager (31)  
Antimicrobial Program Branch  
Registration Division (H7505C)

Enclosures

# **PRECAUTIONARY STATEMENTS** HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER** Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeve cotton shirt, long pants, and hat. Causes irreversible eye damage. May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, mist & dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating or smoking. Use adequate ventilation. While spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash hands before reuse. Users must comply with all applicable OSHA requirements.

## **ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. During and after removal and/or application of new TBT paint, methods must be employed which are designed to prevent release of TBT points into aquatic environment. Following removal of old TBT paint and/or application of new TBT paint, all paint chips and spent abrasives, paint containers, unused paint, and any other waste products from paint removal or application must be disposed of in a sanitary landfill.

## **PHYSICAL, CHEMICAL HAZARDS**

\*\*\* FLAMMABLE \*\*\*

Keep container closed. Use with adequate ventilation. Store in a cool, dry place away from heat, sunlight and open flame. Close container tightly after use. Do not use near heat or open flame.

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed herein we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever however caused. HEMPEL'S only obligation shall be to replace such quantity of product proved to be defective.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT.

# **HEMPEL'S** **ANTIFOULING COMBIC®** **7699-5111 RED**

## **ACTIVE INGREDIENTS**

TRIBUTYL TIN METHACRYLATE (AS PART OF BIS(TRIBUTYL TIN) OXIDE)  
CUPROUS OXIDE

## **INERT INGREDIENTS**

TOTAL METALLIC TIN 2.66% BY WEIGHT

TOTAL METALLIC COPPER 30.35% BY WEIGHT

CONTAINS PETROLEUM-BASED SOLVENTS

ACCEPTED  
with COMMENTS

Label Date:

JUN 8 1989

Under the Federal Insecticide, Fungicide, and Rodenticide Act

Registered under EPA Reg. No.

10250-UN

7.67  
0.57  
33.53  
58.23

100.00

## **KEEP OUT OF REACH OF CHILDREN** **DANGER** **PRACTICAL TREATMENT**

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

\*\*\* SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS \*\*\*

FOR USE IN COMMERCIAL OR BOAT SHIPYARDS ONLY. NOT FOR SALE TO  
USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL

MADE IN U.S.A. AND SOLD BY

HEMPEL COATINGS (USA), INC.

Curie Avenue, Wallington, NJ 07857

ESTABLISHMENT NO. 10250 N.J.

EPA REGISTRATION NO. 10250-UN

NET CONTENTS: 5 U.S. GALLONS

HEMPEL'S ANTIFOULING COMBIC is a organotin formula for the protection of hulls and other sessile marine fouling on the underwater surfaces of global coastal and oceanic vessels.

## **DIRECTIONS**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not use on non-aluminum hulls in length (on deck) except in unit of such vessel. Restrict Aquatic Organisms including commercial applicators and direct supervision of an on-commercial applicator. Restrict APPLICATION INSTRUCTIONS: Sand dry surface with a temperature of 50°F or higher. Apply HEMPEL'S ANTIFOULING COMBIC in pattern, and extended service time between coats of COMBIC be proportionally longer at required for brush, roller, or spray. Do not use HEMPEL'S THINNER promptly cleaned with THINNER. Do not use HEMPEL'S THINNER floated when final coat of COMBIC is applied. Do not expose to the atmosphere.

COMBIC 7699.

## **STORAGE**

Do not contaminate water. Do not dump or discharge.

Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide wastes are toxic.

cide, spray mixture, or run.

If these wastes cannot be dis-

tions, contact your State po-

agency, or hazardous waste

regional office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent)

reconditioning or puncture a

landfill, or by other State

GENERAL

Consult Federal, State, or lo-

approved alternative proced-

**BEST AVAILABLE COPY**