

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeve cotton shirt, long pants, and hat. Causes irreversible eye damage. May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, mist & dust or chips from sanding. Wash thoroughly with soap and water after handling and before eating or smoking. Use adequate ventilation. While spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash hands before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water.

PHYSICAL CHEMICAL HAZARDS

*** FLAMMABLE ***

Keep away from heat and open flame. Store in a cool dry place away from sunlight. Close container tightly after use.

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed hereon we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever however caused. HEMPEL'S only obligation shall be to replace such quantity of product proved to be defective.

HEMPEL'S ANTIFOULING COMBIC 7699 is an advanced self-polishing organotin formula for the prevention of barnacles, algae, and other sessile marine fouling organisms. Recommended for the underwater surfaces of steel vessels operated in all global coastal and oceanic trading waters.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT

ACCEPTED
MAY 22 1992
EPA REG. NO. 10250-40

RESTRICTED USE PESTICIDE

Due to Toxicity to Aquatic Organisms including Shellfish: For Sale only to certified commercial applicators and for use only by certified commercial applicators or by persons under the direct supervision of an on-site (at the work site) certified commercial applicator.

HEMPEL'S ANTIFOULING COMBIC® 7699-5111 RED

ACTIVE INGREDIENTS

TRIBUTYL TIN METHACRYLATE (AS PART OF A POLYMER)	7.67
BIS(TRIBUTYL TIN) OXIDE	0.57
CUPROUS OXIDE	33.53

INERT INGREDIENTS

	58.23

	100.00

TOTAL METALLIC TIN 4.30% BY WEIGHT
TOTAL METALLIC COPPER 30.35% BY WEIGHT
CONTAINS PETROLEUM DISTILLATES

KEEP OUT OF REACH OF CHILDREN DANGER

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS ***

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY NOT FOR SALE TO
USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL
MADE IN U.S.A. AND SOLD BY
HEMPEL COATINGS (USA), INC.
6901 Cavalcade, Houston, TX 77028
ESTABLISHMENT NO 10250 TX
EPA REGISTRATION NO 10250-40
NET CONTENTS: 5 U.S. GALLONS

DIRECTIONS FOR USE

APPLICATION INSTRUCTIONS: Stir thoroughly and apply to a clean dry surface with a temperature above the dew point. Apply over HEMPANYL TAR 1628 or according to specifications. Film thickness and number of coats depend upon hull condition, trading pattern, and extended service life. Allow at least 8 hour dry time between coats of COMBIC 7699 at 20C/63F. Drying time will be proportionally longer at lower temperatures. If chipping is required for brush, roller, conventional spray or airless application, use HEMPEL'S THINNER No. 0808. Equipment should be promptly cleaned with THINNER No. 0808 after use. A ship may be floated when the final coat of paint is dry for 12 hours. Prolonged exposure to the atmosphere will not affect the properties of COMBIC 7699. It is unlawful to use this product on nonaluminum hulled vessels less than 82 feet (25 meters) in length (on deck), except for the outboard motor or lower drive unit of such vessel. Users must comply with all applicable OSHA requirements.

PRACTICAL TREATMENT

IF SWALLOWED: Drink large quantities of water.
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.
IF IN EYES: Flush with plenty of water. Get medical attention.
IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.
IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration (mouth-to-mouth). Get medical aid.

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handled as a hazardous waste). If possible, use all of the contents by application according to label instructions. Manage excess paint, rinseate, and other application wastes in accordance with Federal, State, and local requirements. Consult your State pesticide or Environmental control agency, nearest EPA Regional Office, or the RCRA/Superfund Hotline (800)424-9346 for waste disposal guidance. CONTAINER DISPOSAL

Triple rinse container if intended for recycling or reconditioning. Empty paint containers with small amounts of dried residue must be disposed of in a sanitary landfill (or, if required by Federal, State, or local regulations, handled as a hazardous waste).