

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hats. May be fatal if swallowed or inhaled. Avoid breathing vapor, spray mist, and dust or chips from sanding. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling and before eating or smoking. Use adequate ventilation. While spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL CHEMICAL HAZARDS FLAMMABLE

Keep container closed. Use with adequate ventilation. Store in a cool dry place away from heat, sunlight and open flame. Close container tightly after use. Do not use near heat or open flame.

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed hereon we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever however caused.

HEMPEL'S only obligation shall be to replace such quantity of product proved to be defective.

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT.

HEMPEL'S ANTIFOULING 7660-3180 BLUE

ACTIVE INGREDIENT

CUPROUS OXIDE

INERT INGREDIENTS

TOTAL METALLIC COPPER

ACCEPTED

SEP 18 1989

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended for the purpose of registration under

EPDM BY WEIGHT

CONTAINS PETROLEUM DISTILLATES

WEIGHT PERCENT

45.31

54.69

100.00

HEMPEL'S ANTIFOULING 7660 is an advanced antifouling paint containing cuprous oxide for the prevention of barnacles, algae, coral, and other sessile marine fouling organisms. Recommended for the underwater surfaces of steel vessels operated in all coastal and oceanic waters.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

APPLICATION INSTRUCTIONS Stir thoroughly and apply to a clean dry surface with a temperature above the dew point. Apply over HEMPEL'S TAR 1428 or according to specifications. Film thickness and number of coats depend upon hull condition, trading pattern, and extended service life. Allow at least 10 hours dry time between coats of ANTIFOULING 7660 at 20C/68F. Drying time is proportionally longer at lower temperatures. If thinning is required for brush, roller, conventional spray or airless application, use HEMPEL'S THINNER No. 0808. Equipment should be promptly cleaned with THINNER 0808 after use. The ship may be floated when final coat of paint is dry for 12 hours. Prolonged exposure to the atmosphere may affect the properties of HEMPEL'S ANTIFOULING 7660.

KEEP OUT OF REACH OF CHILDREN

WARNING

PRACTICAL TREATMENT

IF SWALLOWED Drink promptly a large quantity of milk, egg whites, gelatin solution or, if those are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN Probable mucosal damage may contraindicate the use of gastric lavage.

IF IN EYES Flush with plenty of water. Get medical attention if irritation persists.

IF ON SKIN Wash with plenty of soap and water. Get medical attention.

IF INHALED Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

*** SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS ***

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR SALE TO USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL

MADE IN U.S.A. AND SOLD BY

HEMPEL COATINGS (USA), INC
Curie Avenue, Wallington, NJ 07057

ESTABLISHMENT NO. 10250 N J

EPA REGISTRATION NO. 10250-42

NET CONTENTS: 5 U.S. GALLONS

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by using label instructions, contact your State pesticide or environmental control agency, or hazardous waste representative at the nearest EPA regional office.

CONTAINER DISPOSAL

Triple rinse (or equivalent) then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other approved State and Local procedures.

GENERAL

Consult Federal, State, or Local disposal authorities for approved alternative procedures.