!/5

1028	50-56 11/24/2008		·						
	UNITED STATES	EPA Reg. Number:	Date of Issuance:						
	A A A A A A A A A A A A A A A A A A A	10250-56	NOV 2 4 2008						
	U.S. ENVIRONMENTAL PROTECTION AGENCY	Term of Issuance:							
	Office of Pesticide Programs	Expires on December 31 st							
	Antimicrobials Division (7510C) Name of Pesticide Product: Hem								
	1200 Pennsylvania Avenue, N.W. Washington, D.C. 20460	Antifouling Globic 81920 Red 51110							
	NOTICE OF PESTICIDE:								
·	<u>X</u> Registration Re-registration								
	(under FIFRA, as amended)								
	Name and Address of Registrant (include ZIP code):								
	Hempel's Coatings (USA), Inc.								
	600 Conroe Park North								
	Conroe, TX 77803-5056								
	Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce: in any correspondence on this product always refer to the above EPA registration number.								
	On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide,								
	and Rodenticide Act, as amended.								
		Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the							
	environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The accordance of a product under this Act is not to be construed as giving the registrant a right to exclusive use of								
	or to its use if it has been covered by others.								
	This product is conditionally registered in accordance with FIFRA Section 3(c)(7)(A) provided that you:								
	1. Submit and/or cite all data required for reg under FIFRA Section 3(c)(5) when the Agency require products to submit such data; and submit acceptab re-registration of your product under FIFRA Section required by registration review under FIFRA Section	es all registra le responses 4, or as	nts of similar						
	2. Make the following labeling changes:								
	a. Revise the EPA Registration Number to read, EPA Reg. No. 10250-56.								
-	b. Place the appropriate EPA Establishment Number on the product labeling.								
	Signature of Approving Official:	Date:							
·	NIL 'III	· .							
	Allan dell	NOV 2	4 2008						
	Marshall Swindell, Product Manager, Team 33,								
	Regulatory Management Branch I, Antimicrobials Division								

Page 2 EPA Reg. No. 10250-56

3. Submit the protocol and study by June 1st, 2007, of this date stamped of this Notice of Conditional Registration:

Inhalation Monitoring Study* *(Intent: Measure airborne concentration of Sea-Nine 211 during ship painting operations with a representative marine antifoulant (MAF) paint. Prior to initiating the monitoring study submit the study Design for Agency review to ensure compliance with Agency Methodologies for conducting such studies. Also, note that this study is intended to support only the presence of 3% active ingredient in end-use paint formulations).

The data being required as a condition to the registration must be submitted, reviewed, and found to be acceptable by June 1st, 2007. As you are aware, the manufacturer of the active in generating the data to support all end-use products.

This conditional registration will expire automatically on December 31st, 2009. If you fail to satisfy the conditions imposed in this registration, EPA may issue a Notice of Intent to Cancel under Section 6(e) of FIFRA. Your release for shipment of the product constitutes acceptance of these conditions.

4. Submit two copies of the revised final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA Section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the accepted label is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at 703-308-6237.

Sincerely,

Marshall Swindell Product Manager 33 Regulatory Management Branch I Antimicrobial Division(7510C)

Enclosure

81920 Left Panel

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER !

HEMPEL'S

ANTIFOULING

Corrosive. Causes irreversible eye damage and may cause severe skin irritation. Product may be fatal if swallowed. Harmful if inhaled or absorbed through the skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in eyes. Avoid contact with skin. Where skin and eye contact may occur, wear eye protection, such as goggles or face shield, rubber gloves, full body coverings such as coveralls and hat, and other protective clothing such as long sleeved shirt, long pants, and head covering to prevent skin contact. Wash thoroughly with soap and water after handling and before eating or smoking. Remove contaminated clothing and discard; do not reuse. Avoid breathing vapor, mist, dust, or chips from sanding dried paint film. Use adequate ventilation. While spraying paint or sanding boat surface, wear a supplied-air or powered air purifying respirator (PAPR) approved by the National Institute for Occupational Safety and Health (NIOSH) for use with paints and coatings.

Wear a Tyvek hooded coverall or the exact equivalent, coverall beneath the Tyvek hooded coveralls, impervious gloves and impervious footwear that protects the lower leg. Remove contaminated clothing and discard after use, do not reuse. Wash thoroughly with soap and water after handling and before eating or smoking.

ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Wear protective clothing and supplied air respirator in accordance with Precautionary Statements above when handling, painting or removing this paint.

PHYSICAL CHEMICAL HAZARDS: FLAMMABLE

Keep container closed. Use with adequate ventilation. Store in a cool dry place away from heat, sunlight and open flame. Close container tightly after use. Do not use near heat or open flame.

WARRANTY

This labeling must be in the possession of the user at the time of pesticide application. While all HEMPEL products are developed and manufactured with the utmost care, we offer these products with the express understanding that the user will determine the suitability for his intended use and assume all risk and liability in connection therewith. If the product is used other than directed hereon we expressly disclaim any responsibility for its use, handling, storage, result obtained, injury or indirect or consequential damages of any nature whatsoever caused. THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE FOR THIS PRODUCT. Hempel's only obligation shall be to replace such quantity of product found to be defective.



NOV 2 4 2008

April 200

ACTIVE INGREDIENTS Cuprous Oxide 4,5,dichloro-2-octyl-3(2H)-isothiazolone INERT INGREDIENTS TOTAL TOTAL METALLIC COPPER 33.40 % H CONTAINS PETROLEUM DISTILLATES KEEP OUT OF REACH OF CHILDREN DANGER FIRST AID	d 51110 36.10 % 1.86 % 62.04 % 100. 00 % By Weight
Cuprous Oxide 4,5,dichloro-2-octyl-3(2H)-isothiazolone INERT INGREDIENTS TOTAL TOTAL METALLIC COPPER 33.40 % E CONTAINS PETROLEUM DISTILLATES KEEP OUT OF REACH OF CHILDREN DANGER FIRST AID	1.86 % 62.04 % 100. 00 % By Weight
FIRST AID	
FIRST AID	
ve open and rinse slowly and gently with water for 15-20 minutes. > 5 minutes, then continue rinsing eye. > Call a poison control center of Call a poison control center or doctor immediately for treatment advi do so by a poison control center or doctor. > Do not give any liquid a to an unconscious person. HING: > Take off contaminated clothing. >Rinse skin immediately w poison control center or doctor for treatment advice. person to fresh air. > If person is not breathing, call 911 or an ambu eferably mouth-to-mouth, if possible. > Call a poison control center	or doctor for treatment ce. > DO NOT induce to the person. > Do no with plenty of water fo lance, then give
	5 minutes, then continue rinsing eye. > Call a poison control center of Call a poison control center or doctor immediately for treatment advided so by a poison control center or doctor. > Do not give any liquid a to an unconscious person. HING: > Take off contaminated clothing. >Rinse skin immediately we poison control center or doctor for treatment advice. person to fresh air. > If person is not breathing, call 911 or an ambu

1

****SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY SATEMENTS****

FOR USE IN COMMERCIAL OR NAVY SHIPYARDS ONLY. NOT FOR SALE FOR USE OR STORAGE BY PRIVATE APPLICATORS OR MARINA PERSONNEL. NOT FOR USE ON STATIONARY STRUCTURES.

MADE IN USA - Sold by: HEMPEL (USA) INC. Conroe, Texas 77303 EPA Est. No. 10250-TX-1 EPA Reg. No.: 10250-56

81920 - Right Panel

2008....... Functicio, apa Accessantes Actas amanchad, and the set states

10250-56 registered under EFA Reg. No.

HEMPEL'S ANTIFOULING GLOBIC 81920 is an advanced antifouling paint containing cuprous oxide and an organic bioactive material for the prevention of barnacles, algae, coral, and other marine fouling organisms. Recommended for the underwater surfaces of steel, fiberglass and wood vessels operated in all navigable waters where tin containing paints are not suitable. May be applied to aluminum hulled vessels painted with proper barrier coating.

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

APPLICATION INSTRUCTIONS:

For application by brush, roller, or airless spray equipment.

This product is to be used on the underwater surfaces of steel, fiberglass and wood vessels operated in all navigable waters. Antifouling paint is to be applied to newly built vessels and in the repair and maintenance of such vessels as needed. Stir thoroughly and apply to a clean dry surface with a temperature above the dew point. Apply over previous coating (examples: primer, sealer, antifouling paint) or according to the written painting specifications developed for the particular vessel. Film thickness (measured by a film thickness gauge) and the number of coats required to be applied depend upon vessel hull conditions, trading pattern, and designed extensions of painted surface service life. Allow at least 10 hours dry time between coats of this product at 20C / 68F. Drying time is proportionally longer at lower temperatures. If thinning is required for brush, roller, conventional spray or airless application, use HEMPEL'S THINNER 08080. Equipment should be promptly cleaned with THINNER 08080 after use. The ship may be floated when final coat is dry for 12 hours. Prolonged exposure to the atmosphere may effect the properties of this product.

STORAGE and DISPOSAL

PROHIBITIONS: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL:

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by using label instructions, contact your State pesticide or environmental control agency, or hazardous waste representative at the nearest EPA Regional Office.

CONTAINER DISPOSAL:

Triple rinse (or equivalent) then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and Local procedures.

GENERAL:

Consult Federal, State, or Local authorities for approved alternative procedures.

Meets MACT for Shipbuilding / Repair under NESHAP regulations of the Clean Air Act Amendments of 1990. VOHAP / VOC content (grams/liter): < 400 VOHAP / VOC content (grams / liter solids): < 765

Net	Volume value	Gallons	Lot Number / No de lot / Numero de lote:	Lot nur

DOT Shipping Description

Reserved

ımber