MAQUAT TC-76 — 10% is: Economical - Efficient - Stable

MAQUAT TC-76 — 10% is compatible with all swimming pool chemicals and is non-injurious to metal, paint, plastic, and tile.

MAQUAT TC-76 — 10% when used as directed, will improve the appearance and cleanliness of the pool, or water cooling system.

MAQUAT TC-76 — 10% prevents unsightly growths of algae.

MAQUAT TC-76 — 10% may be stored for prolonged periods of time without losing its effectiveness or strength.

MAQUAT TC-76 — 10% requires no special equipment for treating water. May be added directly to the pool in any spot or added to the water-circulation equipment.

MAY 12, 1973 NET CONTENTS

CONTENTS

10324-15

# **MAQUAT TC76—10%**

E. P. A. Reg No. 10324 - 15 Concentrated Algaecide

MAQUAT TC-76 - 10% for Control of Algae and Algal Slime Growth in Swimming Pools and Water Cooling Systems.

*ACTIVE INGREDIENT:	
n-Alkyl (60% C <sub>14</sub> , 30% C <sub>16</sub> , 5% C <sub>12</sub> & 5% C <sub>18</sub> ) dimethyl benzyl ammonium chloride	8.4%
n-Dialkyl (60% C <sub>14</sub> , 30% C <sub>16</sub> , 5% C <sub>12</sub> & 5% C <sub>18</sub> ) methyl benzyl ammonium chloride	1.6%
INERT INGREDIENT:	00.00/
Water	90.0%
*Weight approx.	100.0%
8 Ibs./gallon DANGER	

## Keep Out Of Reach Of Children

Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

#### **PRECAUTION**

This product is toxic to fish. Do not discharge treated effluent into lakes, streams or ponds.

### FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink **promptly** a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

#### NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

Do not reuse empty container - When empty, rinse and destroy.

# **Mason Chemical Company**

A Division of Schrade Batterson Co.

5253 WEST BELMONT AVENUE CHICAGO, ILLINOIS 60641 312/ 282 0200

# DIRECTIONS FOR USE IN SWIMMING POOLS

## (To A Clean Pool)

One gallon MAQUAT TC-76 - 10% to each 50,000 gallons of water or ratio thereof. If Algae growth is visible apply the initial dose. Vacuum pool after 24 hours to remove dead algae. If algae is still visible repeat dose as necessary until pool is free of visible algae.

#### **CONTINUED APPLICATION:**

One quart MAQUAT TC-76 - 10% in 50,000 gallons of water every 3-5 days or as needed to maintain 2 ppm active. Quarternary Test Kits are available for this use.

#### **BOOSTER APPLICATION:**

One quart MAQUAT TC-76 - 10% in 50,000 gallons after a heavy or prolonged rainfall or when there is a heavy bathing load.

The above directions should be followed even when the pool is not in use.

### DIRECTIONS FOR USE IN RECIRCULATING WATER COOLING TOWERS

### INITIAL APPLICATION

(To A Clean System)

The dose should be poured into the sump of a system which is clean or in which growth is first noticed.

26.25 to 51.25 fluid ounces (20 to 40 ppm on an active quaternary basis) per 1000 gallons of contained water. When heavy algae growth is present, system will have to be cleaned manually.

#### SUBSEQUENT APPLICATION:


6.65 to 19.25 fluid ounces (5 to 15 ppm on an active quaternary basis) per 1000 gallons of contained water.

The above directions are to be followed twice weekly or as needed.

If algae growth is noticeable, apply the imital dose.

KEEP FROM FREEZING

FAAQUAT	
	9/_
MG2525-50	
Concentrated	
Germicide - Disinfectant - Saniti	zer
U.S.D.A. Reg. No. 10324 - 17	
ACTIVE INGREDIENTS: D-Alkyl (60% C14, 30% C16, 5% C12, 5% C18)	
dimethyl benzyl ammonium chloride	. 25.0%
LAIkyl (50% C12, 30% C14, 17% C16, 3% C18	
dimethyl ethylbenzyl ammonium chloride	25.0%
MERT INGREDIENTS:	. 50.0%
OFF MACHINE TERMINAL DECCHI	100,0%
SEE HAQUAT TECTRICAL BROKETU	<b>**********************</b> **************
THEEL-REP OIL OL MYCH ME CHA	
SEE FIRST AND Q OTHER PRECAUTIONS ON PHIS	T PANEL



# Mason Chemical Company

A Division of Schrace Eatterson Co.

5253 WEST BELMONT AVENUE CHICAGO, ILLINOIS 60641 312/ 282-0200

## DANGER

# KEEP OUT OF REACH OF CHILDREN. Corrosive.

Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

### FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

### NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

**NET CONTENTS** 

KEEP FROM FREEZING
For Manufacturing Use Only