

10324-122

03-22-2012

1/4

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, D.C. 20460



United States  
Environmental Protection  
Agency

Office of Pesticide Programs

Ms. Elizabeth Tannehill  
Mason Chemical Company  
721 W. Algonquin Road  
Arlington Heights, IL 60005

MAR 22 2012

Subject: Maquat EPA Registration #'s;  
10324-87 Maquat MC 1412-40%-S&W, 10324-122 Maquat MC 1412-PS,  
10324-175 Maquat MC 1412-20%-S&W, 10324-200 Maquat MC 1412-20%-FC,  
10324-203 Maquat MC 1412-40%FC

Amendment Date: January 20, 2012  
Received Date: January 26, 2012

Dear Ms. Tannehill,

The following amendments, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, are acceptable subject to the conditions listed below:

- Addition of storage and disposal language

**Conditions**

Revise the label as follows:

- For Swimming Pool use And Decorative Fountains and Pools in non-refillable containers up to and including 5 gallons revise language to read; "Do not reuse empty container. *Triple rinse (or equivalent)*. Wrap and discard in trash (or recycle)"
- For Use on Non-refillable containers with commercial/industrial uses (for use on containers greater than 5 gallons): revise the Container Disposal section to read:
  - a) "Nonrefillable container. Do not reuse this container to hold materials other than pesticide or diluted pesticide (rinsate). *Triple rinse container (or equivalent) after emptying*. Offer for recycling...."
  - b) "Nonrefillable container. Do not reuse or refill this container. *Triple rinse container (or equivalent) promptly after emptying*. Wrap empty container and put in trash"


CONCURRENCES

SYMBOL	SURNAME	DATE					

**General Comments**

Stamped copies of the accepted labels are enclosed. Submit one (1) copy of your final printed labels before distributing or selling these products bearing the revised labeling. Should you have any questions concerning this letter, please contact Velma Noble at (703) 308-8233 or Jamil Mixon at (703) 308-8032.

Sincerely,



Velma Noble  
Product Manager (31)  
Regulatory Management Branch I  
Antimicrobials Division (7510P)

Enclosure: Stamped Label

**CONCURRENCES**

SYMBOL							
SURNAME							
DATE							

**PRECAUTIONARY STATEMENTS  
 HAZARDS TO HUMANS  
 AND DOMESTIC ANIMALS**

**DANGER. Keep Out of Reach of Children.** Corrosive. Causes irreversible eye and/or skin burns. May be fatal if swallowed. Harmful if inhaled. Avoid vapor or spray mist. Harmful if absorbed through skin. Do not get into eyes, on skin or on clothing. Wear goggles or face shield, protective clothing, and rubber gloves. Wash thoroughly with soap and water after handling and before eating, drinking, using tobacco, or using the toilet. Remove contaminated clothing and wash clothing before reuse.

*(If container is larger than 5 gallons, the following statement must appear on the label)*

**ENVIRONMENTAL HAZARD**

This pesticide is toxic to fish, aquatic invertebrates, oysters, and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

*(For containers up to and including 5 gallons, use the following environmental hazard)*

**ENVIRONMENTAL HAZARD**

This product is toxic to fish.

**PHYSICAL OR CHEMICAL HAZARDS**

Do not mix with soap, anionic detergents or oxidizers.  
 Do not use or store near heat or open flame.

**First Aid**

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. **IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. **IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. **IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. **IF INHALED:** Remove victim to fresh air. If person is not breathing, call 911 or an ambulance. Then give artificial respiration, preferably mouth-to-mouth if possible. **NOTE: COMMENTS:** Probable mucosal damage may occur; irrigate gastric lavage in EPA Letter Dated:

**MAR 22 2012**  
 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 10324-122

For Control of Algae and Algae Slime Growth in Swimming Pools, (Outside) Spas/Whirlpools/Hot Tub Baths, Industrial and/or Commercial Recirculating Cooling Water Towers, Retort Cooling Systems, Auxillary Water and Waste Water Systems and Water Cooling Systems, Oil Field Water Flood/Salt Water Disposal Systems, and Mollusks in Once Trough Fresh and Sea Water Cooling Systems and Mold, Mildew and Fungi in Sap Stains and Wood Preservatives. Controls bacteria and fungal slimes in Pulp, Paper mills and Paper Manufacturing. ("Containedized", "Outside" description, and the use sites that include Retort Water Systems, Retort Water Systems, Auxillary Water and Waste Water Systems and Water Cooling Systems, Oil Field Water Flood/Salt Water Disposal Systems, Sap Stain and Wood Preservative, pulp, paper mills and paper manufacturing not for use in California.)

(Product of USA) (Made in the USA)

**ACTIVE INGREDIENTS**

Alkyl (50% C<sub>14</sub>, 40% C<sub>12</sub>, 10% C<sub>16</sub>) dimethyl benzyl ammonium chloride ..... 80.00%  
**INERT INGREDIENTS:** ..... 20.00%  
**TOTAL:** ..... 100.00%

Weight: Approx. 8 lbs./gallon

**KEEP OUT OF REACH OF CHILDREN**  
**DANGER PELIGRO**

See left (back) (side) (right) panel (of label) (below) for additional precautionary statements and first aid statements.

*(Note to Reviewer: This information has been verified per DOT regulations. It is NOT required to be on the label but is being requested by a customer.)*

**Transportation Information**

**DOT Hazard Class:** 8 Corrosive  
**DOT Proper Shipping Name:** Disinfectant Liquid Corrosive (Quaternary Ammonium Compound), 8, UN1903, PGII

**PELIGRO: SI NO PUEDE LEER EN INGLES, PREGUNTE A SU SUPERVISOR SOBRE LAS INSTRUCCIONES DE USO APROPIADAS ANTES DE TRABAJAR CON ESTE PRODUCTO.**

**DANGER: IF YOU CANNOT READ ENGLISH, ASK YOUR SUPERVISOR TO EXPLAIN THE APPROPRIATE DIRECTIONS FOR USE BEFORE WORKING WITH THIS PRODUCT.**

(Manufacturing and/or Lot no. Date:)

• **80% Concentration**

• **Kills and prevents all type of Algae**

This formulation (Maquat® MC1412-PS) is for use in:

- Industrial and/or commercial recirculating cooling water towers.
- Once through water cooling systems. (Not for use in CA)
- Paper mills and paper mill process water systems. (Not for use in CA)
- Oil field water flood or salt water disposal system and fracturing fluids. (Not for use in CA)
- Oil field injection and waste water. (Not for use in CA)
- Gas production and transmission pipelines and systems. (Not for use in CA)
- Gas storage wells and systems. (Not for use in CA)
- Pipeline pigging and scraping operations. (Not for use in CA)
- Drilling, completion and workover fluids systems. (Not for use in CA)
- Packer fluids. (Not for use in CA)
- Hydrotesting (Not for use in CA)

This product has been designed specifically for control of sulfate-reducing bacteria (SRB) that contribute to souring, the production of sulfide, and abiotic corrosion in water cooling systems, paper mill process water systems, oil field systems, gas production and transmission pipelines and systems. (Not for use in CA)

A microbicide for use in controlling sulfate-reducing bacteria and slime forming bacteria in oil well drilling, oil field processing applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields and equipment; such as steam-injection water holding tanks, flood water, injection water, holding pond water, disposal-well water, water holding tanks, fuel storage tanks and related refinery and oil field closed, industrial recirculating water handling systems. (Not for use in CA)

A highly effective microbicide for use in controlling bacteria including slime forming bacteria and sulfate-reducing bacteria (SRB) and fungi (yeast and molds) and algae in air washers and industrial scrubbing systems, recirculating cooling and process water systems including those that contain reverse osmosis membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including wastewater sludge and holding tanks, and in paper mills and paper mill process water systems and water based coatings for paper and paperboard. (Not for use in CA)

This product is efficient and stable in use dilution.

This product is compatible with most chemicals used in pool water and will not damage tile, concrete, metal or plastics.

This product keeps pool water free and sparkling, clear of visible green and blue-green algae, slime and green brown colors.

This product improves filter operation and reduces need for other chemicals.

This product imparts a pleasant feel to swimming pool water.

This product is formulated to complement swimming pool water being treated with normal chlorine systems. It is especially effective against growth of algae and being non-volatile, aids in maintaining pool water clarity and sparkle. The residual effectiveness of this algacide tends to stabilize the total chemical treatment system.

This product is compatible with most chemicals normally used in swimming pool maintenance. However, in its concentrated form, this chemical must not come in contact with high concentrations of chlorine or any other oxidizer. **DO NOT MIX THIS PRODUCT AND CHLORINE OR ANY OTHER OXIDIZER TOGETHER** before adding to the pool. These chemicals must be handled separately.

This product was formulated to complement most swimming pool sanitizers. This product is not a stand-alone product. It must be used with either halogen based or non-halogen based pool sanitizers. This product supports your overall pool chemical maintenance program, offering a residual effectiveness that protects your pool against algae formation while keeping your pool water sparkling clear. This product protects the unattended pool when you're away (refer to Vacation Treatment section under Directions For Use).

### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Please read entire label and use strictly in accordance with precautionary statements and directions.

Do not use water containing residues from use of this product to irrigate crops for food or feed.

**Note to reviewer:** This paragraph will be used only for Once Through Cooling Systems

Use of the product in either public/municipal or single or multiple family private/residential potable/drinking water systems is strictly prohibited. Use of the product in any cooling water system that discharges effluent within ¼ mile of either a public/municipal or single or multiple family private/residential potable/drinking water intake is strictly prohibited.

### INDUSTRIAL WATER TREATMENT

This product aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, influent systems such as flow through filters and lagoons, industrial water scrubbing systems and brewery pasteurizers. (Not for use in CA)

### INDUSTRIAL AND/OR COMMERCIAL RECIRCULATING COOLING WATER TOWERS AND RETORT WATER SYSTEMS, ONCE THROUGH COOLING SYSTEMS, EVAPORATIVE CONDENSERS, HEAT EXCHANGE WATER SYSTEMS, INFLUENT SYSTEMS (Retort Water Systems not for use in California)

1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.
3. **Method Of Application:**
  - a. **INTERMITTENT OR SLUG METHOD**

**Initial Dose:** When the system is noticeably fouled, apply 3.2 to 6.4 fluid ounces (20 to 40 ppm on an active quaternary basis) per 1000 gallons of water in the system. Repeat until control is achieved.

**Subsequent Dose:** When microbial control is evident, add 0.8 to 2.4 fluid ounces (5 to 15 ppm on an active quaternary basis) per 1000 gallons of water in the system twice weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.
  - b. **MODIFIED INTERMITTENT METHOD**

**Initial Dose:** When the system is noticeable fouled, apply 3.2 to 6.4 fluid ounces (20 to 40 ppm on an active quaternary basis) per 1000 gallons of water

in the system. Apply half of this initial dose when half of the water in the system has been lost by blowdown.  
**Subsequent Dose:** When control of microbial growth is evident, apply 0.8 to 2.4 fluid ounces (5 to 15 ppm on an active quaternary basis) per 1000 gallons of water in the system. Apply half of this subsequent dose when half of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

(OR)  
**INTERMITTENT OR SLUG METHOD**

When this treatment is required, add this product at the rate of 3.2 to 6.4 ounces per 1000 gallons of water already in the system, or being added to the system, for 4 to 8 hours, 1 to 4 times per week or as needed to achieve the desired level of control. When control is obtained, add this product at the rate of 0.8 to 2.4 ounces per 1000 gallons of water in the system.

**c. CONTINUOUS FEED METHOD**

**Initial Dose:** When the system is noticeably fouled, apply 3.2 fluid ounces (20 ppm on an active quaternary basis) per 1000 gallons of water in the system.  
**Subsequent Dose:** Maintain this treatment by starting a continuous feed of 0.8 fluid ounces (5 ppm on an active quaternary basis) per 1000 gallons of water lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

**ONCE THROUGH FRESH AND SEA WATER COOLING SYSTEMS**

(Use in Sea water cooling systems not allowed in CA)

- Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
- Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.

**3. Method Of Applications:**

**a. INTERMITTENT OR SLUG METHOD**

**Initial Dose:** When the system is noticeably fouled, apply 0.16 to 1.6 fluid ounces (1 to 10 ppm on an active quaternary basis) per 1000 gallons of water based on system flow rates. The minimum treatment must be 6 to 24 hours. Repeat until control is achieved. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum of 5 ppm clay to 1 ppm product.

**Subsequent Dose:** When microbial control is evident, add 0.08 to 0.8 fluid ounces (.5 to 5 ppm on an active quaternary basis) per 1000 gallons of water based upon system flow rates on a as needed basis to maintain control. Frequency of feed must be tied to an in plant monitoring program for macro fowling growth. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum ratio of 5 ppm clay to 1 ppm product.

**TO DEACTIVATE:** Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. Deactivation must occur prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

(OR)

**ONCE THROUGH FRESH AND SEA WATER COOLING SYSTEM**

(Use in Sea water cooling systems not allowed in CA)

- Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
- Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.

**3. Method Of Applications:**

- Wear safety glasses, rubber gloves and impervious apron.
- To reduce foaming, mix 2 parts of water to 1 part of this product.
- Add product directly from drum or add the product at a point where it will be mixed uniformly.
- Use 0.15 to 1.5 fluid ounces (1-10 ppm on an active quaternary basis) per thousand gallons.
- Do not discharge without performing proper deactivation. To perform deactivation use Bentonite Clay. The minimum ratio to be used is 5 ppm of clay to 1 ppm of product.
- Do not use product more than 4 times per year.
- Treatment time cannot exceed 120 hours/application.
- Avoid oxidizers and reducing agents. Product is cationic and must not be mixed with soap or anionic surfactants.

**TO DEACTIVATE:** Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. Deactivation must occur prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

**OIL FIELD & GAS PRODUCTION TREATMENT (Not for use in CA)**

Specific treatment requirements vary among oil and/or gas field sites and subsystem components. The Primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction (low pressure) side of pumping equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system fouling. OR

Specific treatment requirements vary among oil and/or gas field sites and subsystem components. Oil field fluids and subsystems most commonly requiring microbial contamination control are raw water sources, separators, ballast, storage and mixing tanks, screens, surface injection equipment, production equipment (such as injection and production piping casting, completion and valving) and the formation itself. The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction (low pressure) side of pumping equipment or similar device. This product can be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system found.

**OIL FIELD WATER FLOOD OR SALT WATER DISPOSAL SYSTEMS AND FRACTURING FLUIDS**

This product must be added to the water flood or salt water disposal system at a point of uniform mixing.

- For the control of slime forming and sulfate reducing bacteria in oil field water flood or salt water disposal systems, add 5 - 10 ppm (active) of this product (0.6 - 1.18 gallons per 3,000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.
- For intermittent use, dose at rate of 5 - 20 ppm (active) of this product (0.6 - 2.36 gallons per 3,000 barrels of water) for 4 to 8 hours per day, one to four times a week as needed to maintain control.

3. For treatment of flow back return water (Post Hydraulic Fracturing - Dose at a rate of 5-20ppm active of this product (0.6 - 2.36 gallons of this product per 3,000 barrels of water) for 4 to 8 hours per day, one to four times a week as needed to maintain control.

#### OILFIELD INJECTION AND WASTE WATER

This product must be added to the water handling system at a point of uniform mixing such as the area of addition of make-up water to the holding tank.

#### Method of application:

1. **CONTINUOUS INJECTION:** Add this product at 30 ppm active (4.5 fluid ounces per 1000 gallons of water) when system is noticeably fouled. When microbial control is evident, add this product at 15 ppm active (2.25 fluid ounces per 1000 gallons of water) to maintain control.
2. **BATCH TREATMENT:** Add this product at 180 ppm active (27 fluid ounces per 1000 gallons of water) over a period of 4 - 6 hours one or more times per week when the system is noticeably fouled. When microbial control is evident, add this product at 90 ppm active (13.5 fluid ounces per 1000 gallons of water) over a period of 4 - 6 hours one or more time per week.

OR

For use in oil field and/or petrochemical water subsurface injection systems of secondary and/or tertiary oil recovery systems to reduce the number of anaerobic bacteria, aerobic bacteria, sulfate-reducing bacteria.

1. **DOSING LOCATION** (site of use): This product is to be applied at a point in the recovery system where it will be uniformly mixed, such as at the screens, storage tanks and other mixing device locations.
2. **DOSING CONDITIONS:** This product should be applied when the system is in jeopardy of being affected. Badly fouled systems must be cleaned before treatment is begun.
3. **EQUIPMENT USED:** Use the injection pump to apply the product.
4. **USE LIMITATIONS:** Dependent upon pH, temperature and salt content, adjust according to conditions found at the site as needed to maintain control.
5. **DOSAGE APPLICATIONS:**

#### a. SLUG METHOD

**Initial Dose:** When the system is noticeably fouled, apply 9.6 ounces (60 ppm active ingredient) of this product per 1000 gallons of water in the system. Apply for 3 to 8 hours daily until control is achieved.

**Subsequent Dose:** When microbial control is evident, add 4.8 ounces (30 ppm active ingredient) of this product per 1000 gallons of water in the system daily or as needed to maintain control.

#### b. INTERMITTENT DOSAGE

**Initial Dose:** When the system is noticeably fouled, apply 9.6 ounces (60 ppm active ingredient) of this product per 1000 gallons of water in the system. Apply for 3 to 8 hours daily until control is achieved.

**Maintenance Dose:** When control of microbial growth is evident, apply 4.8 gallons (30 ppm active ingredient) of this product per 1000 gallons of water in the system daily or as needed to maintain control.

#### c. CONTINUOUS FEED METHOD

**Initial Dose:** When the system is noticeably fouled, apply 2.4 ounces (15 ppm active ingredient) of this product per 1000 gallons of water in the system.

**Subsequent Dose:** Maintain this treatment by starting a continuous feed of 2.4 ounces (15 ppm active ingredient) of this product per 1000 gallons of water daily or as needed to maintain control.

#### OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS

For the control of sulfate-reducing bacteria and slime forming bacteria, this product must be added at a point in the production or transmission pipeline via direct injection where uniform. The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate applications, it is desirable to dilute the product with an appropriate solvent immediately before use. The concentration in the solvent must not fall below an active concentration range of 500 to 5,000 ppm based on the volume of water in the pipeline. Injections to the system must be weekly, or as needed to maintain control.

#### GAS STORAGE WELLS AND SYSTEMS

Individual injection wells must be treated with a sufficient quantity of this product to produce concentration of 65-1000 ppm (on an active quaternary basis) when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injection must be repeated yearly or as needed to maintain control

#### PIPELINE PIGGING AND SCRAPING OPERATIONS

Add this product to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper and the trailing pig). Sufficient product is added to produce an effective concentration of 75 - 500 ppm on an active quaternary basis (1.2 to 8 ounces per 100 gallons of water) depending on the length of the pipeline and the severity of the biofouling.

#### DRILLING, COMPLETION AND WORKOVER FLUIDS SYSTEMS

This product is to be applied to these fluid systems at a point of uniform mixing, such as a circulating holding tank and other mixing device locations.

**Initial treatment:** Add 65 - 1000 ppm (on an active quaternary basis) of this product (0.25 to 4 gallons of this product per 100 barrels) to a freshly prepared fluid. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

**Maintenance dosage:** Add 65 - 1000 ppm (on an active quaternary basis) of this product (0.25 to 4 gallons of this product per 100 barrels) to the fluid. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

#### PACKER FLUIDS

This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank and other mixing device locations. Add 0.25 to 4 gallons (65 - 1000 ppm active quaternary basis) of this product per 100 barrels of packer fluid. This product is applied to a freshly prepared fluid. Levels for effective control will vary depending on conditions at the site and the severity of the contamination. Seal the treated packer fluid in the wall between the casing and the production tube.

#### HYDROTESTING

Treat water in the hydrotest pipelines or vessels with 65 - 1000 ppm on an active quaternary basis (10.25 to 159.25 ounces per 1000 gallons of water) of this product, depending on the water quality and length of time the equipment will remain idle.

#### AUXILIARY SERVICE WATER AND WASTE WATER SYSTEM

This product is effective for the control of odor-forming and slime-forming bacterial, fungi and algae in auxiliary service water systems such as fire protection systems and pump

or screen bays, water waste systems such as storage tanks, storage piles, associated piping, setting ponds or lagoons, transport spillways or canals and disposed wells.

Add 5 - 180 ppm (active) of this product (0.6 - 21.25 gallons per 3,000 barrels of water) continuously. This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile. The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination. Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing.

#### **PULP AND PAPER MILLS** (Not for use in CA)

##### **SLIMICIDE APPLICATIONS**

This product can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination. Apply this product intermittently or continuously depending on mill conditions to the paper making system at a point of uniform mixing such as a the beaters, thin or thick stock chests, broke chest pump, save-all tank, process tank or whitewater tank. Do not use to treat paper or paperboard which will contact food.

**Initial Dose:** When system is noticeably contaminated, add 0.125 to 25 gallons of this product per 100,000 gallons of whitewater to be treated (1.0 to 200 ppm of product) as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems must be boiled out prior to initial treatment.

**Subsequent Dose:** When microbial control is evident, add 0.125 to 12.5 gallons of this product per 100,000 gallons of whitewater to be treated (1.0 to 100 ppm of product) as necessary to maintain control.

##### **CONTROL OF BACTERIAL, FUNGI/MOLD AND ALGAE ON PULP, PAPERBOARD & WET LAP**

This product is used to inhibit fungal growth, which causes discoloration, odor and degradation of paper, paperboard or wet lap. Application of this product must be made at a point in the system where mixing action is good. Application can also be made at the size press or water box. Apply at a rate of 0.4 to 80 pounds of this product per ton (dry basis) of pulp or paperboard produced.

**Dosing Application:** This product may be drip fed continuously from the drum, diluted and showered to the wet sheet or fed by suitable pumps.

For inhibition of wet lap or sheet pulp this product must be applied to the dewatered pulp surface via applicator rolls or showers. Application can also be made at the size press or water box.

##### **SAP STAIN**

For the control of mold and fungus on green or freshly cut lumber. May be used in a dip or spray application. Before use, dilute at rate of 25-100 gallons of water per gallon of this product. Seasonal variations in storage and shipping conditions, species and condition of wood must be considered in a manner that ensures that all surfaces are uniformly treated.

For best results, green wood must be treated immediately at least within twenty-four hours after cutting or sawing. Mold and fungus growth begins immediately after cutting so delayed treatment is much less effective and requires increased chemical concentration. Green, untreated lumber must not be used for stickers.

Freshly treated lumber must not be allowed to remain unprotected in heavy rains. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of the anti-stain solution.

Treated lumber must be stored under cover, or indoors, or at least 100 feet from any pond, lake, stream, wetland or river to prevent possible runoff of the product into the waterway. Treated lumber stored outdoors within 100 feet of a pond, lake, stream, wetland, or river must be either covered with plastic or surrounded by berm to prevent surface water runoff into the nearby waterway. If a berm is used around the site, it must consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

##### **WOOD PRESERVATIVES**

This product is a concentrated biocide for use as a wood preservative. When used as directed, this product will protect treated wood articles from the destructive attack of fungi, mold, mildew and both Reticulitermes and Formosan species of termites. Treatment can be done by pressure, double vacuum, dip, brush and/or spray, although dip, brush and spray can not be used for protection against termites. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood applications, wood shingles, posts and other articles to be used in above ground applications. Dilute this product in either water or mineral spirits solution to product a 0.5% to 3.0% active solution. This formulation is to be used for both pressure and double vacuum treatment.

(OR)

This product will protect treated wood articles from the destructive attack of fungi, mold or mildew. Treatment can be done by pressure or double vacuum. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood shingles, posts and other articles to be used in above ground applications.

(OR)

Treatment can be done by brush or spray for wood shingle applications, and by pressure, double vacuum or dip method for other wood products. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood shingles, and posts.

This product can be used in combination with other EPA registered organic and inorganic wood preservatives or it can be used alone.

##### **MAQUAT® MC1412-PS**

Dilute this product in either water or mineral spirits (or Sentry GoldSeal™) to produce a 0.5% to 3.0% active quaternary ammonium compound solution.

Percent Active Quat Solution	Ounces of this product per gallon
0.5	0.80
1.0	1.60
1.5	2.40
2.0	3.20
2.5	4.00
3.0	4.80

To find the ounces of this product per gallon for other dilutions take the percent active desired and divide by 0.625.

##### **MAQUAT MC1412-PS AND COPPER COMPOUNDS**

Mix this product with water and either (ACQ-C2 EPA Reg. No. 10465-36 or ACQ-C EPA Reg. No. 10465-33) (NW 100-C, EPA Reg. No. 3008-87 or NW 200-C, EPA Reg. No. 10465-33-3008). Refer to the product labels for (ACQ-C and ACQ-C2) (NW 100-C and NW 200-C) for precise mixing instructions. **This product may only be used in combination with copper compounds in pressure treatment applications.**

### MAQUAT MC1412-PS AND BORATES

Mix this product and either (Disodium Octaborate Tetrahydrate) Wood Bor, EPA Reg. No. 3008-61, Envirotech Insecticide, EPA No. 65705-1, Timbersaver, EPA Reg. No. 71916-1, TimberSaver PT, EPA Reg. No. 71916-1-10465, Tim-Bor, EPA Reg. No. 1624-39, or Cellu-Treat DOT Wood Preservative, EPA Reg. No. 64405-8, Bor-Ram, EPA Reg. No. 72304-10 or Borathor Max PT, EPA Reg. No. 81824-11 in water. Refer to the product labels for precise mixing. **This product may only be used in combination with the above borates in pressure treatment or dip treatment applications.**

Mix this product and Lum-Bor, EPA Reg. No. 19713-286 in water. Refer to the product label for precise mixing instructions. **This product may only be used in combination with the above borate in brush or spray applications.**

Mix this product and BORA-CARE, EPA Reg. No. 64405-1 in water. Refer to the product label for precise mixing instructions. **This product may only be used in combination with the above borate in dip treatment applications.**

### MAQUAT MC1412-PS AND PROPICONAZOLE

Mix this product with Woodlife P, EPA Reg. No. 1409-65 and dilute with either water, mineral spirits or other light organic solvent to produce a 0.5 to 3.0% quaternary ammonium compound solution. Follow the instructions on the Woodlife P label for the appropriate concentration of propiconazole. **PLEASE NOTE THAT THIS FORMULATION CAN ONLY BE USED FOR DIP TREATMENT.**

### PRESSURE TREATMENT

Place the wood article to be treated into the pressure cylinder and seal unit. Treat the wooden articles using the pressure treatment procedures consistent with the equipment being used and standard treatment practices. Treatment conditions must be such as to produce a 0.1 to 0.6 lb./cu. foot retention in the treatment article. Such treated wood is to be used for above ground uses only.

### DOUBLE VACUUM

Stack the wooden articles to be treated in the treatment vessel so that the preservative solution will have access to all sides of the articles. Seal the vessel. Reduce the pressure within the vessel to -10 inches for 5 minutes. Cover all the articles with preservative solution. Allow the pressure to return to atmospheric conditions and discharge the preservative solution. Reduce the pressure to -20 in. and maintain for 20 minutes. Allow the pressure to return to atmospheric and remove treated wood articles. Treatment conditions must be used as to produce a 0.1 to 0.6 lbs/cu. ft retention of ADBAC in the treated article. Wood treated to this retention for above ground use only.

### DIP TREATMENT

Stack the wood to be treated on a suitable holder and convey the stack into the treating solution making sure the stack is completely immersed. Dip times must range from 30 seconds (individual pieces) up to 30 minutes (bundled wooden articles). Use a concentration of 0.5 to 3.0% active quaternary ammonium compound. The concentration should be customized to the degree of sap stain protection desired, which must be determined by an independent test on the intended species of wood. This treatment will not provide protection against termites.

### PERSONAL PROTECTION EQUIPMENT FOR PRESSURE TREATMENT, DOUBLE VACUUM AND DIP TREATMENT

Applicators must wear gloves which are chemical-resistant (such as nitrile or butyl) in all situations where dermal contact is expected (i.e. handling freshly treated wood and manually opening cylinder doors). Individuals who enter pressure treatment cylinders and other related equipment that are contaminated with the wood treatment solution (e.g. cylinders that are in operation or are not free of all treatment solution) must wear coveralls over a long sleeved shirt and long pants, socks, chemical-resistant footwear,

and protective eyewear. Federal, State and local confined space entry procedures need to be taken.

Applicators must not eat, drink or use tobacco products during those parts of the applications process that may expose them to the wood treatment formulation (e.g. manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and work shoes or boots and equipment at the plant. Worn out protective clothing and work shoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations.

### BRUSH OR SPRAY

A 0.5% to 3.0% active solution with water (or Sentry GoldSeal™) may be applied by commercial applicators using brush or spray for use on wood shingles or shake roofs and siding on existing homes and on interior construction products and surfaces such as lumber, concrete, sheetrock, wallboard, block and steel. Use low-pressure equipment for spray applications. A moderately fine spray, not an aerosol or fog, generally provides the best coverage at practical product concentrations. Apply only to point of runoff. To make a 0.5% to 3.0% active solution, use the following table:

Percent Active Quat Solution	Ounces of this product per gallon
0.5	0.80
1.0	1.60
1.5	2.40
2.0	3.20
2.5	4.00
3.0	4.80

To find the ounces of this product per gallon for other dilutions take the percent active desired and divide by 0.625.

### PERSONAL PROTECTION EQUIPMENT FOR BRUSH AND SPRAY APPLICATIONS

Applicators must wear gloves, which are chemical-resistant (such as nitrile or butyl). Applicators must also wear coveralls over a long sleeved shirt and long pants, socks, chemical-resistant footwear, and protective eyewear. Applicator must not eat, drink, or use tobacco during the application process. Use with adequate ventilation. Mist or vapor generated by spraying this product may be harmful if inhaled. Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms. Protective clothing must be changed when it shows signs of contamination. Brush/Spray treatment may require frequent changing. Discard clothing and other absorbent materials that have been drenched or heavily contaminated. Do not reuse them.

Follow manufacturers' instructions for cleaning/maintaining protective equipment. If no such instructions exist for washables, use detergent and hot water. Keep and wash protective equipment separate from other laundry.

Worn out protective clothing and work shoes or boots must be disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations.

### SWIMMING POOLS

This product requires no special equipment for treating swimming pool water. The correct use dilution may be added directly to the pool in any spot or added to the water



circulation equipment. This product works best when added by itself directly to pool water.

#### **INSTRUCTIONS FOR USE WITH HALOGEN BASED POOL SANITIZERS**

This product is formulated to complement most swimming pool sanitizers. When using other products as outlined in Directions For Use on those products, always follow Directions For Use of those products. This product is effective against the growth of algae. This product is efficient and non-staining when used as directed. This product will not evaporate and its algae fighting abilities actually increase as pool water temperature increases.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturer's directions. Adjust pH to between 7.2-7.6. Adjust chlorine residual to 1-3 ppm. In a chlorine treated pool, add stabilizer to establish a minimum level of 40-50 ppm to reduce the degradative effects of sunlight upon the chlorine residual. Check for metals and if present add a stain and scale inhibitor to prevent staining of pool surface due to metals. Check chlorine residual and adjust to 1-3 ppm. Maintain sanitizer residual in accordance with label directions found on your sanitizer of choice. This product is effective in controlling the growth of the following types of algae: *Chlorella pyrenoidosa* (green algae), *Phormidium inundatum* (blue-green algae) and *Phormidium ritzii*. When using other products as outlined in directions for this product, always follow directions on those products.

Add this product directly into pool by pouring around entire outside perimeter of pool. Allow the filter to run for at least six (6) hours after adding algaecide. During this period, swimmers must not be allowed into the water.

1. **DOSAGES** – For pools, which are, free of algae or contain algae growth.

**Initial Application:** Backwash the filter thoroughly. Vacuum algae debris and thoroughly brush pool. For an initial application, pour directly into pool at a rate of 16 oz. of this product per 50,000 gallons of water (or equivalent use dilution) (2 ppm). More rapid distribution will be achieved by pouring a portion of the specified amount into several areas of the pool until all of the required quantity has been added. Vacuum pool after 24 hours to remove dead algae. If algae is still visible repeat dose as necessary until pool is free of visible algae. Once algae are under control, clean filter and return to normal operation.

**Maintenance:** Pour directly into pool at a rate of 4 ozs. per 50,000 gallons of water (0.5 ppm) every 5-7 days depending on weather and use factors. After each rain of consequence, add 4 ounces per 50,000 gallons water. Even when the pool may not be in use for periods of time, algaecide additions must be made since a heavy accumulation of algae growth is difficult to remove. The appropriate amount of this product must be added by pouring a portion of the specified amount into several areas of the pool until the required quantity has been added. Recirculation accomplished by running the filter will assure rapid dispersion of product.

2. **Reentry interval:** swimmers are allowed to re-enter the pool 15 minutes after application of the product.

3. Ensure that water quality conditions are maintained for the successful use of the product.

#### **Booster Application**

Add 2 oz. of this product per 25,000 gallons of water after a heavy or prolonged rainfall or when there is a heavy bathing load.

The above directions must be followed even when the pool is not in use. If algae growth is noticeable, apply initial dose.

#### **Vacation Treatment**

When you are going to be away for one week or more add 3.2 ounces of this product per 10,000 gallons of water for every week unattended. Pour product around the edges of the shallow end of the pool, if shock is also being applied in the deep end of pool.

#### **OPTIONAL INSTRUCTIONS FOR USE WITH NON-HALOGEN BASED POOL SANITIZERS**

This product is formulated to complement swimming pool water being treated with the BioGuard Softswim System, Bacquacil and other non-halogen systems. When using other products as outlined in Directions For Use for this product, always follow Directions For Use of those products. This product is efficient and non-staining when used as directed. This product will not evaporate and its algae fighting abilities actually increase as the pool water temperature increases. The residual effectiveness of this product tends to stabilize the total chemical treatment system.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturers' directions. Adjust pH between 7.2-7.6. Check for metals and if present add satin and scale inhibitor to prevent staining of pool surface due to metals.

Add this product directly into pool by pouring around entire outside perimeter of pool. Allow the filter to run for at least six (6) hours after adding algaecide. During this period, swimmers must not be allowed into the water.

#### **Initial Application:**

1. Backwash the filter thoroughly.
2. Vacuum algae debris and thoroughly brush pool.
3. Add 6.4 ounces of this product per 20,000 gallons of water (2 ppm) or ratio thereof.
4. Vacuum pool after 24 hours to remove dead algae.
5. If algae is still visible repeat dose (steps 3 & 4) as necessary until pool is free of visible algae.
6. Once algae are under control, clean filter and return to normal operation.

#### **Maintenance Application**

Add 2 ozs. per 50,000 gallons of water (.5 ppm) every 3-5 days or as needed to maintain 0.5 ppm active.

#### **Booster Application**

Add 2 ozs. of this product in 25,000 gallons of water after a heavy or prolonged rainfall or when there is a heavy bathing load.

The above directions must be followed even when the pool is not in use.

If algae growth is noticeable, apply initial dose.

#### **Vacation Treatment**

When you are going to be away for one week or more add 3.2 ounces of this product per 10,000 gallons of water for every week unattended. Pour product around the edges of the shallow end of the pool, if shock is also being applied in the deep end of pool.

#### **FOR WINTERIZING POOLS BEFORE FREEZING** (not for use in California)

Test the water and adjust to the proper levels.

After pool is no longer in use, super-chlorinate, using a recommended winter shock treatment, according to label directions. Allow pump to circulate for several hours or overnight.

Add winterizing algaecide directly to pool water, walking around the pool, so that it is evenly distributed. Use at the rate of 16 ounces (6.7 ppm) per 15,000 gallons. Allow to circulate for a few hours.

Clean pool water line, shut down filter, drain pump, and winterize as per manufacturer's instructions. Cover with a solid cover if possible. Pools without a solid cover may need a second treatment later in the non-swimming season.

Swimming Pool Capacity Gallon of Water	Initial Treatment	Maintenance Dose
5,000	1.6 ounces	0.4 ounces
10,000	3.2 ounces	0.8 ounces
20,000	6.4 ounces	1.6 ounces
25,000	8.0 ounces	2.0 ounces
30,000	9.6 ounces	2.4 ounces
40,000	12.8 ounces	3.2 ounces
50,000	16.0 ounces	4.0 ounces

**TO DETERMINE POOL CAPACITY**

**Rectangular Pools:** Length (times) width (times) average depth (in feet) (times) 7.5 (equals) gallons.

**Round and Oval Pools:** Long diameter (times) short diameter (times) average depth (in feet) (times) 5.9 (equals) gallons.

**OTHER**

**DIRECTIONS FOR USE IN (OUTSIDE) SPAS/WHIRLPOOLS/HOT TUBS**

("Outside" description not for use in California)

**Initial Dose:** Add 1.6 ounces of this product per 5,000 gallons of water. Initial dose is used upon filling of (outside) spa/whirlpool/hot tub bath.

**Maintenance Dose:** Add 0.4 ounces of this product per 5,000 gallons of water. Maintenance dose must be added at 3-5 day intervals. If high temperatures prevail or (outside) spa/whirlpool/hot tub bath has unusually heavy use, add maintenance dose more frequently. Drain and clean outside spa/whirlpool/hot tub bath at least once a month or as needed depending upon bather load.

**CONTROLLING ALGAE GROWTH**

**Bird Baths:** Do not use with fish. Clean to remove algae growth prior to filling birdbath. Then spray all exposed surfaces with a solution of 1/4 ounce of this product per gallon of water. Allow to air dry and brush off dead algae.

(Or)

**INSTRUCTIONS FOR BIRD BATHS**

This product is toxic to fish. **DO NOT** use this product when fish are present.

**Initial Dose:**

1. Drain Bird Bath.
2. Wipe, mop or spray all exposed surfaces using 1/8 ounce of this product per gallon of water. Spray device must be a mechanical coarse spray device. When applied with spray device, surfaces must be sprayed until thoroughly wetted. Do not rinse.
3. Allow to air dry and brush off dead algae. Repeat, if necessary, until no algae is visible.
4. Refill Bird Bath with fresh water.

**Maintenance Dose:** Repeat initial treatment when algae growth returns.

**ALGAE CONTROL ON WALKWAYS:** For heavy infestations, spray or swab a solution of 1/8 ounce of this product per gallon of water. Let stand for an hour or more then brush and wash away dead algae. Soak area again with the solution. Do not rinse. Allow to (air) dry on the surface and repeat application when algae growth returns.

**INSTRUCTIONS FOR (CONTAINERIZED) DECORATIVE FOUNTAINS AND POOLS**

(Note to Reviewer: "Containerized" description must be used in California.)

This product is not to be used in open water ways connected to larger watersheds or in waters that serve as natural habitats for aquatic and amphibious organisms. **DO NOT** use when fish or other wildlife (for example, amphibians) are present. This product is toxic to fish. **DO NOT** use this product when fish are present.

**Initial Dose:**

1. Remove floating algae by raking, dragging with cable or chain or any other suitable method. It is more economical to remove floating type algae (if possible) before the water is treated.
2. Add this product at any point that is convenient, such as the bowl, pool, or sump.
3. Add 18 ounces of this product to each 25,000 gallons (4 ounces per 12,500 gallons) or ratio thereof.

**Weekly Maintenance Dose:** Add 4 ounces of this product to each 50,000 gallons of water every 3-5 days or as to maintain 0.5 ppm active.

Each month drain and clean bowl. Refill with fresh water and repeat initial treatment. Draining removes airborne dirt, dust, contamination and alkali buildup.

Decorative Fountains or Pools Capacity in gallons of water	Initial Treatment	Maintenance Dose Booster Dose
25,000	8 ounces	2 ounces
12,500	4 ounces	1 ounces
6,250	2 ounces	1/2 ounces
3,125	1 ounce	1/4 ounce
1,562	1/2 ounce	1/8 ounce
781	1/8 ounce	0.0625 ounce

(Note to reviewer: The title and first statement of this section must appear on every label, followed by the appropriate Storage and Disposal section.)

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage and disposal.

(For Swimming Pool Use and Decorative Fountains and Pools in nonrefillable containers up to and including 5 gallons)

Nonrefillable container. Store in original container in areas inaccessible to small children. Keep from freezing. Do not reuse empty container. Wrap and discard in trash (or recycle).

(For Swimming Pool Use and Decorative Fountains and Pools in containers over 5 gallons)

**PESTICIDE STORAGE:** Store in original containers and place in locked storage area. Keep from freezing. Do not contaminate water, food, or feed by storage or disposal.

**SPILL OR LEAK PROCEDURES:** Small spills may be mopped up or flushed away with water or absorbed on some absorbent material and incinerated.

**PESTICIDE DISPOSAL:** Securely wrap original container in several layers of newspaper and discard in trash.

**CONTAINER DISPOSAL:** Do not reuse container (bottle, cans, jars). Triple rinse (or equivalent). Then dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

(For Industrial Water Treatment Use, Industrial and/or Commercial Recirculating Cooling Water Towers and Recirculating Cooling Water Systems, Auxiliary water and waste water systems and water cooling systems, once through fresh water cooling systems, sap stains, wood preservatives and all containers up to and including 5 gallons.)

**PESTICIDE STORAGE:** Store in original containers and place in locked storage area. Keep from freezing.

equivalent) promptly after emptying. Continue to drain for 10 seconds after the flow ends. Repeat this procedure two more times.

Made in USA



[Optional – for use on residential use swimming pool and spa products.]



**SPILL OR LEAK PROCEDURES:** Small spills may be mopped up or flushed away with water or absorbed on some absorbent material and incinerated. Large spills should be contained and the material then moved into containers and disposed of by approved methods for hazardous wastes.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Nonrefillable container. Do not refill or reuse container. Triple rinse as follows: Fill container ¼ full with water and recap. Shake for 10 seconds. Follow Pesticide Disposal instructions for rinsate disposal. Drain for 10 seconds after the flow begins to drip. Repeat procedure two more times. Then offer for recycling or reconditioning. If not available, puncture and dispose of in a sanitary landfill.

**(FOR USE ON NON-REFILLABLE CONTAINERS WITH COMMERCIAL/INDUSTRIAL USES)**

(Note: For use on containers greater than 5 gallons)

**PESTICIDE STORAGE:** Open dumping is prohibited. Store only in original container. Do not reuse empty container. If a leaky container must be contained within another, mark the outer container to identify the contents. Store pesticides away from food, pet food, feed, seed, fertilizers, and veterinary supplies. Keep [(this product) (Product Name)] under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** (Note: Only one of the following Container Disposal paragraphs will be used, depending on packaging type)

Non-refillable container. Do not reuse this container to hold materials other than pesticides or diluted pesticides (rinsate). Offer for recycling if available or puncture and dispose in a sanitary landfill, or by other procedures approved by state and local authorities. If rinsate cannot be used, follow pesticide disposal instructions.

(Note: Several of our customers' packaging options are sealed containers or bottles designed to reduce worker exposure to the concentrate. None of these can be triple rinsed because they are closed sealed containers. The following text will be used on these **non-refillable sealed container** types only.)

Nonrefillable container. Do not reuse or refill this container. Wrap empty container and put in trash.

**RESIDUE REMOVAL INSTRUCTIONS:** To clean the container before final disposal, empty the remaining contents from this container into [(application equipment) (a mix tank)]. Fill the container ¼ full with water. Replace and tighten closures. [Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds then stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times] (Agitate vigorously or recirculate water for 30 seconds)]. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times.

**(FOR USE ON REFILLABLE STORAGE TANK/FIXED STORAGE TANK/TOTE CONTAINERS)**

**PESTICIDE STORAGE:** Open dumping is prohibited. Store only in original container. If a leaky container must be contained within another, mark the outer container to identify the contents. Store pesticides away from food, pet food, feed, seed, fertilizers, and veterinary supplies. Keep [(this product) (Product Name)] under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER HANDLING/RESIDUE REMOVAL INSTRUCTIONS:** Drain rinsate into application equipment and dispose of according to Pesticide Disposal instructions. Triple rinse container (or