

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS  
AND DOMESTIC ANIMALS**

**DANGER.** Keep Out of Reach of Children. Corrosive. Causes irreversible eye damage and skin burns. May be fatal if inhaled or swallowed. Harmful if absorbed through skin. Do not get in eyes, on skin or on clothing. Do not breath vapor or spray mist. Wear goggles or face shield, rubber gloves and protective clothing when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or frequent skin contact may cause allergic reactions in some individuals.

*(If container is 5 gallons or larger the following statement must appear on the label.)*

**ENVIRONMENTAL HAZARD**

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS**

Do not mix with oxidizers, anionic soaps and detergents.  
Do not use or store near heat or open flame.

*(If the container is greater than one gallon use the following storage and disposal statements.)*

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage and disposal.

**PESTICIDE STORAGE:** Open dumping is prohibited. Store only in original container. Do not reuse empty container. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.


**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL** (Larger than 1 gal.) - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

*(If container is one gallon or less use the following storage and disposal statements.)*

**STORAGE AND DISPOSAL**

Store in original container in areas inaccessible to small children. Do not store on side. Avoid creasing or impacting of side walls. Do not reuse empty container. Wrap and discard in trash (or recycle).



**MAQUAT® WP-80%**  
A Wood Treatment Preservative

<b>ACTIVE INGREDIENT:</b>	
Didecyl Dimethyl Ammonium Chloride .....	80.0%
<b>INERT INGREDIENTS:</b> .....	20.0%
<b>TOTAL</b> .....	100.00%

Contains 7.4 lbs of product per gallon

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

See left panel for additional precautionary statements.

**First Aid**

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**IF SWALLOWED:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage.

**MASON CHEMICAL COMPANY**

"THE QUATERNARY SPECIALISTS"



721 W. Aiguquin Road  
Arlington Heights, IL 60005  
847-290-1621

Toll Free:  
1-800-362-1855

E.P.A. Reg. No. 10324-136  
E.P.A. Est. No. 10324-IL-1

NET CONTENTS

BATCH NO

APR-22-2005 12:24PM FROM-MASON CHEMICAL

10324-136

05/18/2005

+1847 290 1625

T-725

P. 004/009

F-877

13

Maquat® WP-80% is a concentrated biocide for use as a wood preservative. When used as directed, Maquat® WP-80% will protect treated wood articles from the destructive attack of fungi, mold, mildew and both Reticulitermes and Formosanus species of termites. Treatment can be done by pressure, double vacuum, dip, brush and/or spray, although dip, brush and spray can not be used for protection against termites. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood shingles, posts and other articles to be used in above ground applications.

OR

This product will protect treated wood articles from the destructive attack of fungi, mold or mildew. Treatment can be done by pressure or double vacuum. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood shingles, posts and other articles to be used in above ground applications. (10324-42)

Treatment can be done by brush or spray for wood shingle applications, and by pressure, double vacuum or dip method for other wood products. Wood articles that will be protected by these treatments would include millwork, construction timbers, decking, wood shingles, and posts.

#### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product can be used in combination with other EPA registered organic and inorganic wood preservatives or it can be used alone.

#### MAQUAT® WP-80%

Dilute this product in either water or mineral spirits (or Sentry GoldSeal™) to produce a 0.5% to 3.0% active quaternary ammonium compound solution.

Percent Active Quat Solution	Ounces of this product per gallon
0.5	0.80
1.0	1.60
1.5	2.40
2.0	3.20
2.5	4.00
3.0	4.80

To find the ounces of this product per gallon for other dilutions take the percent active desired and divide by 0.625.

#### MAQUAT® WP-80% AND COPPER COMPOUNDS

Mix this product with water and either (ACQ-C2 EPA Reg. No. 10465-38 or ACQ-C EPA Reg. No. 10465-33) (NW 100-C, EPA Reg. No. 3008-87 or NW 200-C, EPA Reg. No. 10465-33-3008). Refer to the product labels for (ACQ-C and ACQ-C2) (NW 100-C and NW 200-C) for precise mixing instructions. This product may only be used in combination with copper compounds in pressure treatment applications.

#### MAQUAT® WP-80% AND BORATES

Mix this product and either (Disodium Octaborate Tetrahydrate) Wood Bor, EPA Reg. No. 3008-81, Envirotech Insecticide, EPA No. 65705-1, Timbersaver, EPA Reg. No. 71916-1, TimberSaver PT, EPA Reg. No. 71916-1-10465, Tim-Bor, EPA Reg. No. 1624-39, or Cellu-Treat DOT Wood Preservative, EPA Reg. No. 64405-8 in water. Refer to the product labels for precise mixing. This product may only be used in combination with the above borates in pressure treatment or dip treatment applications.

Mix this product and Lum-Bor, EPA Reg. No. 19713-286 in water. Refer to the product label for precise mixing instructions. This product may only be used in combination with the above borate in brush or spray applications.

Mix this product and BORA-CARE, EPA Reg. No. 64405-1 in water. Refer to the product label for precise mixing instructions. This product may only be used in combination with the above borate in dip treatment applications.

#### MAQUAT® WP-80% AND PROPICONAZOLE

Mix this product with Woodlife P, EPA Reg. No. 1409-65 and dilute with either water, mineral spirits or other light organic solvent to produce a 0.5 to 3.0% quaternary ammonium compound solution. Follow the instructions on the Woodlife P for the appropriate concentration of propiconazole. PLEASE NOTE THAT THIS FORMULATION CAN ONLY BE USED FOR DIP TREATMENT.

#### PRESSURE TREATMENT

Place the wood article to be treated into the pressure cylinder and seal unit. Treat the wooden articles using the pressure treatment procedures consistent with the equipment being used and standard treatment practices. Treatment conditions should be such as to produce a 0.1 to 0.6 lb./cu. foot retention in the treatment article. For protection against termites, wood must be treated to a minimum of 0.38 lb./ft.<sup>3</sup>. Such treated wood is to be used for above ground uses only.

#### DOUBLE VACUUM

Stack the wooden articles to be treated in the treatment vessel so that the preservative solution will have access to all sides of the articles. Seal the vessel. Reduce the pressure within the vessel to -10 inches for 5 minutes. Cover all the articles with preservative solution. Allow the pressure to return to atmospheric conditions and discharge the preservative solution. Reduce the pressure to -20 inches and maintain for 20 minutes. Allow the pressure to return to atmospheric and remove treated wood articles. Treatment conditions should be used as to produce a 0.1 to 0.6 lbs/cu.ft retention of DDAC in the treated article. Wood treated to this retention for above ground use only.

#### DIP TREATMENT

Stack the wood to be treated on a suitable holder and convey the stack into the treating solution making sure the stack is completely immersed. Dip times should range from 30 seconds (individual pieces) up to 30 minutes (bundled wooden articles). Use a concentration of 0.5 to 3.0% active quaternary ammonium compound. The concentration should be customized to the degree of sap stain protection desired, which should be determined by an independent test on the intended species of wood. This treatment will not provide protection against termites.

#### PERSONAL PROTECTION EQUIPMENT FOR PRESSURE TREATMENT, DOUBLE VACUUM AND DIP TREATMENT

Applicators must wear gloves, which are chemical-resistant (such as nitrile or butyl) in all situations where dermal contact is expected (i.e. handling freshly treated wood and manually opening cylinder doors). Individuals who enter pressure treatment cylinders and other related equipment that are contaminated with the wood treatment solution (e.g. cylinders that are in operation or are not free of all treatment solution) must wear coveralls over a long sleeved shirt and long pants, socks, chemical-resistant footwear, and protective eyewear. Federal, State and local confined space entry procedures need to be taken.

Applicators must not eat, drink or use tobacco products during those parts of the applications process that may expose them to the wood treatment formulation (e.g. manually opening/closing cylinder doors, moving trams out of cylinder mixing chemicals, handling freshly treated wood).

3/3

Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and work shoes or boots and equipment at the plant. Worn out protective clothing and work shoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations.

**BRUSH OR SPRAY**

A 0.5% to 3.0% active solution with water (or Sentry GoldSeal™) may be applied by brush or spray for use on wood shingles or shake roofs and siding on existing homes by commercial applicators, and on interior construction products and surfaces such as lumber, concrete, sheetrock, wallboard, block and steel. Low-pressure equipment is recommended for spray applications. A moderately fine spray, not an aerosol or fog, generally provides the best coverage at practical product concentrations. Apply only to point of runoff. This treatment will not provide protection against termites. To make a 0.5% to 3.0% active solution, use the following table:

Percent Active Quat Solution	Ounces of this product per gallon
0.5	0.80
1.0	1.60
1.5	2.40
2.0	3.20
2.5	4.00
3.0	4.80

To find the ounces of this product per gallon for other dilutions take the percent active desired and divide by 0.625.

**PERSONAL PROTECTION EQUIPMENT FOR BRUSH AND SPRAY APPLICATIONS**

Applicators must wear gloves, which are chemical-resistant (such as nitrile or butyl). Applicators must also wear coveralls over a long sleeved shirt and long pants, socks, chemical-resistant footwear, and protective eyewear. Applicator must not eat, drink, or use tobacco during the application process. Use with adequate ventilation. Mist or vapor generated by spraying this product may be fatal if inhaled. Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms. Protective clothing must be changed when it shows signs of contamination. Brush/Spray treatment may require frequent changing. Discard clothing and other absorbent materials that have been drenched or heavily contaminated. Do not reuse them.

Follow manufacturers instructions for cleaning/maintaining protective equipment. If no such instructions exist for washables, use detergent and hot water. Keep and wash protective equipment separate from other laundry.

Worn out protective clothing and work shoes or boots must be disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations.