

# UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

January 25, 2017

Kresti Lyddon Senior Registration Specialist Mason Chemical Company 723 W. Algonquin Road Arlington Heights, IL 60005

Subject: PRIA Label and CSF Amendment – Revised Label and Product Chemistry

Product Name: Maquat 40-10

EPA Registration Number: 10324-188

Application Date: 9/7/2016 Decision Number: 521146

Dear Ms. Lyddon:

The amended label and CSFs referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, are acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Please note that the record for this product currently contains the following CSFs:

- Basic CSF dated 9/7/2016
- Alternate CSF 2 dated 9/7/2016
- Alternate CSF 3 dated 9/7/2016
- Alternate CSF 4 dated 9/7/2016

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the

Page 2 of 2 EPA Reg. No. 10324-188 Decision No. 521146

website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, you may contact Aline Heffernan at 703-347-8602 or via email at <a href="mailto:heffernan.aline@epa.gov">heffernan.aline@epa.gov</a>.

Sincerely,

John Hebert, Chief

Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs

Enclosure: Stamped Label

## MASON CHEMICAL COMPANY "The Quaternary Specialists"

723 W. Algonquin Road | Arlington Heights, IL 60005 847-290-1621 or 800-362-1855

EPA Reg. No. 10324-188 EPA Est. No.

# MAQUAT® 40-10

(Note to Reviewer: Marketing claims may be used on the front panel.)

#### **ACTIVE INGREDIENTS:**

Glutaraldehyde	40.0%
Didecyl dimethyl ammonium chloride	
Alkyl (50%C <sub>14</sub> , 40%C <sub>12</sub> , 10%C <sub>16</sub> )	
dimethyl benzyl ammonium chloride	4.0%
OTHER INGREDIENTS:	
TOTAL:	1 <u>00.0%</u>

{Weight Approx. 9.05 lbs./gal.}

# DANGER {PELIGRO}

{See [{left} {back} {side} {right} {insert} {panel} {of label} {below}] for {additional} {precautionary statements}{and}{or}{first aid}.}

(Note to Reviewer: First Aid may only appear on different area of the container label if the Front Panel is less than 12 square inches in total.)

#### **FIRST AID**

In case of emergency, call a poison control center or doctor for treatment advice. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

IF ON SKIN: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.

**IF SWALLOWED:** Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. Call a poison control center or doctor immediately for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

{For [{chemical} {and} {or} {medical} {and} {or} {environmental}] emergencies, call {insert name and/or number of emergency contact} {hours of operation} {24 hours a day} {7 days a week}}.



{See {additional} {sheet} {insert} {outer container} for {other} {directions for use} {information} {claims} {organisms}.}

Net Contents: {{Batch} {Lot} No} {Manufacturing Date}: {Product of USA} {Made in the USA}

## ACCEPTED

Jan 25, 2017

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under

EPA Reg. No. 10324-188

#### **TABLE OF CONTENTS**

(Note to Reviewer: The Table of Contents will not be on any label. This is for our customer's reference only.)

MARKETING CLAIMS	2
WATER TREATMENT (Not for Use in CA.)	4
OIL FIELD, GAS PRODUCTION AND TRANSMISSION PIPELINE AND SYSTEMS (Not for use in CA)	
PULP AND PAPER MILLS (Not for use in CA.)	6
STORAGE AND DISPOSAL	
PRECAUTIONARY STATEMENTS	
ENVIRONMENTAL HAZARDS	

### MARKETING CLAIMS

(Note to Reviewer: Marketing text is considered optional. Commas and the words "and" "or" can be added to phrases to make text grammatically correct.)

#### {LOCATIONS/SURFACES}

(Note to Reviewer: The locations/surfaces have been grouped for space purposes only; they can be used individually or grouped together in any order however at least one location/surface must appear on the label. In the case where one or more location/surface is chosen, an "and" "&" "or" may be used to link locations/surfaces.)

This product is for use in (insert location) For use {in} {on} (insert location/surface).

#### {LOCATIONS}

- Air washers
- Auxiliary water systems
- · Commercial recirculating cooling water towers
- Dairy sweetwater systems
- Drilling, completion and workover fluids systems
- Evaporative Condensers
- Gas storage wells and systems
- · Hydrotesting facilities
- Industrial {and/or} {commercial} recirculating cooling towers.
- Industrial scrubbing systems
- Oil field water flood systems {and fracturing fluid systems}
- Packer fluid systems
- Pipeline pigging and scraping operations
- Recirculating water systems
- Retort water systems
- Waste water systems
- Water cooling systems
- Paper manufacturing
- Pulp and paper mills {water process systems}

#### **{SURFACES}**

Paper and paperboard. Do not use to treat paper or paperboard which will contact food.

#### WATER TREATMENT MARKETING CLAIMS

(Note to Reviewer: The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}".)

- Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, air washers, dairy sweetwater systems, hydrostatic sterilizers and retorts, pasteurizers, warmers, and industrial water scrubbing systems.
- A water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, retort water systems and flood systems and fracturing fluids.
- A microbiocide for use in controlling sulfate-reducing bacteria and slime forming bacteria in oil well drilling, oil field processing
  applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields
  and equipment; such as steam-injection water holding tanks, flood water, injection water, holding pond water, disposal-well
  water, water holding tanks, fuel storage tanks and related refinery and oil field closed systems, industrial recirculating water
  handling systems.
- A microbiocide for use in controlling slime forming bacteria, sulfate-reducing bacteria (SRB) and fungi (yeast and molds) and
  algae in air washers and industrial scrubbing systems, process water systems including those that contain reverse osmosis
  membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including
  wastewater sludge and holding tanks, and in paper mills and paper mill process water systems and water based coatings for
  paper and paperboard.
- Controls algae and algal slime growth in industrial and/or commercial recirculating cooling water towers.
- Effective against the growth of algae.
- For control of algae, algal, fungal and bacterial slimes in recirculating water systems, auxiliary water and waste water systems and water cooling systems, oil field water flood systems.
- Has been designed specifically for control of sulfate-reducing bacteria that contribute to souring, the production of sulfide, and abiotic corrosion in water cooling systems, paper mill process water systems, oil field systems, gas production and transmission pipelines and systems.
- Helps inhibit the growth of unsightly algae.
- Is a microbiocide that helps clean and loosen slime debris from cooling and flooding system surfaces.
- Is a water treatment microbiocide that will control algae and bacterial slimes found in recirculating cooling tower waters.
- Kills and prevents algae.
- The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.
- This product is effective for the control of odor-forming and slime-forming bacterial, fungi and algae in auxiliary service water systems such as fire protection systems and pump or screen bays, waste water systems such as storage tanks, storage piles, associated piping, setting ponds or lagoons, transport spillways or canals and disposal wells.
- This product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations.
- To control algae and bacterial slimes, use this water treatment microbiocide as directed.

#### PULP AND PAPER MILL MARKETING CLAIMS

(Note to Reviewer: The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}".)

- Is used to inhibit fungal growth, which causes discoloration, odor and degradation of paper, paperboard or wet lap.
- Can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination.
- For control of bacterial and fungal slimes in pulp mills, paper mills and paper manufacturing.
- This product can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination. Do not use to treat paper or paperboard which will contact food
- This product is used to inhibit fungal growth which causes discoloration, odor and degradation of paper or paperboard.

#### **GENERAL MARKETING CLAIMS**

(Note to Reviewer: The following marketing claims may be used with the prefix "This product" or "This product is {a} {an}".)

- Efficient and non-staining when used as directed.
- Is non-staining.
- Will not damage tile, concrete, metal or plastics.

#### **PACKAGING CLAIMS**

- Concentrate(d).
- Easy to use.
- Is an economical concentrate.
- This [{container} {bottle}] is made of {at least} (x) % post-consumer recycled plastic.

#### **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

(**Note to Reviewer (General Considerations):** Numbered instructions will be used if label space permits, otherwise may appear in paragraph format. Unit abbreviations can be spelled out. When choosing optional text, appropriate punctuation can be inserted or deleted. Equivalent use dilution ratios may be substituted within the directions.)

{Please read entire label and use strictly in accordance with precautionary statements and directions.}

#### WATER TREATMENT (Not for Use in CA.)

Do not use water containing residues from use of this product to irrigate crops for food or feed.

(Note to Reviewer: The following sentence must be used with the air washer use listed in the directions:) For use only in industrial air washers and air washer systems which have mist-eliminating components.

AIR WASHERS, INDUSTRIAL {{AND/OR} COMMERCIAL} RECIRCULATING COOLING WATER TOWERS, RETORT WATER SYSTEMS, EVAPORATIVE CONDENSERS, HEAT {{EXCHANGE} {TRANSFER}} {WATER} SYSTEMS, DAIRY SWEETWATER SYSTEMS, HYDROSTATIC STERILIZERS, PASTEURIZERS AND WARMERS: For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with this algaecide. {Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages.} Repeat every seven days or increase frequency if needed. Should slime develop again, repeat initial dosage.

- 1. **Dosing Location:** This product is to be applied at a point in the system where it will be uniformly mixed, such as the basin area, the sump, or another reservoir or collecting area.
- 2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired. {Tower bleed off valves must be closed to permit a retention time of 4 hours.}
- 3. Method of Application:
  - a. INTERMITTENT OR SLUG METHOD
    - **Initial Dose:** When the system is noticeably fouled, apply 12.8 25.6 oz. of this product per 1,000 gal. of water {(50 100 ppm active)} in the system. Repeat until control is achieved.
    - **Subsequent Dose:** When microbial control is evident, add 5.1 12.8 oz. of this product per 1,000 gal. of water  $\{(20 50 \text{ ppm active})\}$  in the system weekly or as needed to maintain control.
  - b. **CONTINUOUS FEED METHOD** 
    - **Initial Dose:** When the system is noticeably fouled, apply 12.8 25.6 oz. of this product per 1,000 gal. of water {(50 100 ppm active)} in the system.
    - **Subsequent Dose:** Maintain this treatment by starting a continuous feed of 2.56 12.8 oz. of this product per 1,000 gal. of water {(10 50 ppm active)} lost by blowdown.

**AUXILIARY SYSTEMS AND SERVICE WATER:** Add 12.8 – 25.6 oz. of this product per 1,000 gal. of water {(50-100 ppm active)} in the system continuously. This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile. The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination. Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing.

**INDUSTRIAL WASTEWATER SYSTEMS (Wastewater Systems, Wastewater Sludge and Wastewater Holding Tanks):** This product is added to a wastewater system or sludge at a convenient point of uniform mixing such as digester. Add 0.5 – 2.5 gal. of this product per 1,000 gal. of wastewater or sludge {(250 – 1250 ppm active)}.

#### OIL FIELD, GAS PRODUCTION AND TRANSMISSION PIPELINE AND SYSTEMS (Not for use in CA)

**{{OIL FIELD} {GAS PRODUCTION} {TRANSMISSION PIPELINE} {AND} {SYSTEMS}:}** Specific treatment requirements vary among oil and/or gas field sites and subsystem components. **{Oil field fluids and subsystems most commonly requiring microbial contamination control are raw water sources, separators, ballasts, storage and mixing tanks, screens, surface injection equipment, production equipment <b>{(such as injection and production piping casting, completion and valving)}** and the formation itself.} The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction (low pressure) side of pumping equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system fouling.

**OIL FIELD WATER FLOOD SYSTEMS AND FRACTURING FLUIDS:** This product must be added to the water flood system at a point of uniform mixing.

- 1. **Continuous Use:** Add 1 50 gal. of this product per 10,000 gal. of flood water {(50 2500 ppm active)} to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.
- 2. **Intermittent Use**: Add at a rate of 1 50 gal. of this product per 10,000 gal. of flood water {(50-2500 ppm active)} for 4 8 hrs. per day, one to four times a week as needed to maintain control.
- 3. **Treatment of flow back return water** {(Post Hydraulic Fracturing)}: Dose at a rate of 1 50 gal. of this product per 10,000 gal. of flood water {(50 2500 ppm active)} for 4 8 hours per day, one to four times a week as needed to maintain control.

[{FRACTURING} {FRAC}] FLUIDS: Add this product to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down-hole.

**Dose Range:** Add 1 – 50 gal. of this product per 10,000 gal. of frac water {(50 – 2500 ppm active)} to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.

OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS: For the control of sulfate-reducing bacteria and slime forming bacteria, this product must be added to a gas production or transmission pipeline via direct injection at a point where uniform and maximum distribution will occur. The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate application, it is desirable to dilute the product with an appropriate solvent immediately before use. The concentration in the solvent must not fall below an active concentration range of 500 - 5000 ppm active based on the volume of water in the pipeline. Injections to the system must be weekly, or as needed to maintain control.

**GAS STORAGE WELLS AND SYSTEMS:** Treat individual injection wells with 1 – 10 gal. of this product per 1,000 gal. of water {(500 – 5000 ppm active)}. Update treatment rate as needed. This product must be diluted by the water present in the formation. Injection takes place before gas is injected and may be repeated yearly or as needed to maintain control.

Individual drips should be treated with a sufficient quantity of this product to produce a concentration of 200 – 2000 ppm active of this product when diluted by the water present in the drip. Injections should be repeated yearly or as needed to maintain control.

**PIPELINE PIGGING AND SCRAPING OPERATIONS:** Add this product to slug water immediately following the scraper {(keep the water volume to a minimum and contained between the scraper and the [{following} {trailing}] pig)}. Add an effective concentration of 1 – 10 gal. of product per 1,000 gal. of water {(50 – 5000 ppm active)} {to produce 0.05 – 0.5% active solution} depending on the length of the pipeline and the severity of the biofouling.

**DRILLING, COMPLETION AND WORKOVER FLUIDS SYSTEMS:** This product is to be added to these fluid systems at a point of uniform mixing, such as a circulating, holding or mud tank. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

- 1. Initial treatment: Add 0.1 2.0 gal. of this product per 1,000 gal. of freshly prepared fluid {(50 1000 ppm active)}.
- 2. **Maintenance dosage:** Add 0.1 2.0 gal. of this product per 1,000 gal. of freshly prepared fluid {(50 1000 ppm active)}.

**PACKER FLUIDS:** This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank {and} {other mixing device locations}. Add 0.5 – 6 gal. of this product per 10,000 of freshly prepared packer fluid {(25 – 300 ppm active)}. Levels for effective control vary depending on conditions at the site and the severity of contamination. Seal the treated packer fluid in the wall between the casing and the production tube.

**HYDROTESTING:** Treat water used to hydrotest pipelines or vessels by adding 0.1 – 4.0 gal. of this product per 1,000 gal. of water {(50 – 2,000 ppm active)} depending on the water quality and length of time the equipment will remain idle.

#### PULP AND PAPER MILLS (Not for use in CA.)

Do not use to treat paper or paperboard which will contact food.

**SLIMICIDE APPLICATIONS:** Do not use to treat paper or paperboard which will contact food. Apply this product to the paper making system at a point of uniform mixing such as, thin or thick stock chests, save-all tank, process tank or whitewater tank.

**Initial Dose:** When system is noticeably contaminated, add 0.2 - 40.0 gal. of this product per 100,000 gal. of whitewater  $\{(1 - 200 \text{ ppm active})\}$  to be treated as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems must be boiled out prior to initial treatment.

**Subsequent Dose:** When microbial control is evident, add 0.2 - 40.0 gal. of this product per 100,000 gal. of whitewater  $\{(1 - 200 \text{ ppm active})\}$  to be treated as necessary to maintain control.

WATER BASED COATING, PIGMENTS AND FILLER SLURRIES FOR PULP AND PAPERBOARD: Application of this product must be made at a point in the system where mixing action is good or can be made at the size press or water box.

**Dosing Application:** Apply at a rate of 0.1 - 0.6 lbs. per 1,000 lbs. of dry powder or 0.045 - 0.272 kg of this product per metric ton of dry slurry to produce a concentration of 100 - 600 ppm active as product (based on slurry solids) in the mixed slurry.

## STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

**(PESTICIDE) STORAGE:** Store only in original container at room temperature. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

#### **CONTAINER HANDLING:**

(Note to Reviewer: One or more of the following paragraphs for Container Handling will be selected, depending on packaging use/type.)

#### {For non-refillable containers equal to or less than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water and recap. Shake for 10 seconds. Drain for 10 seconds after the flow begins to drip. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

#### {For non-refillable containers greater than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip back and forth several times. Turn the container over onto its other end and tip back and forth several times. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

#### {Refillable containers}

Refillable Container. Refill this container with this product only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal empty the remaining contents from this container into application equipment or a mix tank. Fill container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER.** Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed. Harmful if absorbed through the skin or inhaled. Do not get in eyes, on skin or on clothing. Do not breathe spray mist. Wear goggles or face shield, chemical-resistant gloves and long-sleeve shirt, long pants, shoes, socks and chemical-resistant apron when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse.

#### **ENVIRONMENTAL HAZARDS**

(If container is equal to or greater than 5 gal., the following statement must appear on the label.)

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

(If container is less than 5 gal., use the following as an alternate to the above statement.) This product is toxic to fish, aquatic invertebrates, oysters and shrimp.

#### **(SPANISH ADVISORY STATEMENTS)**

(Note to Reviewer: This statement is optional except when used on labels with agricultural uses.)

(SI USTED NO ENTIENDE LA ETIQUETA, BUSQUE A ALGUIEN PARA QUE SE LA EXPLIQUE A USTED EN DETALLE. IF YOU DO NOT UNDERSTAND THE LABEL, FIND SOMEONE TO EXPLAIN IT TO YOU IN DETAIL.)

#### **GRAPHICS AND ICONS**

(Note to Reviewer: These are representative icons for use sites/application methods that may appear on the label with the appropriate directions for use, PPE or package type.)

{Baby Drowning in Bucket Warning Graphic}

{Made in USA Logo/Flag}

{Recycling Logo}

#### **{WARRANTY STATEMENT}**

(Note to Reviewer: This statement is optional.)

Read Product Material Safety Data Sheet prior to use, PRODUCT WARRANTY, DISCLAIMER AND LIMITATION OF LIABILITY ARE FOUND on the Product Material Safety Data Sheet. Unless inconsistent with applicable law, use of Product signifies agreement with these provisions.

Lea la Hoia de Seguridad del Producto antes de usarlo. LA GARANTIA DEL PRODUCTO, DECLINACION Y LIMITACION DE RESPONSBILDAD SE ENCUENTRAN en la Hoia de Seguridad del Producto. A menos de que sea inconsistence con la ley, el uso del product signigica acuerdo con esteas disposiconies.