

10324-205

7/31/2012

1/12

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, D C 20460



Office of Pesticide Programs

Ms Elizabeth Tannehill  
Mason Chemical Company  
721 W Algonquin Road  
Arlington Heights IL 60005

Subject                      Maquat LC12S 10%FC  
Registration #              10324 205  
Amendment Date            April 24 2012  
Received Date                May 2 2012  
Submission #                 916903

JUL 31 2012

Dear Ms Tannehill

The following amendments submitted in connection with registration under the Federal Insecticide Fungicide and Rodenticide Act (FIFRA) as amended are acceptable with comments listed below

- Response to EPA letter dated 4/24/12

Revise the label as follows

**Conditions**

Revise the For Use on Refillable Containers with Commercial/Industrial Use as following

- Add the following statement to the section beginning Cleaning the container before final disposal and ending is the responsibility of the refiller Add *When empty return to point of sale for refilling*
- Add the following statements to both the Container Handling/Residue Removal Instructions for all refillable container except fixed tank containers as well as fixed tanks Revise to begin Refillable container *Refill this container with pesticide only Do not reuse this container for any other purpose* To clean container
- Add the following statements to both the Container Handling/Residue Removal Instructions for all refillable container except fixed tank containers as well as fixed tanks Revise to end as follows *Puncture or dispose of in a sanitary landfill or by other procedures approved by state and local authorities*

2/12

- Add the following statements to both the Container Handling/Residue Removal Instructions for fixed tanks Revise to include application equipment or mix tank and *continue to drain for 10 seconds after the flow begins to drip* Insert pressure rinsing nozzle in the side of the container and rinse at about 40 PSI for at least 30 seconds Drain for 10 seconds after the flow begins to drip Drain rinsate into application

**General Comments**

A stamped copy of the accepted labeling with conditions is enclosed Summit 1 Copy of your final printed label before distributing or selling the product bearing the revised labeling Should you have any questions concerning this letter please contact Velma Noble at (703) 308 8233 or Jamil Mixon at (703) 308 8032

Sincerely



Velma Noble  
Product Manager (31)  
Regulatory Management Branch I  
Antimicrobials Division (7510P)

Enclosure Stamped Label

**MASON CHEMICAL COMPANY**  
The Quaternary Specialists

721 W. Algonquin Road | Arlington Heights, IL 60005 | 847 290 1621 or 800 362 1855

EPA Reg No 10324 205  
EPA Est No 10324 IL 1

# MAQUAT® LC12S-10%FC

Net Contents

Batch No

### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER Keep Out of Reach of Children** Corrosive Causes irreversible eye damage and skin burns Harmful if swallowed or absorbed through the skin Do not get into eyes on skin or on clothing Wear goggles or face shield and rubber gloves and protective clothing when handling Wash thoroughly with soap and water after handling and before eating drinking chewing gum using tobacco or using the toilet Remove contaminated clothing and wash clothing before reuse

*(If container is larger than 5 gallons the following statement must appear on the label)*

#### ENVIRONMENTAL HAZARD

This pesticide is toxic to fish aquatic invertebrates oysters and shrimp Do not discharge effluent containing this product into lakes streams ponds estuaries oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority For guidance contact your State Water Board or Regional Office of the EPA

*(For containers up to and including 5 gallons use the following environmental hazard)*

#### ENVIRONMENTAL HAZARD

This product is toxic to fish

#### PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame or in car  
Do not mix with oxidizers anionic soaps and detergents

#### FIRST AID

Have the product container or label with you when calling a poison control center or doctor or going for treatment

**IF ON SKIN OR CLOTHING** Take off contaminated clothing Rinse skin immediately with plenty of water for 15 20 minutes Call a poison control center or doctor for treatment advice

**IF IN EYES** Hold eye open and rinse slowly and gently with water for 15 20 minutes Remove contact lenses if present after first 5 minutes then continue rinsing eye Call a poison control center or doctor for treatment advice

**IF SWALLOWED** Call a poison control center or doctor immediately for treatment advice Have person sip a glass of water if able to swallow Do not induce vomiting unless told to do so by a poison control center or doctor Do not give anything by mouth to an unconscious person

**NOTE TO PHYSICIAN** Probable mucosal damage. **DO NOT** indicate the use of gastric lavage

**with COMMENTS**  
in EPA Letter Dated.

**AUG 31 2012**

Under the Federal Insecticide Fungicide and Rodenticide Act, as amended for the pesticide registered under EPA Reg No. 10324-205

For Control of Algae and Algal Slime Growth in Swimming Pools (Outside) Spas/Whirlpools/Hot Tub Baths (Contained) Decorative Fountains and Pools Industrial and/or Commercial Recirculating Cooling Water Towers Auxiliary Water and Waste Water Systems Oil Field Water Flood/Salt Water Disposal Systems Retort Water Systems and Mold Mildew and Fungi in Sap Stains and Wood Preservatives Controls bacteria and fungal slimes in pulp paper mills and paper manufacturing (Outside description and the use site Retort Water Systems not for use in California Contained description must be used in California)

(Product of USA) (Made in the USA)

#### ACTIVE INGREDIENTS

n-Alkyl (67% C<sub>12</sub> 25% C<sub>14</sub> 7% C<sub>16</sub> 1% C<sub>18</sub>) dimethyl benzyl ammonium chloride

#### INERT INGREDIENTS

#### TOTAL

10.0%  
90.0  
100.0

Weight Approx 8lbs/gallon

## KEEP OUT OF REACH OF CHILDREN

## DANGER PELIGRO

See left (back) (side) (right) panel (of label) (below) for additional precautionary statements and first aid statements

*(Note to Reviewer This information has been verified per DOT regulations It is NOT required to be on the label but is being requested by a customer)*

#### Transportation Information

DOT Hazard Class Non corrosive

DOT Proper Shipping Name Not applicable

**PELIGRO SI NO PUEDE LEER EN INGLES PREGUNTE A SU SUPERVISOR SOBRE LAS INSTRUCCIONES DE USO APROPIADAS ANTES DE TRABAJAR CON ESTE PRODUCTO**

**DANGER IF YOU CANNOT READ ENGLISH ASK YOUR SUPERVISOR TO EXPLAIN THE APPROPRIATE DIRECTIONS FOR USE BEFORE WORKING WITH THIS PRODUCT**

(Manufacturing and/or Lot no Date)

3/12

10% Concentration

Kills and prevents all type of Algae

This formulation (Maquat<sup>®</sup> LC12S 10%FC) is for use in

- Industrial and/or commercial recirculating cooling water towers
- Once through water cooling systems
- Paper mills and paper mill process water systems
- Oil field water flood or salt water disposal system and fracturing fluids
- Oil field injection and waste water
- Gas production and transmission pipelines and systems
- Gas storage wells and systems
- Pipeline pigging and scraping operations
- Drilling completion and workover fluids systems
- Packer fluids
- Hydrotesting

This product has been designed specifically for control of sulfate reducing bacteria (SRB) that contribute to souring the production of sulfide and abiotic corrosion in water cooling systems, paper mill process water systems, oil field systems, gas production and transmission pipelines and systems

A microbicide for use in controlling sulfate reducing bacteria and slime forming bacteria in oil well drilling oil field processing applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields and equipment such as steam injection water holding tanks, flood water injection water holding pond water disposal well water holding tanks, fuel storage tanks and related refinery and oil field closed industrial recirculating water handling systems

A highly effective microbicide for use in controlling bacteria including slime forming bacteria and sulfate reducing bacteria (SRB) and fungi (yeast and molds) and algae in air washers and industrial scrubbing systems, recirculating cooling and process water systems including those that contain reverse osmosis membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including wastewater sludge and holding tanks and in paper mills and paper mill process water systems and water based coatings for paper and paperboard

This product is efficient and stable in use dilution

This product is compatible with most chemicals used in pool water and will not damage tile, concrete, metal or plastics

This product keeps pool water free and sparkling, clear of visible green and blue green algae, slime and green brown colors

This product improves filter operation and reduces need for other chemicals

This product imparts tone and a pleasant feel to swimming pool water

This product is formulated to complement swimming pool water being treated with normal chlorine systems. It is especially effective against growth of algae and being non-volatile aids in maintaining pool water clarity and sparkle. The residual effectiveness of this algacide tends to stabilize the total chemical treatment system

This product is compatible with most chemicals normally used in swimming pool maintenance; however, in its concentrated form, this chemical must not come in contact

with high concentrations of chlorine or any other oxidizer. **DO NOT MIX THIS PRODUCT AND CHLORINE OR ANY OTHER OXIDIZER TOGETHER** before adding to the pool. These chemicals must be handled separately.

This product was formulated to complement most swimming pool sanitizers. This product is not a stand alone product; it must be used with either halogen based or non-halogen based pool sanitizers. This product supports your overall pool chemical maintenance program, offering a residual effectiveness that protects your pool against algae formation while keeping your pool water sparkling clear. This product protects the unattended pool when you're away (refer to Vacation Treatment section in Directions For Use).

### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Please read entire label and use strictly in accordance with precautionary statements and directions.

Do not use water containing residues from use of this product to irrigate crops for food or feed.

Use of the product in either public/municipal or single or multiple family private/residential potable/drinking water systems is strictly prohibited. Use of the product in any cooling water system that discharges effluent within 1/2 mile of either a public/municipal or single or multiple family private/residential potable/drinking water intake is strictly prohibited.

### INDUSTRIAL WATER TREATMENT

This product aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, influent systems such as flow through filters and lagoons, industrial water scrubbing systems and brewery pasteurizers.

### INDUSTRIAL AND/OR COMMERCIAL RECIRCULATING COOLING WATER TOWERS, RETORT WATER SYSTEMS, EVAPORATIVE CONDENSERS, HEAT EXCHANGE WATER SYSTEMS, INFLUENT SYSTEMS

(Note: Retort Water Systems use site not applicable in California)

- 1 Dosing Location** This product is to be applied at a point in the system where it will be uniformly mixed, such as at the sump.
- 2 Dosing Conditions** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.
- 3 Method Of Application**

#### a INTERMITTENT OR SLUG METHOD

**Initial Dose** When the system is noticeably fouled, apply 12.8 to 25.6 fluid ounces (20 to 40 ppm on an active quaternary basis) per 500 gallons of water in the system. Repeat until control is achieved.

**Subsequent Dose** When microbial control is evident, add 6.4 to 19.2 fluid ounces (5 to 15 ppm on an active quaternary basis) per 1000 gallons of water in the system twice weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

#### b MODIFIED INTERMITTENT METHOD

**Initial Dose** When the system is noticeable fouled, apply 12.8 to 25.6 fluid ounces (20 to 40 ppm on an active quaternary basis) per 500 gallons of water in the system. Apply half of this initial dose when half of the water in the system has been lost by blowdown.

ACCEPTED  
with COMMENTS  
fracturing fluids Dated.

FUL 31 2012

Under the Federal Insecticide  
Fungicide and Rodenticide Act as  
amended for the pesticide  
registered under EPA Reg No.

10324-205

**Subsequent Dose** When control of microbial growth is evident apply 6.4 to 19.2 fluid ounces (5 to 15 ppm on an active quaternary basis) per 1000 gallons of water in the system. Apply half of this subsequent dose when half of the water in the system has been lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

(OR)

#### INTERMITTENT OR SLUG METHOD

When this treatment is required add this product at the rate of 12.8 to 25.6 ounces per 500 gallons of water already in the system or being added to the system for 4 to 8 hours. 1 to 4 times per week or as needed to achieve the desired level of control. When control is obtained add this product at the rate of 6.4 to 19.2 ounces per 1000 gallons of water in the system.

#### c CONTINUOUS FEED METHOD

**Initial Dose** When the system is noticeably fouled apply 12.8 fluid ounces (20 ppm on an active quaternary basis) per 1000 gallons of water in the system.

**Subsequent Dose** Maintain this treatment by starting a continuous feed of 6.4 fluid ounces (5 ppm on an active quaternary basis) per 1000 gallons of water lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

#### ONCE THROUGH FRESH AND SEA WATER COOLING SYSTEMS

**1 Dosing Location** This product is to be applied at a point in the system where it will be uniformly mixed such as at the sump.

**2 Dosing Conditions** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficacy is already impaired.

#### 3 Method Of Applications

##### a INTERMITTENT OR SLUG METHOD

**Initial Dose** When the system is noticeably fouled apply 0.75 to 7.5 fluid ounces (0.6 to 6 ppm on an active quaternary basis) per 1000 gallons of water based on system flow rates. The minimum treatment is 6 to 24 hours. Repeat until control is achieved. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum ratio of 5 ppm clay to 1 ppm product.

**Subsequent Dose** When microbial control is evident add 3/8 to 3/75 fluid ounces (0.3 to 3 ppm on an active quaternary basis) per 1000 gallons of water based upon system flow rates on a as needed basis to maintain control. Frequency of feed must be tied to an in plant monitoring program for macro clogging growth. Deactivation must be conducted prior to discharge from the system by using bentonite clay at a minimum ratio of 5 ppm clay to 1 ppm product.

**DEACTIVATION** Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. This product must be deactivated prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

(OR)

**1 ONCE THROUGH FRESH AND SEA WATER COOLING SYSTEM** ACCEPTED  
This product is to be applied at a point in the system with COMMENTS

**2 Dosing location** This product must be applied when the system is in jeopardy in EPA Letter Dated 11/22/90

**3 Dosing conditions** This product must be applied when the system is already being affected or after cleaning systems where efficiency is already impaired.

**Method of applications**

a Wear safety glasses, rubber gloves and impervious apron. Under the Federal Insecticide, Fungicide and Rodenticide Act as amended for the pesticide registered under EPA Reg. No. 127-4221

b To reduce foaming mix 10 parts of water to 1 part of this product.

c Add product directly from drum or add the product at a point where it will be mixed uniformly.

d Use 0.75 to 7.5 fluid ounces (0.6 to 6 ppm on an active quaternary basis) per thousand gallons.

e Do not discharge without performing proper deactivation. To perform deactivation use Bentonite Clay. The minimum ratio to be used is 5 ppm of clay to 5 ppm of product.

f Do not use product more than 4 times per year.

g Treatment time cannot exceed 120 hours/application.

h Avoid oxidizers and reducing agents. Product is cationic and must not be mixed with soap or anionic surfactants.

**TO DEACTIVATE** Use bentonite clay at the minimum ratio of 5 ppm clay to 1 ppm product. Deactivation must occur prior to discharge of the NPDES outfall. Do not apply this product more than 4 times a year.

#### OIL FIELD & GAS PRODUCTION TREATMENT

Specific treatment requirements vary among oil and/or gas field sites and subsystem components. The Primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump, equipment suction (low pressure) side of pumping equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis depending on the degree of system fouling.

OR

Specific treatment requirements vary among oil and/or gas field sites and subsystem components. Oil field fluids and subsystems most commonly requiring microbial contamination control are raw water sources, separators, ballast storage and mixing tanks, screens, surface injection equipment, production equipment (such as injection and production piping, casting, completion and valving) and the formation itself. The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump, equipment suction (low pressure) side of pumping equipment or similar device. This product can be added to the system by slug, continuous or on an intermittent basis depending on the degree of system fouling.

#### OIL FIELD WATER FLOOD OR SALT WATER DISPOSAL SYSTEMS AND FRACTURING FLUIDS

This product must be added to the water flood or salt water disposal system at a point of uniform mixing.

**1** For the control of slime forming and sulfate reducing bacteria in oil field water flood or salt water disposal systems, add 5 - 10 ppm (active) of this product (4.7 - 9.5 gallons per 3,000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.

**2** For intermittent use, dose at rate of 5 - 20 ppm (active) of this product (4.7 - 18.9 gallons per 3,000 barrels of water) for 4 to 8 hours per day, one to four times a week as needed to maintain control.

**3** For treatment of flow back return water (Post Hydraulic Fracturing - Dose at a rate of 5.20 ppm active of this product (4.7 - 18.9 gallons per 3,000 barrels of water) for 4 to 8 hours per day, one to four times a week as needed to maintain control.

### OILFIELD INJECTION AND WASTE WATER

This product must be added to the water handling system at a point of uniform mixing such as the area of addition of make up water to the holding tank

#### Method of application

- CONTINUOUS INJECTION** Add this product at 30 ppm active (38.4 ounces per 1000 gallons of water) when system is noticeably fouled When microbial control is evident add this product at 15 ppm active (20 fluid ounces per 1000 gallons of water) to maintain control
- BATCH TREATMENT** Add this product at 180 ppm active (230.4 ounces per 1000 gallons of water) over a period of 4 - 6 hours one or more times per week when the system is noticeably fouled When microbial control is evident add this product at 90 ppm active (115 fluid ounces per 1000 gallons of water) over a period of 4 - 6 hours one or more time per week

OR

For use in oil field and/or petrochemical water subsurface injection systems of secondary and/or tertiary oil recovery systems to reduce the number of anaerobic bacteria aerobic bacteria sulfate reducing bacteria

- DOSING LOCATION** (site of use) This product is to be applied at a point in the recovery system where it will be uniformly mixed such as at the screens storage tanks and other mixing device locations
- DOSING CONDITIONS** This product should be applied when the system is in jeopardy of being affected Badly fouled systems must be cleaned before treatment is begun
- EQUIPMENT USED** Use the injection pump to apply the product
- USE LIMITATIONS** Dependent upon pH temperature and salt content adjust according to conditions found at the site as needed to maintain control
- DOSAGE APPLICATIONS**

#### a SLUG METHOD

**Initial Dose** When the system is noticeably fouled apply 56.5 gallons (60 ppm active ingredient) of this product per 1000 gallons of water in the system Apply for 3 to 8 hours daily until control is achieved

**Subsequent Dose** When microbial control is evident add 28.25 gallons (30 ppm active ingredient) of this product per 1000 gallons of water in the system daily or as needed to maintain control

#### b INTERMITTENT DOSAGE

**Initial Dose** When the system is noticeably fouled apply 56.5 gallons (60 ppm active ingredient) of this product per 1000 gallons of water in the system Apply for 3 to 8 hours daily until control is achieved

**Maintenance Dose** When control of microbial growth is evident apply 28.25 gallons (30 ppm active ingredient) of this product per 1000 gallons of water in the system daily or as needed to maintain control

#### c CONTINUOUS FEED METHOD

**Initial Dose** When the system is noticeably fouled apply 56.5 gallons (60 ppm active ingredient) of this product per 1000 gallons of water in the system

**Subsequent Dose** Maintain this treatment by starting with 30 ppm active ingredient of 3.75 ounces (15 ppm active ingredient) of this product per 1000 gallons of water daily or as needed to maintain control

**ACCEPTED**  
With COMMENTS  
Fungicide and Rodenticide Act  
amended for the pesticide registered under EPA Reg No  
10324-305

### OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS

For the control of sulfate reducing bacteria and slime forming bacteria this product must be added at a point in the production or transmission pipeline via direct injection where uniform The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates To facilitate applications it is desirable to dilute the product with an appropriate solvent immediately before use The concentration in the solvent must not fall below an active concentration range of 500 to 5000 ppm based on the volume of water in the pipeline Injections to the system must be weekly or as needed to maintain control

#### GAS STORAGE WELLS AND SYSTEMS

Individual injection wells must be treated with a sufficient quantity of this product to produce concentration of 65 1000 ppm (on an active quaternary basis) when diluted by the water present in the formation Injection should take place before gas is injected (during the summer) Injection must be repeated yearly or as needed to maintain control

#### PIPELINE PIGGING AND SCRAPING OPERATIONS

Add this product to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper and the trail pig) Sufficient product is added to produce an effective concentration of 75 - 500 ppm on an active quaternary basis (9.6 to 64 ounces per 100 gallons of water) depending on the length of the pipeline and the severity of the biofouling

#### DRILLING COMPLETION AND WORKOVER FLUIDS SYSTEMS

This product is to be applied to these fluid systems at a point of uniform mixing such as a circulating holding tank and other mixing device locations

**Initial treatment** Add 65 - 1000 ppm (on an active quaternary basis) of this product (2.1 to 31.5 gallons of this product per 100 barrels) to a freshly prepared fluid Levels for effective control will vary depending on conditions at the site and the severity of the contamination

**Maintenance dosage** Add 65 - 1000 ppm (on an active quaternary basis) of this product (2.1 to 31.5 gallons of this product per 100 barrels) to a freshly prepared fluid Levels for effective control will vary depending on conditions at the site and the severity of the contamination

#### PACKER FLUIDS

This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank and other mixing device locations Add 2.1 to 31.5 gallons (65 - 1000 ppm active quaternary basis) of this product per 100 barrels of packer fluid The product is applied to a freshly prepared fluid Levels for effective control will vary depending on conditions at the site and the severity of the contamination Seal the treated packer fluid in the wall between the casing and the production tube

#### HYDROTESTING

Treat water in the hydrotest pipelines or vessels with 65 - 1000 ppm on an active quaternary basis (0.65 - 10 gallons of this product per 1000 gallons of water) of this product depending on the water quality and length of time the equipment will remain idle

#### AUXILIARY SERVICE WATER AND WASTE WATER SYSTEM

This product is effective for the control of odor forming and slime forming bacterial fungi and algae in auxiliary service water systems such as fire protection systems and pump or screen bays water waste systems such as storage tanks storage piles associated piping setting ponds or lagoons transport spillways or canals and disposed wells

Add 5 - 180 ppm (active) of this product (0.95 34 gallons per 3 000 barrels of water) continuously This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing

### PULP AND PAPER MILLS

#### SLIMICIDE APPLICATIONS

This product can be used as a slimicide in the manufacture of paper and paperboard that contacts food depending on the type of stock quality of raw water complexity of the system and degree of contamination Apply this product intermittently or continuously depending on mill conditions to the paper making system at a point of uniform mixing such as a the beaters thin or thick stock chests broke chest pump save all tank process tank or whitewater tank

**Initial Dose** When system is noticeably contaminated add 4 to 800 pounds of this product per 100 000 gallons of whitewater to be treated (1 0 to 200 ppm of product) as a continuous or slug dose Repeat until control is achieved Heavily fouled systems must be boiled out prior to initial treatment

**Subsequent Dose** When microbial control is evident add 1 to 100 gallons of this product per 100 000 gallons of whitewater to be treated (1 0 to 100 ppm of product) as necessary to maintain control

**Dosing Application** This product is to be applied at a point in the system where it will be uniformly mixed such as at the suction side of a pump This product must be fed as early as possible in the system Additions of this product must be made at a point in the system where mixing action is good Suitable sites are the hydropulper suction side of the machine chest or broke system pump Badly fouled process systems must be cleaned before initial treatment

#### CONTROL OF BACTERIAL FUNGI/MOLD AND ALGAE ON PULP PAPERBOARD & WET LAP

This product is used to inhibit fungal growth which causes discoloration odor and degradation of paper paperboard or wet lap Application of this product must be made at a point in the system where mixing action is good Application can also be made at the size press or water box Apply at a rate of 2 to 400 pounds of this product per ton (dry basis) of pulp or paperboard produced

**Dosing Application** This product may be drip fed continuously from the drum diluted and showered to the wet sheet or fed by suitable pumps

For inhibition of wet lap or sheet pulp this product must be applied to the dewatered pulp surface via applicator rolls or showers Application can also be made at the size press or water box

#### SAP STAIN

For the control of mold and fungus on green or freshly cut lumber May be used in a dip or spray application Before use dilute at rate of 25 100 gallons of water per 5 gallons of this product Seasonal variations in storage and shipping conditions species and condition of wood must be considered in a manner that ensures that all surfaces are uniformly treated For effective inhibition of mold and fungus lumber and logs must be dipped or sprayed in a manner that ensures that all surfaces are uniformly treated

For best results green wood must be treated immediately at least within twenty four hours after cutting or sawing Mold and fungus growth begins immediately after cutting

so delayed treatment is much less effective and requires increased chemical concentration Green untreated lumber must not be used for stickers

Freshly treated lumber must not be allowed to remain unprotected in heavy rains Dip tanks and drip aprons must be roofed paved and drained to prevent dilution and loss of the anti stain solution

Treated lumber must be stored under cover or indoors or at least 100 feet from any pond lake stream wetland or river to prevent possible runoff of the product into the waterway Treated lumber stored outdoors within 100 feet of a pond lake stream wetland or river must be either covered with plastic or surrounded by berm to prevent surface water runoff into the nearby waterway If a berm is used around the site it must consist of impermeable material (clay asphalt concrete) and be of sufficient height to prevent runoff during heavy rainfall events

#### WOOD PRESERVATIVES

This product is a concentrated biocide for use as a wood preservative When used as directed this product will protect treated wood articles from the destructive attack of fungi mold mildew and both Reticulitermes and Formosan species of termites Treatment can be done by pressure double vacuum dip brush and/or spray although dip brush and spray can not be used for protection against termites Wood articles that will be protected by these treatments would include millwork construction timber decking wood shingles posts and other articles to be used in above ground applications

(OR)

This product will protect treated wood articles from the destructive attack of fungi mold or mildew Treatment can be done by pressure or double vacuum Wood articles that will be protected by these treatments would include millwork construction timbers decking wood shingles posts and other articles to be used in above ground applications

OR

Treatment can be done by brush or spray for wood shingle applications and by pressure double vacuum or dip method for other wood products Wood articles that will be protected by these treatments would include millwork construction timbers decking wood shingles and posts

This product can be used in combination with other EPA registered organic and inorganic wood preservatives or it can be used alone

#### MAQUAT® LC12S 10% FC

Dilute this product in either water or mineral spirits (or Sentry GoldSeal™) to produce a 0.5% to 3.0% active quaternary ammonium compound solution

Percent Active Quat Solution	ACQUANCES of this product per gallon
0.5	6 40
1.0	12 80
1.5	19 25
2.0	25 60
2.5	32 00
3.0	38 40

To find the ounces of this product per gallon of water, dilutions take the percent active desired and divide by 0.3906

#### MAQUAT® LC12S 10% FC AND COPPER COMPOUNDS

Mix this product with water and either (ACQ C2 EPA Reg No 10465 36 or ACQ C EPA Reg No 10465 33) (NW 100 C EPA Reg No 3008 87 or NW 200 C EPA Reg No 10465 33 3008) Refer to the product labels for (ACQ C and ACQ C2) (NW 100 C and

NW 200 C) for precise mixing instructions **This product is only to be used in combination with copper compounds in pressure treatment applications**

#### **MAQUAT® LC12S 10 %FC AND BORATES**

Mix this product and either (Disodium Octaborate Tetrahydrate) Wood Bor EPA Reg No 3008 61 Envirotech Insecticide EPA No 65705 1 Timbersaver EPA Reg No 71916 1 TimberSaver PT EPA Reg No 71916 1 10465 Tim Bor EPA Reg No 1624 39 Cellu Treat DOT Wood Preservative EPA Reg No 64405 8 Bor Ram EPA Reg No 72304 10 or Borathor Max PT EPA Reg No 81824 11 in water Refer to the product labels for precise mixing **This product may only be used in combination with the above borates in pressure treatment or dip treatment applications**

Mix this product and Lum Bor EPA Reg No 19713 286 in water Refer to the product label for precise mixing instructions **This product may only be used in combination with the above borate in brush or spray applications**

Mix this product and BORA CARE EPA Reg No 64405 1 in water Refer to the product label for precise mixing instructions **This product may only be used in combination with the above borate in dip treatment applications**

#### **MAQUAT® LC12S 10 / FC AND PROPICONAZOLE**

Mix this product with Woodlife P EPA Reg No 1409 65 and dilute with water mineral spirits or other light organic solvent to produce a 0.5 to 3.0% quaternary ammonium compound solution Follow the instructions on the Woodlife P label for the appropriate concentration of propiconazole **PLEASE NOTE THAT THIS FORMULATION CAN ONLY BE USED FOR DIP TREATMENT**

#### **PRESSURE TREATMENT**

Place the wood article to be treated into the pressure cylinder and seal unit Treat the wooden articles using the pressure treatment procedures consistent with the equipment being used and standard treatment practices Treatment conditions must be such as to produce a 0.1 to 0.6 lb/cu foot retention in the treatment article Such treated wood is to be used for above ground uses only

#### **DOUBLE VACUUM**

Stack the wooden articles to be treated in the treatment vessel so that the preservative solution will have access to all sides of the articles Seal the vessel Reduce the pressure within the vessel to -10 inches for 5 minutes Cover all the articles with preservative solution Allow the pressure to return to atmospheric conditions and discharge the preservative solution Reduce the pressure to -20 in and maintain for 20 minutes Allow the pressure to return to atmospheric and remove treated wood articles Treatment conditions must be used as to produce a 0.1 to 0.6 lbs/cu ft retention of ADBAC in the treated article Wood treated to this retention for above ground use only

#### **DIP TREATMENT**

Stack the wood to be treated on a suitable holder and convey the stack into the treating solution making sure the stack is completely immersed Dip times must range from 30 seconds (individual pieces) up to 30 minutes (bundled wooden articles) Use a concentration of 0.5 to 3.0% active quaternary ammonium compound The concentration should be customized to the degree of sap stain protection desired which must be determined by an independent test on the intended species of wood

#### **PERSONAL PROTECTION EQUIPMENT FOR PRESSURE TREATMENT DOUBLE VACUUM AND DIP TREATMENT**

Applicators must wear gloves which are chemical resistant (such as nitrile or butyl) in all situations where dermal contact is expected (i.e. handling freshly treated wood and manually opening cylinder doors) Individuals who enter pressure treatment cylinders and other related equipment that are contaminated with the wood treatment solution

(e.g. cylinders that are in operation or are not free of all treatment solution) must wear coveralls over a long sleeved shirt and long pants socks chemical resistant footwear and protective eyewear Federal State and local confined space entry procedures need to be taken

Applicators must not eat drink or use tobacco products during those parts of the applications process that may expose them to the wood treatment formulation (e.g. manually opening/closing cylinder doors moving trams out of cylinders mixing chemicals handling freshly treated wood)

Wash thoroughly after skin contact and before eating drinking use of tobacco products or using restrooms

Protective clothing must be changed when it shows signs of contamination Applicators must leave protective clothing and work shoes or boots and equipment at the plant Worn out protective clothing and work shoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations

#### **BRUSH OR SPRAY**

A 0.5% to 3.0% active solution with water (or Sentry GoldSeal™) may be applied by brush or spray for use on wood shingles or shake roofs and siding on existing homes by commercial applicators and on interior construction products and surfaces such as lumber concrete sheetrock wallboard block and steel Use low pressure equipment for spray applications A moderately fine spray not an aerosol or fog generally provides the best coverage at practical product concentrations Apply only to point of runoff To make a 0.5% to 3.0% active solution use the following table

Percent Active Quat Solution	Ounces of this product per gallon
0.5	6.40
1.0	12.80
1.5	19.25
2.0	25.60
2.5	32.00
3.0	38.40

To find the ounces of this product per gallon for other dilutions take the percent active desired and divide by 0.3906

#### **PERSONAL PROTECTION EQUIPMENT FOR BRUSH AND SPRAY APPLICATIONS**

Applicators must wear gloves which are chemical resistant (such as nitrile or butyl) Applicators must also wear coveralls over a long sleeved shirt and long pants socks chemical resistant footwear and protective eyewear Applicator must not eat drink use tobacco during the application process Use with adequate ventilation Mist or v.c. generated by spraying this product may be harmful if inhaled Wash thoroughly after skin contact and before eating drinking use of tobacco products or using restrooms Protective clothing must be changed when it shows signs of contamination Brush/Spray treatment may require frequent changing Discard clothing and other absorbent materials that have been drenched or heavily contaminated Do not reuse them

Follow manufacturers instructions for cleaning and disinfecting protective equipment If no such instructions exist for washables use a mild detergent water Keep and wash protective equipment separate from other laundry

Worn out protective clothing and work shoes or boots must be disposed of in a manner approved for pesticide disposal and in accordance with State and Federal regulations

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended for the pesticide registered under EPA Reg No / 0334-905

ACCEPTED  
WITH COMMENTS  
in EPA Label dated  
MAY 13 2012



## SWIMMING POOLS

This product requires no special equipment for treating swimming pool water. The correct use dilution may be added directly to the pool in any spot or added to the water circulation equipment. This product works the best when added by itself directly to pool water.

### IMPORTANT NOTES

- 1 Do not allow swimming in pool for at least 15 minutes after this product has been applied
- 2 Always apply this and other pool treatment chemicals separately never combine them
- 3 Sunlight rainfall temperature number of swimmers and frequency of pool use all affect the rate at which unsanitary pool water conditions develop. Adjust your pool cleaning and maintenance functions accordingly.

### BEFORE YOU BEGIN

- 1 Make sure all pool equipment is working properly including pump filter skimmer and heater. Allow the filter to run for at least 6 hours after adding algaecide
- 2 Backwash filter following normal procedure for your pools filter
- 3 Check water pH (acidity/alkalinity balance) with a Test Kit following label direction. Desired pH range is between 7.2-7.6. If necessary adjust pH by adding pH increaser to lower pH or pH increaser to raise pH
- 4 Recheck pH and maintain it between 7.2-7.6 for at least 6 hours before adding this product
- 5 Add this product directly into pool by pouring around entire outside perimeter of pool

### INITIAL APPLICATION FOR SWIMMING POOLS

- 1 Backwash the filter thoroughly
- 2 Vacuum algae debris and thoroughly brush pool
- 3 Add 2.56 ounces of this product to each 10,000 gallons of water or ratio thereof. Add this product directly into pool by pouring around entire outside perimeter of pool
- 4 Vacuum pool after 24 hours to remove dead algae
- 5 If algae is still visible repeat dose (steps 3 & 4) as necessary until pool is free of visible algae
- 6 Once algae are under control clean filter and return to normal operation

### MAINTENANCE APPLICATION

Add one (1) quart of this product in 50,000 gallons of water every 3-5 days. Add this product directly into pool by pouring around entire outside perimeter of pool.

### BOOSTER APPLICATION

Use one (1) quart of this product in 50,000 gallons of water after a heavy rainfall or when there is a heavy bathing load. Add this product directly into pool by pouring around entire outside perimeter of pool. If algae growth is noticeable apply initial dose.

**THE ABOVE DIRECTIONS MUST BE FOLLOWED EVEN WHEN THE POOL IS NOT IN USE**

OR

**INSTRUCTIONS FOR USE WITH HALOGEN BASED POOL SANITIZERS**  
This product is formulated to complement most swimming pool sanitizers. For use on those products always follow Directions For Use of those products. This product is effective against the growth of algae. This product is efficient and non-staining when used as directed. This product will

not evaporate and its algae fighting abilities actually increase as pool water temperature increases.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturers directions. Adjust pH between 7.2-7.6. Adjust chlorine residual to 1-3 ppm. In a chlorine treated pool add stabilizer to establish a minimum level of 40-50 ppm to reduce the degradative effects of sunlight upon the chlorine residual. Check for metals and if present add stain and scale inhibitor to prevent staining of pool surface due to metals. Check chlorine residual and adjust to 1-3 ppm. Maintain sanitizer residual in accordance with label directions found on your sanitizer of choice. When using other products as outlined in directions for this product always follow directions on those products.

Add this product directly into pool by pouring around entire outside perimeter of pool. Allow the filter to run for at least six (6) hours after adding algaecide. During this period do not allow swimmers in the water.

### Initial Application for Swimming Pools

- 1 Backwash the filter thoroughly
- 2 Vacuum algae debris and thoroughly brush pool
- 3 Add 26 ounces of this product per 10,000 gallons of water or ratio thereof
- 4 Vacuum pool after 24 hours to remove dead algae
- 5 If algae is still visible repeat dose (steps 3 & 4) as necessary until pool is free of visible algae
- 6 Once algae are under control clean filter and return to normal operation

### Maintenance Application

Add one quart of this product in 50,000 gallons of water every 3-5 days or as needed.

### Booster Application

Add one quart of this product in 50,000 gallons of water after a heavy or prolonged rainfall or when there is a heavy bathing load.

The above directions must be followed even when the pool is not in use.

If algae growth is noticeable apply initial dose.

### Vacation Treatment

When you are going to be away for one week or more add 24 ounces of this product per 10,000 gallons of water for every week unattended. Pour product around the edges of the shallow end of the pool. If shock is also being applied in the deep end of pool.

### OPTIONAL INSTRUCTIONS FOR USE WITH NON-HALOGEN BASED POOL SANITIZERS

This product is formulated to complement swimming pool water being treated with BioGuard Softswim System, Bacquacil and other non-halogen systems. When using other products as outlined in Directions For Use for this product always follow Directions For Use of those products. This product is efficient and non-staining when used as directed. This product will not evaporate and its algae fighting abilities actually increase as the pool water temperature increases. The residual effectiveness of this product tends to stabilize the total chemical treatment system.

Ensure all pool equipment is working properly. Backwash the filter system following manufacturers directions. Adjust pH between 7.2-7.6. Check for metals and if present add stain and scale inhibitor to prevent staining of pool surface due to metals.

Add this product directly into pool by pouring around entire outside perimeter of pool. Allow the filter to run for at least six (6) hours after adding algaecide. During this period do not allow swimmers in the water.

9/12

**Initial Application for Swimming Pools**

- 1 Backwash the filter thoroughly
- 2 Vacuum algae debris and thoroughly brush pool
- 3 Add one gallon of this product to each 50 000 gallons of water (26 ounces per 10 000 gallons) or ratio thereof
- 4 Vacuum pool after 24 hours to remove dead algae
- 5 If algae is still visible repeat dose (steps 3 & 4) as necessary until pool is free of visible algae
- 6 Once algae are under control clean filter and return to normal operation

**Maintenance Application**

Add one quart of this product in 50 000 gallons of water every 3 5 days or as needed

**Booster Application**

Add one quart of this product in 50 000 gallons of water after a heavy or prolonged rainfall or when there is a heavy bathing load

The above directions must be followed even when the pool is not in use if algae growth is noticeable apply initial dose

**Vacation Treatment**

When you are going to be away for one week or more add 24 ounces of this product per 10 000 gallons of water for every week unattended Pour product around the edges of the shallow end of the pool if shock is also being applied in the deep end of pool

**WINTERIZING TREATMENT (Not applicable in California)**

When swimming pool season is over add 32 ounces of this product per 4 000 gallons (or ratio thereof) of water left in pool This dose helps provide a measure of control of algae growth during the winter months This treatment will also help the servicing of the pool before it is returned to use the following season

For persistent algae or slime producing organisms add 1 quart of this product into the skimmer with the filter pump running After one minute shut off pump and allow the system to remain off overnight The following day restart the filter pump and add 1 quart of this product to the pool Run filter continuously for 24 48 hours brushing the sides and bottom of the pool frequently

(Usage chart for one gallon containers)

Swimming Pool Capacity Gallon of Water	Initial Treatment	Maintenance Dose Booster Dose
5 000	12 8 ounces	3 2 ounces
10 000	25 6 ounces	6 4 ounces
20 000	51 2 ounces	12 8 ounces
25 000	64 0 ounces	16 0 ounces
30 000	76 8 ounces	19 2 ounces
40 000	102 4 ounces	25 6 ounces
50 000	128 0 ounces	32 0 ounces

(Or)

(Usage chart for one quart containers)

Swimming Pool Capacity Gallon of Water	Initial Treatment	Maintenance Dose Booster Dose
5 000	12 8 ounces	3 2 ounces
10 000	25 6 ounces	6 4 ounces

**ALTERNATE WINTERIZATION METHOD (not applicable in California)**

This product may be used with the following pool chemicals to form a winterization package

- 1 Add a maintenance dose of chloride or oxygen shock
- 2 Top up BioGuard Softswim System Bacquacil or other non halogen systems to 50 ppm
- 3 Add 32 ounces per 4 000 gallons (or ratio there of) of water left in pool This dose helps provide a measure of control of algae growth during the winter months This treatment will also help the servicing of the pool before it is returned to use the following season
- 4 Allow filter to run for several hours after chemical additions for good mixing

**Note** Before using chlorine or oxygen shock read the Directions for Use and Precautionary Statements specific to that product

**TO DETERMINE POOL CAPACITY**

**Rectangular Pools** Length (times) width (times) average depth (in feet) (times) 7 5 (equals) gallons

**Round and Oval Pools** Long diameter (times) short diameter (times) average depth (in feet) (times) 5 9 (equals) gallons

**OTHER**

**DIRECTIONS FOR USE IN (OUTSIDE) SPAS/WHIRLPOOLS/HOT TUBS**

(Outside description not for use in California)

**Initial Dose** Add 12 8 ounces of this product per 5 000 gallons of water Initial dose is used upon filling of (outside) spa/whirlpool/hot tub bath

**Maintenance Dose** Add 3 2 ounces of this product per 5 000 gallons of water Maintenance dose must be added at 3 5 day intervals if high temperatures prevail or (outside) spa/whirlpool/hot tub bath has unusually heavy use add maintenance dose more frequently Drain and clean outside spa/whirlpool/hot tub bath at least once a month or as needed depending upon bather load

**CONTROLLING ALGAE GROWTH**

**BIRD BATHS** Do not use with fish Clean to remove algae growth prior to filling birdbath Then spray all exposed surfaces with a solution of 1 ounce of this product per gallon of water Allow to air dry and brush off dead algae (Or)

**INSTRUCTIONS FOR BIRD BATHS**

This product is toxic to fish **DO NOT** use this product when fish are present

**Initial Dose**

- 1 Drain Bird Bath
- 2 Wipe mop or spray all exposed surfaces using 1 ounce of this product per gallon of water Spray device must be a mechanical coarse spray device when applied with spray device surfaces must be sprayed until thoroughly wetted to 2002
- 3 Allow to air dry and brush off dead algae Repeat if necessary until no algae is visible
- 4 Refill Bird Bath with fresh water

Under the Federal Insecticide Fungicide and Rodenticide Act as amended for the pesticide registered under EPA Reg No

10394-005

**Maintenance Dose** Repeat initial treatment when algae growth is observed  
**ALGAE CONTROL ON WALKWAYS** For heavy infestations spray or swab a solution of 1 ounce of this product per gallon of water Let stand for an hour or more then brush and wash away dead algae Soak area again with the solution Do not rinse Allow to (air) dry on the surface and repeat application when algae growth returns

10/12

**INSTRUCTIONS FOR (CONTAINERIZED) DECORATIVE FOUNTAINS AND POOLS**

(Note to Reviewer: *Containerized description must be used in California*)  
 This product is not to be used in open water ways connected to larger watersheds or in waters that serve as natural habitats for aquatic and amphibious organisms. **DO NOT** use when fish or other wildlife (for example amphibians) are present. This product is toxic to fish. **DO NOT** use this product when fish are present.

**Initial Dose**

- 1 Remove floating algae by raking, dragging with cable or chain or any other suitable method. It is more economical to remove floating type algae (if possible) before the water is treated.
  - 2 Add this product at any point that is convenient such as the bowl, pool or sump.
  - 3 Add 32 ounces per 12,500 gallons or ratio thereof.
- Weekly Maintenance Dose:** Add one quart of this product to each 50,000 gallons of water every 3-5 days or as to maintain 0.5 ppm active.  
 Each month drain and clean bowl. Refill with fresh water and repeat initial treatment. Draining removes airborne dirt, dust, contamination and alkali buildup.

Decorative Fountain or Pools Capacity in gallons of water	Initial Treatment	Maintenance Dose Booster Dose
12,500	32 ounces	8 ounces
6,250	16 ounces	4 ounces
3,125	8 ounces	2 ounces
1,562	4 ounces	1 ounce
781	2 ounces	1/2 ounce (1 Tablespoon)
390	1 ounce	1/4 ounce
195	1/2 ounce (1 Tablespoon)	0.125 ounces

(Note to reviewer: The title and first statement of this section must appear on every label followed by the appropriate Storage and Disposal section. Brackets [ ] indicate that one option within the brackets **MUST** be used in the final label text. Each option within the brackets is enclosed in a set of parenthesis ( ). All Notes are only for reviewers and **WILL NOT** be included on label.)

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage and disposal.  
 (For Swimming Pool Use and Decorative Fountains and Pools in nonrefillable containers in the Act as and including 5 gallons)  
 Nonrefillable container: Store in original container in areas inaccessible to children and pets. Keep from freezing. Offer for recycling if available or wrap and discard in trash. (See container label for recycling instructions.)  
 (For Swimming Pool Use and Decorative Fountains and Pools in containers over 5 gallons)  
**PESTICIDE STORAGE:** Store in original containers and place in locked storage area. Keep from freezing. Do not contaminate water, food, or feed by storage or disposal.  
**SPILL OR LEAK PROCEDURES:** Small spills may be mopped up or flushed away with water or absorbed on some absorbent material and incinerated.  
**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to the label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.  
**CONTAINER DISPOSAL:** Non-refillable container: Do not reuse container (bottle, cans, jars). Triple rinse (or equivalent). Offer for recycling if available or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.  
**(FOR USE ON NON REFILLABLE CONTAINERS WITH COMMERCIAL/INDUSTRIAL USES)**  
 (Note: For use on containers of 5 gallons or less.)

**PESTICIDE STORAGE:** Store only in original container. Keep from freezing. If a leaky container must be contained within another, mark the outer container to identify the contents. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL/RESIDUE REMOVAL:** Non-refillable container: Do not reuse empty container. Triple rinse as follows: Fill container / full with water and recap. Shake for 10 seconds. Follow Pesticide Disposal instructions for rinsate disposal. Drain for 10 seconds after the flow begins to drip. Repeat procedure two more times. Wrap container and put in trash or offer for recycling or reconditioning if not available. Puncture and dispose of in a sanitary landfill.  
**SPILL OR LEAK PROCEDURES:** Small spills may be mopped up or flushed away with water or absorbed on some absorbent material and incinerated. Large spills should be contained and the material then moved into containers and disposed of by approved methods for hazardous wastes.

**(FOR USE ON NON REFILLABLE CONTAINERS WITH COMMERCIAL/INDUSTRIAL USES)**  
 (Note: For use on containers greater than 5 gallons.)

**PESTICIDE STORAGE:** Open dumping is prohibited. Store only in original container. Keep from freezing. If a leaky container must be contained within another, mark the outer container to identify the contents. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** (Note: Only one of the following Container Disposal paragraphs will be used depending on packaging type.)

Non-refillable container: Do not reuse this container to hold materials other than pesticides or diluted pesticides (rinsate). Offer for recycling if available or puncture and dispose in a sanitary landfill or by other procedures approved by state and local authorities. If rinsate cannot be used follow pesticide disposal instructions.

(Note: Several of our customers' packaging options are sealed containers or bottles designed to reduce worker exposure to the concentrate. None of these can be triple-rinsed because they are closed sealed containers. The following text will be used on these non-refillable sealed container types only.)

Non-refillable container: Do not reuse or refill this container. Wrap empty container and put in trash.

**RESIDUE REMOVAL INSTRUCTIONS:** To clean the container before final disposal, empty the remaining contents from this container into (application equipment) (a mix tank). Fill / container / full with water. Replace and tighten closures. (Tip container on its side and rotate back and forth ensuring at least one complete revolution for 30 seconds, then stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times.) (Agitate vigorously or recirculate water for 30 seconds). Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times.

**(FOR USE ON REFILLABLE CONTAINERS WITH COMMERCIAL/INDUSTRIAL USES)**  
 (Note: For use on all refillable containers.)

Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

**PESTICIDE STORAGE:** Open dumping is prohibited. Store only in original container. If a leaky container must be contained within another, mark the outer container to identify the contents. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

11/12

12/12

**PESTICIDE DISPOSAL** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.


*(For use on all refillable containers except fixed tank containers)*

**CONTAINER HANDLING/RESIDUE REMOVAL INSTRUCTIONS** Refillable container. To clean the container before final disposal, empty the remaining contents from this container into (application equipment) (a mix tank). Fill the container / full with water. Replace and tighten closures. (Trip container on its side and roll it back and forth ensuring at least one complete revolution for 30 seconds then stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times) (Agitate vigorously or recirculate water for 30 seconds). Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Follow Pesticide Disposal instructions for rinsate disposal.

*(Note: To be used on fixed tanks only)*

**CONTAINER HANDLING/RESIDUE REMOVAL INSTRUCTIONS** Refillable container. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Drain rinsate into application equipment and dispose of according to Pesticide Disposal instructions. Triple rinse container (or equivalent) promptly after emptying. Continue to drain for 10 seconds after the flow ends. Repeat this procedure two more times.

Made in USA



[Optional - for use on residential use swimming pool and spa products]



ACCEPTED  
with COMMENTS  
in EPA Letter Dated.

NOV 31 2012

Under the Federal Insecticide  
Fungicide and Rodenticide Act as  
amended for the pesticide  
registered under EPA Reg No 10324-205