

10324-207

1/7/2011

1/7

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY



U.S. ENVIRONMENTAL PROTECTION AGENCY

Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Avenue NW
Washington, D.C. 20460

EPA Reg. Number: 10324-207

Date of Issuance: JAN -7 2011

Term of Issuance: Conditional

Name of Pesticide Product: Maquat 1412-40:10

NOTICE OF PESTICIDE:

[x] Registration
Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Mason Chemical Company
721 West Algonquin Rd.
Arlington Heights, IL 60005

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for re-registration of your product under FIFRA section 4.
2. Make the labeling changes listed below before you release the product for shipment:
a. Revise the EPA Registration Number to read, "EPA Reg. No. 10324-207".

Signature of Approving Official:

[Signature]
Velma Noble

Date:

JAN -7 2011

Product Manager Team-31

CONCURRENCES

Table with columns for SYMBOL, SURNAMES, and DATE, containing names like Regulatory Management Branch I and Antimicrobials Division (7510P).

- b. Revise the First Aid Statements to be ordered from most toxic to least toxic route of exposure as per PR Notice 2001-1 by placing the "If in Eyes" statement to precede the "If On Skin Or Clothing" statement.
- c. Your Storage and Disposal language must be revised. Your application (EPA Form 8570-1) list multiple container sizes (1 qt, 1gal, 5 gal, 55 gal, tote, and tank truck). Based on PR Notice 2007-4, the language must incorporate residue removal instructions that are comparable the container type. Therefore, the following instructions must be added:

For those containers less than 5 gallons

Under the **Pesticide Disposal** section, insert the statement "Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times"

Or, for those sections greater than 5 gallons

Triple rinse as follows: Empty the remaining contents into application equipment or mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip the container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two or more times.

Refillable Containers (Totes and Tank Trucks)

In the **Pesticide Disposal** section, insert the statement, "Refill the container with pesticide only. Do not reuse this container for any other purpose.

In the **Pesticide Disposal** section, insert the statement "Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

In the **Pesticide Disposal** section, instructions for cleaning each refillable container prior to disposal are required. The residue removal instructions must be appropriate for the characteristics and formulation of the pesticide product and must be adequate to protect human health and the environment. Please refer to PR Notice 2007-4, Appendix C (All Other Products in Refillable Container) for more information pertaining to what you could include in your labeling as appropriate residue removal statement.


(Storage and Stability) and OPPTs 830.6320 (Corrosion Characteristics) that are currently in progress and will be made available to the Agency upon their completion. The associated chemistry review is attached.

General Comments

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label and Exposure Assessment for this new use is enclosed for your records. Submit one (1) copy of your final printed labeling prior to release of this product for shipment. If you have any questions concerning this letter, please contact Emilia Oiguenblik at (703) 347 0199.

Sincerely,



Velma Noble
Product Manager 31
Regulatory Branch I
Antimicrobials Division (7510P)

Enclosure: DER 0381780 (Stamped Label)

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

AIR WASHERS AND INDUSTRIAL SCRUBBING SYSTEMS/RECIRCULATING COOLING AND PROCESS WATER SYSTEMS

This product may be used only in industrial air washers and air washers systems which have mist-eliminating components.

This product should be added at the application rates described below to a water treatment system at a convenient point of uniform mixing such as the basin area. Addition may be made intermittently (Slug Dose) or continuously. Badly fouled systems can be shocked treated with this product. Under these conditions, blowdown should be discontinued for up to 24 hours.

This product can be used in industrial process water systems that contain ultra filtration units and non-medical reverse osmosis membranes (where approved by membrane manufacturer) and associated distribution systems.

INTERMITTENT (SLUG DOSE) METHOD

Initial Dose: When the system is noticeably fouled, apply 12.8 to 25.6 fluid ounces (100 to 200 ppm) of this product per 1,000 gallons of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 5.1 to 12.8 fluid ounces (100 to 200 ppm) of this product per 1,000 gallons of water in the system weekly, or as needed to maintain control.

Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled apply 12.8 to 25.6 fluid ounces (100 to 200 ppm) of this product per 1,000 gallons of water in the system.

Subsequent Dose: Maintain this treatment level by starting a continuous feed of 2.56 to 12.8 fluid ounces (20 to 100 ppm) of this product per 1,000 gallons of water in the system per day.

Badly fouled systems must be cleaned before treatment is begun.

SERVICE WATER AND AUXILIARY SYSTEMS

This product should be used at the same application rates, and in the same manner as described above. It should be added to the system at a point that will allow for uniform mixing throughout the system.

HEART TRANSFER SYSTEMS

(Evaporative Condensers, Dairy Sweetwater Systems, Hydrostatic Sterilizers and Retorts, and Pasteurizers and Warmers)

This product should be used at the same application rates, and in the same manner as described above. It should be added to the system at a point of uniform mixing such as a basin area, sump area or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the system.

INDUSTRIAL WASTEWATER SYSTEMS

(Wastewater Systems, Wastewater Sludge and Wastewater Holding Tanks)

This product should be added to a wastewater system or sludge at a convenient point of uniform mixing such as digester. Add 0.5 to 2.5 gallons (500 to 2,500 ppm of this product) per 1,000 gallons of wastewater or sludge.

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

This product should be added to a paper making system at a point of uniform mixing such as the thin or thick stock chest, save-all tank, process tank or white water tank.

Initial Dose: When the system is noticeably contaminated, add 0.5 to 3.0 lbs. of this product per ton or 0.15 to 1.5 kg of this product per metric ton of pulp or paper (dry basis) as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 0.3 to 2.0 lbs. of this product per ton or 0.15 to 1.0 kg of this product per metric ton of pulp or paper (dry basis) as necessary to maintain control.

WATER BASED COATING, PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD

Note: For use in non-food contact coating only.

Use from 0.1 to 0.6 lbs. of this product per 1,000 lbs. of dry powder to produce a concentration of 100 to 600 ppm as product (based on slurry solids) in the mixed slurry.

WATER FLOODS

This product should be added to a water flood system at a point of uniform mixing.

Initial Treatment: When the system is noticeably contaminated, add 100 to 5,000 ppm of this product to the system (0.1 to 5.0 gallons of this product per 1,000 gallons flood water). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 20 to 5,000 ppm of this product (0.02 to 5.0 of this product per 1,000 gallons floodwater) to the system weekly, or as needed to maintain control.

FRAC FLUIDS

This product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations. Add this product to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down-hole.

Dose Range: This product should be added at a rate 100 to 5,900 ppm (0.1 to 5.9 gallons per 10,000 gallons), depending on the degree of bacterial fouling in the source water.

DRILLING, COMPLETION, AND WORKOVER FLUIDS

This product should be added to a drilling fluid system at a point of uniform mixing such as the circulating mud tank.

Initial Treatment: Add 50 to 1,000 ppm of this product (0.21 to 4.2 gallons of this product per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination.

Maintenance Dose: Maintain a concentration of 50 to 1,000 ppm of this product by adding 0.21 to 4.2 gallons of this product per 100 barrels of additional fluid, or as needed, depending on the severity of contamination.

PACKER FLUIDS

This product should be added to a packer fluid at a point of uniform mixing such as circulating holding tank. Add 50 to 600 ppm of this product (0.21 to 2.52 gallons of this product per 100 barrels of fluid) to a freshly prepared fluid depending on the severity of contamination. Seal treated packer fluid in the wall between the casing and production tube.

OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS

This product should be added to an oil/gas production or transmission line via direct injection. The application should be conducted to ensure maximum distribution of this product throughout the entire internal pipeline surface by adding a sufficient amount of biocide to detect/measure a residual concentration at the back end of the pipeline system. Criteria for success of the treatment will be a reduction in bacterial counts and/or reduced corrosion rates. To facilitate application, it may be desirable to dilute this product with an appropriate solvent immediately before use. The concentration in the solvent should not fall below an active concentration range of 500 to 5,000 ppm based on the volume of water in the pipeline. Injections to the system should be weekly, or as needed to maintain control.

GAS STORAGE WELLS AND SYSTEMS

Individual injection well should be treated with a sufficient quantity of this product to produce a concentration of 500 to 5,000 ppm of this product when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injections should be repeated yearly, or as needed to maintain control.

Individual drips should be treated with a sufficient quantity of this product to produce a concentration of 200 to 2000ppm of this product when diluted by the water present in the drip. Injections should be repeated yearly or as needed to maintain control.

HYDROTESTING

Water used to hydrotest pipelines or vessels should contain 100 to 4,000 ppm of this product (0.1 to 4.0 gallons of this product per 1,000 gallons water), depending on the water quality and length of time the equipment remains idle.

PIPELINE PIGGING AND SCRAPING OPERATIONS

Add the product to a slug of water immediately following the scraper. Ideally, this water volume can be kept to a minimum and contained between the scraper and a trailing pig. Sufficient product should be added to produce a concentration of 0.1 to 1.0% (0.1 to 1.0 gallon of this product per 100 gallons of water, depending on the length of the pipeline and the severity of biofouling.

(Note to reviewer: The title and first statement of this section must appear on every label, followed by the appropriate Storage and Disposal section.)

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

(FOR USE ON NON-REFILLABLE CONTAINERS WITH
INSTITUTIONAL/COMMERCIAL/INDUSTRIAL NON-PUBLIC HEALTH USES ONLY)

PESTICIDE STORAGE: Open dumping is prohibited. Store only in original container. Do not reuse empty container. If a leaky container must be contained within another, mark the outer container to identify the contents. Store pesticides away from food, pet food, feed, seed, fertilizers, and veterinary supplies. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING DISPOSAL: Non-refillable container. Do not reuse this container to hold materials other than pesticides or diluted pesticides (rinsate). Offer for recycling if available or puncture and dispose in a sanitary landfill, or by other procedures approved by state and local authorities. If rinsate cannot be used, follow pesticide disposal instructions. If not triple rinsed, these containers are acute hazardous wastes and must be disposed in accordance with local, state and federal regulations.

RESIDUE REMOVAL INSTRUCTIONS (For containers less than 5 gallons): Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

RESIDUE REMOVAL INSTRUCTIONS (For containers greater than 5 gallons): Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store for later use or disposal. Repeat this procedure two more times.

BATCH CODE: (Can be placed on container or label)

(FOR USE ON REFILLABLE CONTAINERS – 5 gallon and 55 gallon containers)

PESTICIDE STORAGE: Open dumping is prohibited. Store only in original container. If a leaky container must be contained within another, mark the outer container to identify the contents. Store pesticides away from food, pet food, feed, seed, fertilizers, and veterinary supplies. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING DISPOSAL: Triple rinse (or equivalent). Refillable container. Refill this container with this product only. Do not reuse this container for any other purpose.

RESIDUE REMOVAL INSTRUCTIONS (For containers greater than 5 gallons with Industrial/Commercial Non-public Health Uses): Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times.

Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill or by incineration.