

ACTIVE INGREDIENT: Calcium Hypochlorite 70% INERT INGREDIENTS: 30%

DIRECTIONS FOR USE IN INDUSTRIAL RECIRCULATING WATER COOLING TOWERS:

S-TEC-3C tablets are slow dissolving for continuous chlorination of Industrial recirculating cooling water to control bacterial growth. Tablets dissolve in about 4 hours in the sump. One tablet (1 oz.) in 5000 gallons of water will provide 1 ppm available chlorine when completely dissolved. For initial treatment add 4 tablets (4 oz.) where product will be uniformally mixed per 5000 gallons of water to reach a residual chlorine of 0.6 ppm. Run the chlorine test to determine dosages and chlorine consumption. Repeat the subsequent dosage every week, or as needed to maintain 0.6 ppm available chlorine. pH of system should be kept at 7.2 - 7.8 with acid. (AQUAPHASE pH-A or Muriatic Acid).

IF SYSTEM IS BADLY FOULED, (\$LIME, DEBRIS, ETC.) CLEAN MAN-UALLY BEFORE USING S-TEC-3C.

Use this product when the system is in jeopardy of being affected or after cleaning systems who efficiency is already impaired.

KEEP OUT OF REACH OF CHILDREN

DANGER: STRONG OXIDIZING AGENT. DO NOT MIX ANY FOREIGN MATERIAL. CONTACT WITH ANY MATERIAL BUT WATER MAY CAUSE AN INTENSE FIRE OR EXPLOSION. USE ORIGINAL CONTAINER, CARRY SMALL AMOUNTS IN CLEAN DRY CONTAINER, MAY CAUSE CHEMICAL BURNS, MAY BE HARMFUL OR FATAL IF SWALLOWED, STORE IN ORIGINAL CONTAINER WITH COVER CLOSED IN A COOL DRY PLACE.

IN CASE OF FIRE, DRENCH WITH LARGE AMOUNTS OF WATER. DISCARD EMPTY CONTAINER AFTER RINSING WITH WATER. DO NOT REUSE EMPTY CONTAINER.

ANTIDOTE: External - In case of contact wash throughly with water. For eyes, get prompt medical attention. Internal - Give Milk, Water, or Egg Whites. Get medical attention immediately.

THIS PRODUCT IS TOXIC TO FISH. Treated effluent should not be discharged where it will drain into lakes, streams, or ponds, or public water.