



**OIL WATERFLOOD OR SALTWATER DISPOSAL SYSTEM
BACTERIA CONTROL CHEMICAL
and
CORROSION INHIBITOR**

ACTIVE INGREDIENTS:

3-alkoxy*-2-hydroxy-n-propyl
trimethylammonium chloride 50%
Isopropyl alcohol 20%

*as ir. linear, primary alcohol (C₁₂—C₁₅)

INERT INGREDIENTS: 30%

Total 100%

Weight/Gallon = 7.97 lbs.
EPA Reg. No. 10349-4

DIRECTIONS

For control of slime forming and free living bacteria in oil field waterflood or saltwater disposal systems, add 50-100 ppm VISCO 1152 (5-10 gallons per 2400 barrels of water) continuously until the desired degree of control is achieved. Follow up with 10-15 ppm VISCO 1152 (1-2½ gallons per 2400 barrels of water) continuous feed to maintain control.

VISCO 1152 may also be fed intermittently at a rate of 50-200 ppm (5-20—gallons per 2400 barrels of water) for 4-8 hours a day, one to four times a week or as needed to maintain control.

NOTE: This product is not recommended for brines with greater than 30-40,000 mg/L of NaCl.

Feed VISCO 1152 directly from the drum through any type chemical pump.

NOTE: VISCO 1152 IS INTENDED FOR INDUSTRIAL USE ONLY. Do not apply to potable or domestic water systems. Treated water should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment, or disposal of waste. Do not reuse this container. Return to drum reconditioner or destroy by perforating and burial in a safe place. Apply this product only as specified on this label.

This product is toxic to fish. Keep out of lakes, streams or ponds.

DANGER

CORROSIVE. FLAMMABLE. KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM HEAT OR OPEN FLAME. CAUSES SEVERE EYE AND SKIN DAMAGE. MAY BE HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. Do not get in eyes, on skin or on clothing. Do not take internally. Keep container closed when not in use. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food.

In case of contact, immediately flush affected area with water for at least 15 minutes, call a physician. Remove and wash contaminated clothing before reuse.

FIRST AID: If swallowed, do not induce vomiting, drink large quantities of fluid and call a physician at once.

NALCO CHEMICAL COMPANY

P. O. BOX 87 • SUGAR LAND, TEXAS 77478

EPA Est. No. 1706-TX-1

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER