



# NALCO VISCO<sup>®</sup> 3990

BACTERIA CONTROL CHEMICAL  
AND  
CORROSION INHIBITOR

**ACTIVE INGREDIENTS:**

1-(Alkylamino) 3-aminopropane acetate	36%
Bis(trichloromethyl) sulfone	5%
INERT INGREDIENTS	59%
<b>TOTAL</b>	<b>100%</b>

\* Alkyl as in fatty acids of coconut oil

Weight Per Gallon: 8.7 lbs  
EPA Est. No. 1706-1X-1  
EPA Reg. No. 10349-15

**KEEP OUT OF REACH OF CHILDREN  
DANGER!**

**CORROSIVE CAUSES SEVERE EYE AND SKIN DAMAGE**

**Statement of Practical Treatment**

If swallowed, do not induce vomiting, drink promptly a large quantity of milk, egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol, call a physician immediately.

If on skin, immediately flush skin with copious quantities of water for at least 15 minutes.

If in eyes, immediately flush eyes with copious quantities of water, call a physician.

See Side Panel for Additional Precautionary Statements

# NALCO CHEMICAL COMPANY

P. O. BOX 87 • SUGAR LAND, TEXAS 77478

**DANGER!**

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)**

Corrosive causes severe eye and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed. See front panel for first aid instructions.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of wastes.

**Physical or Chemical Hazards**

**Flammable - Keep Away From Heat and Open Flame**

**DIRECTIONS FOR USE**

**GENERAL CLASSIFICATION**

It is a violation of Federal Law to use this product in a manner inconsistent with it's labeling.

**DIRECTIONS:** For control of bacteria in oil field, waterflood, or saltwater disposal systems.

Visco 3990 may be fed intermittently at a rate of 50-100 ppm (5-20 gallons per 2400 barrels of water) for 1-2 hours a day, 1-4 times a week, or as needed to maintain control. Visco 3990 may also be fed continuously at a rate of 50-200 ppm until the desired degree of control is achieved. Follow up with 10-25 ppm Visco 3990 (1-2.5 gallons per 2400 barrels of water) continuous feed to maintain control. Feed Visco 3990 directly from the drum through any chemical pump.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide spray mixture or rinsate that cannot be used or chemically processed should be disposed of in a land fill approved for pesticides or buried in a safe place away from water supplies.

**CONTAINER DISPOSAL**

Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill, or bury in a safe place. Consult Federal, State or local disposal authorities for approved alternative procedures.