



**NALCO**  
**VISCO** ACCEPTED  
**4960** 02 MAY 1980

**BACTERIA CONTROL CHEMICAL**  
**AND**  
**CORROSION INHIBITOR**

**ACTIVE INGREDIENTS:**

3-alkoxy-2-hydroxy-n-propyl trimethyl ammonium chloride as in linear, primary alcohol (C12-C15)	50%
<b>INERT INGREDIENTS:</b>	50%
<b>Total</b>	<b>100%</b>

Weight/Gallon = 7.97 lbs.  
 EPA Registration No. 10349-20 EPA Est No 1706-TX-1

**KEEP OUT OF REACH OF CHILDREN**

**DANGER!**

**STATEMENT OF PRACTICAL TREATMENT**

If swallowed, promptly drink a large quantity of milk, beaten egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Call a physician at once. NEVER give an unconscious person anything by mouth.

If on skin, immediately flush contacted area with copious quantities of water for at least 15 minutes. Remove and wash contaminated clothing.

If in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

**DANGER!**

**HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)**

Corrosive. Causes eye and skin damage. May be harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or clothing. Keep container closed when not in use. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling. See statement of practical treatment.

**PHYSICAL AND CHEMICAL HAZARDS**  
**FLAMMABLE, KEEP AWAY FROM HEAT OR OPEN FLAME**  
**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA.

**DIRECTIONS FOR USE**  
**GENERAL CLASSIFICATION**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For control of slime forming and free living bacteria in oil field production wells, add 50-100 ppm VISCO 4960 (5-10 gallons per 2400 barrels of fluid) continuously until the desired degree of control is achieved. Follow up with 10-15 ppm VISCO 4960 (1-2½ gallons per 2400 barrels of fluid) continuous feed to maintain control.

VISCO 4960 may also be fed intermittently at a rate of 50-200 ppm (5-20 gallons per 2400 barrels of fluid) for 4-8 hours a day, one to four times a week or as needed to maintain control.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide spray mixture or rinsate that cannot be used or chemically processed should be disposed of in a land fill approved for pesticides or buried in a safe place away from water supplies.

**CONTAINER DISPOSAL**

Triple rinse (or equivalent) and: offer for recycling, reconditioning, or disposal in an approved landfill, or bury in a safe place. Consult Federal, State or local disposal authorities for approved alternative procedures.

**NALCO CHEMICAL COMPANY**  
 P. O. BOX 87 • SUGAR LAND, TEXAS 77478

8.1014.1S

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

31