

**NALCO
VISCO
4997**

**OILFIELD BACTERIA CONTROL CHEMICAL
AND
CORROSION INHIBITOR**

ACTIVE INGREDIENTS

3-alkoxy-2-hydroxypropyl
trimethylammonium chloride
*as in linear primary alcohol (C₁₂-C₁₅)

INERT INGREDIENTS

Total

Weight/Gallon 7.91 lbs

EPA Registration No. 10349-22 EPA Est. No. 17061-K-1

KEEP OUT OF REACH OF CHILDREN

DANGER!

STATEMENT OF PRACTICAL TREATMENT

If swallowed, promptly drink a large quantity of milk, beaten egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Call a physician at once. NEVER give an unconscious person anything by mouth.

If on skin, immediately flush contacted area with copious quantities of water for at least 15 minutes. Remove and wash contaminated clothing.

If in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

DANGER!

Corrosive. Causes eye and skin damage. May be harmful if swallowed or absorbed through skin. Do not get in eyes, on skin or clothing. Keep container closed when not in use. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling. See statement of practical treatment.

Physical or Chemical Hazards

Flammable — Keep Away From Heat and Open Flame

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge treated effluent into lakes, streams, ponds or public waters unless in accordance with a NPDES permit. For guidance contact your Regional Office of the EPA.

DIRECTIONS FOR USE

GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For control of slime-forming and free-living bacteria in oil field waterflood or saltwater disposal systems, add 100-200 ppm VISCO 4997 (10-20 gallons per 2400 barrels of water) continuously until the desired degree of control is achieved. Follow up with 20-35 ppm VISCO 4997 (2-5 gallons per 2400 barrels of water) continuous feed to maintain control.

For control of slime-forming and free-living bacteria in oil field production wells, add 100-200 ppm VISCO 4997 (10-20 gallons per 2400 barrels of fluid) continuously until the desired degree of control is achieved. Follow up with 20-30 ppm VISCO 4997 (2-5 gallons per 2400 barrels of fluid) continuous feed to maintain control.

VISCO 4997 may also be fed intermittently at 100-2100 ppm (10-40 gallons per 2400 barrels of fluid) for 4-8 hours a day, one to four times a week or as needed to maintain control.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide spray mixture or rinsate that cannot be used or chemically processed should be disposed of in a land fill approved for pesticides or buried in a safe place away from water supplies.

CONTAINER DISPOSAL

Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill, or bury in a safe place. Consult Federal, State or local disposal authorities for approved alternative procedures.

NALCO CHEMICAL COMPANY
P. O. BOX 87 • SUGAR LAND, TEXAS 77478