UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

OCT 2 6 1989

Union Carbide Corporation P. O. Box 670 Bound Brook, N.J. 08805

Attention: Joan E. Young

Subject: Ucarsan 420 Sanitizer
Registration Number 10352-18
Your Submission Dated September 14, 1989
EPA Received Dated August 31, 1989

The amendment referred to above, submitted in connection with registration under FIFRA is acceptable provided that you submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy at (703)-557-3966.

Sincerely Yours,

John H. Lee Product Management (31) Antimicrobial Programs Branch Registration Division (H7505-C)

CONCURRENCES								
SYMBOL								
SURNAME								
DATE							}	

See MSDS for exposure limits of components.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS

DANGERKEEP OUT OF REACH OF CHILDREN

Corrosive Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. May cause skin sensitization.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge efficient containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge efficient containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the FPA.

STORAGE AND HANDLING


UCARSAN[®] Sanitizer 420 solutions are corrosive to many commonly used materials of construction such as steel galvarized iron, aluminum tin, and zinc. These solutions can be stored and handled in baked phenolic-laned steel, polyethylene, stainless steel, or reinforced epoxy-pastic equipment. This product freezes at about 4°C (16°F). Therefore, unless the storage tank is inside or underground, heating and insulation may be required, theating its needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F can be tolerated but the preferred maximum temperature is about 80°F.

A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with teffon a suitable for gaskets and packing.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL. Do not contaminate water food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your confronmental Control Agency or the Hazardous Waste representative at the hearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers. Triple rinse (or equivalent) Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or other procedures approved by state and local authorities. Do not out in weld on or near metal containers: Plastic Containers: may be incinerated, if allowed by state and local authorities if burned is allowed by state and local authorities.



Active Ing

KEEP (

STA

IF IN EYES: Immediately flush with plent IF ON SKIN: Wash with plenty of soap a IF INHALED: Remove to fresh air. If bre IF SWALLOWED: DO NOT INDUCE VC Note to Physician: Aspiration may sau gastric lavage

UNION CARBIDE CORPO

IN CASE OF EMERGENCY, TEL





UNION CARBIDE

Ucarsan

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician. IF SWALLOWED: DO NOT INDUCE YOMITING. Be not give anything to drink. Seek medical advice with urgency. Note to Physician: Aspiration may enuseding damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Union Carbide Corporation • Specialty Chemicals Division

55911 CONTAINER SIZE 55 GALLONS PRODUCT CODE 482 POUNDS NET WEIGHT EPA Est. No. 10352-WV-2 UCC-L 55911 (11/88) Made in U.S.A.

, IN CASE OF EMERGENCY, TELEPHONE (24 HOURS PER DAY) IN USA 1-800-UCC-HELP.

BEST AVAILABLE COPY

. Bei der . Di:

0.6

3. U

. 41

Specific G Vapor Prei Freezing F

The manufa

product is re such directe

sponsible ex

have not be MAKES NO OTHER WA IMPLIED WA ranty does no from the use

BUYER'S E AND ALL CI THIS PROD LIABILITY II PLACEMEN WITH RESP

WITH RESP ER BE LIAB OR HANDLI