

Active Ingredient: Glutaraldehyde 20.0%

Inert Ingredients: 80.0%

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention. IF ON SKIN; Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician. IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency. NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

UNION CARBIDE CORPORATION

39 Old Ridgebury Road • Danbury, CT 06817-0001 EPA Reg. No. 10352-18 UCARSAN® is a registered trademark of Union Carbide Net Contents 5 or 55 gallons

EPA Est. No. 10352-WV-2 UCC-L55911 (F 12/98) Made In USA PE1298

ļ		CONTAINER SIZE	CONTAINER SIZE
	55911 PRODUCT CODE	5 GALLONS	55 GALLONS
		43 POUNDS"	470 POUNDS
1		-NET WEIGHT	NET WEIGHT

EMERGENCY CONTACT (24 HOURS PER DAY): IN-USA 1-800-UCC-HELP (1-800-822-4357)
OUTSIDE USA 01-304-744-3487

DIRECTIONS FOR USE

GENERAL CLASSIFICATION

It is a violation of Fuderal law to use this product in a manner inconsistent with its labeling.

SANITIZING NON-FOOD CONTACT SURFACES, FARM, ANIMAL, AND POULTRY HOUSING FACILITIES AND EQUIPMENT.

Remove all poultry and other animals and feed from the premises. Remove all portable equipment. Remove all litter and manure from floors and other surfaces. Empty all water troughs and feed racks. Do not repopulate with poultry or other animals, or use equipment until treatment has been absorbed or dried.

Thoroughly saturate all surfaces with a solution prepared by mixing 0.64 to 1.6 fluid ounces of UCARSAN® Sanitizer 420 per gallon of water (5 to 12.5 milliliters per liter) to produce a solution containing 0.1% to 0.25% active ingredient. Allow to set for at least five minutes, or until thoroughly dried. Ventilate thoroughly before re-use.

All treated feeders, fountains, and waterers must be thoroughly scrubbed with detergent and rinsed with potable water prior to re-use.

, SANITIZING NON-FOOD CONTACT SURFACES, INDUSTRIAL EQUIPMENT AND BUILDINGS.

Before applying UCARSAN® Sanitizer 420, remove heavy fifth and soil deposits from surfaces using a suitable cleaner.

Dilute UCARSAN® Sanitizer 420 to 0.1% to 0.25% active ingredient by mixing 0.64 to 1.6 fluid ounces of UCARSAN® Sanitizer 420 per gallon of water (5 to 12.5 milliliters per liter). Using suitable commerciativ available equipment, saturate all surfaces with diluted UCARSAN® Sanitizer

CCEPTED

Under the Federal Insecticide, Funcicide, and Rodenticide Act as amended, for the peetleide, registered under EPA Reg. No. 12.252 - 15

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities. Plastic Containers: May be incinerated, or, if allowed by state and local authorities, by burning, if burned, stay out of smoke. Metal Containers: Must not be incinerated. Do not cut or weld on or near metal containers.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes Irreversible eye damage. Causes skin irritation. Hamful if inhaled. Hamful if swallowed. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This positioids is toxic to fish. Do not discharge effluent containing this product into lakes, streams, points, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

UCARSAN® Sanitizer 420 solutions are incompatible with many commonly used materials of construction such as stoel, galvanized fron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 16°F (-9°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centritugat pump is suggested for transfer service. Spiral wound stainless steel with TEFLON® is suitable for gaskets and packing.

LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants (a) that this product conforms to the chemical description on the label; (b) that this product is reasonably fit for the purposes set forth in the directions for use when it is used in accordance with such directions; and (c) that the directions, warnings and other statements on this label are based upon responsible experts' evaluation of reasonable tests of effectiveness and of toxicity to laboratory antimats. Tests have not been made on all variation or in all states or under all conditions. THE MANUFACTURER NEITHER MAKES NOR INTENDS, NOR DOES IT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE, ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED, AND IT EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. This warranty does not extend to, and the Buyer shall be solely responsible for, any and all loss or damage which results from the use of this product in any manner which is inconsistent with the label directions, warnings or cautions.

BUYER'S EXCLUSIVE REMEDY AND MANUFACTURER'S OR SELLER'S EXCLUSIVE LIABILITY FOR ANY AND ALL CLAIMS, LOSSES, DAMAGES, OR INJURIE'S RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, WHETHER OF NOT SUCH HABILITY IS BASED IN CONTRACT, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE, SHALL BE LIMITED, AT THE MANUFACTURER'S OPTION, TO REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRICE FOR, THE QUANTITY OF PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED. IN NO EVENT SHALL MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

BEFORE HANDLING OR USING, READ AND UNDERSTAND
CURRENT UNION CARBIDE MATERIAL SAFETY DATA
SHEET FOR THIS PRODUCT.

