UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Union Carbide Corporation P. O. Box 670 Bound Brook, NJ 08805

ರ .*ುವ*೦ aat

Attention: Joan E. Young

Subject: UCARCIDE 250 Antimicrobial

EPA Registration Number 10352-21

Your Submission Dated January 3, 1994 EPA Received Date January 13, 1994

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to amend the Hazard Warnings Statement, is acceptable provided that you make the following labeling revisions:

The heading "Hazards to Humans and Domestic Animals" is acceptable.

Revise the statement "May cause allergic skin reaction" to read "Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals."

The addition of the statement "Cause asthmatic signs and symptoms in hyper reactive individuals" to the product labeling is acceptable.

A stamped copy of the labeling is enclosed for your records. Submit one (1) copy of the final printed label prior to release of the product for shipment.

If you have any questions concerning this letter, please contact Karen M. Leavy at (703)-305-6966.

Sincerely yours,

Marion J. Johnson Product Manager (31)

Antimicrobial Program Branch Registration Division (7505C)

CONCURRENCES							
SYMBOL							
SURNAME		***************************************					
DATE							
EPA Form 1320-1A (1/90)	Printed on Recycled Paper	OFFICIAL FILE COPY					

Printed on Recycled Paper

*U.S. GPO 1994 522 503/820

P: CAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. May cause allergic skin reaction. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into takes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Ekmination System (NPDES) permit and the nermitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

UCARCaTE® 250 Antimorobial solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenotic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about -6°F (-21°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. It heating is needes, a exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is, about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON® is suitable for gaskets and packing.

LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants (a) that this product conforms to the chemical description on the label; (b) that this product is reasonably (if for the purposes set forth in the directions for use when it is used in accordance with such directions; and (c) that the directions, warnings and other statements on this label are based upon responsible expends; evaluation of reasonable tests of effectiveness and of toxicity to laboratory animals. Tests have not been made on all varieties or in all states or under all conditions. THE MANUFACTURER NEITHER MAKES NOR INTENDS, NOR DOES IT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE, ANY OTHER WARRANTIES, EXPRESSED OR MIPLIED, AND IT EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. This warranty does not extend to, and the Buyer shall be solely responsible for, any and all loss or damage which results from the use of this product in any manner which is inconsistent with the label directions, warnings or cautions.

BUYER'S EXCLUSIVE REMEDY AND MANUFACTURER'S OR SELLER'S EXCLUSIVE LIABILITY FOR ANY AND ALL CLAIMS, LOSSES, DAMAGES, OR INJURIES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, WHETHER OR NOT SUCH LIABILITY IS BASED IN CONTRACT, NEGLIGENCE, STRICT LIABILITY IN TOTAL OR THE REPAYMENT OF THE LIMITED, AT THE MANUFACTURER'S OPTION, TO REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRICE FOR, THE QUANTITY OF PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED. IN NO EVENT SHALL MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

BEFORE HANDLING OR USING, READ AND UNDERSTAND CURRENT UNION CARBIDE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.



Active Ingredient: Glutaraldehyde 50.0% Inert Ingredients: 50.0%

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate med IF ON SKIN; Immediately wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms per

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medica urgency.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMEN

UNION CARBIDE CORPORATION

39 Old Ridgebury Road • Danbury, CT 06817-0001 EPA Reg. No. 10352-21 UCARCIDE[®] is a registered trademark of Union Carbide Net Contents 55 gallons EPA Est. No UCC-L90222 Made In USA PE1293

	90222	CONTAINER SIZE 56 GALLONS	SHIPPING NAME	CORROSIVE LIQUID, N O S (CONTAINS GLUTARAL DEHYDE.)	
ļ	PRODUCT CODE	500 POUNDS	HAZARD CLASS	ID NUMBER	PG II
		NET WEIGHT	8	UN 1760	741

EMERGENCY CONTACT (24 HOURS PER DAY): IN USA 1-800-UCC-HELP (OUTSIDE USA 01-304-744

6