

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS**

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive - Causes irreversible eye damage. Causes burns. May cause skin sensitization.

Harmful if swallowed.

Do not get in eyes, on skin or on clothing. Avoid breathing vapors. Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in a NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL PROPERTIES

Specific Gravity at 20/20°C	1.118	Solubility in Water at 20°C	Complete
Vapor Pressure at 20°C	14.7 mm Hg	Solubility of Water in at 20°C	Complete
Freezing Point	-17°C	pH at 25°C	3.1 to 4.5

STORAGE AND HANDLING

AQUACAR "545" solutions are corrosive to many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy plastic equipment. This product freezes at about -17°C (1°F). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F can be tolerated but the preferred maximum storage temperature is about 80°F.

A stainless steel centrifugal pump is suggested for transfer service. Asbestos is suitable for gaskets and packing.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinse is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal: Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

**UNION
CARBIDE**

Aquacar

**545
WATER TREATMENT
MICROBIOCIDES**

A MICROBIOCIDES FOR USE IN CONTROLLING SLIME FORMULATING BACTERIA, SULFATE REDUCING BACTERIA, AND ALGAE IN AIR WASHER SYSTEMS, AND IN RECIRCULATING WATER COOLING TOWERS AND SYSTEMS, INCLUDING PASTEURIZER COOLING WATER SYSTEMS AND INDUSTRIAL CLOSED, RECIRCULATING PROCESS WATER SYSTEMS

Active Ingredient: Glutaraldehyde 45.0%
Inert Ingredients: 55.0%
100.0%

ACCEPTED

KEEP OUT OF REACH OF CHILDREN

FEB 03 1987

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF SWALLOWED: DO NOT INDUCE VOMITING. Give at least two glasses of water. Seek medical advice with urgency.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

UNION CARBIDE CORPORATION • SPECIALTY CHEMICALS DIVISION

Danbury, CT 06817 • Offices in Principal Cities

EPA Reg. No. 10352-22

AQUACAR® is a registered trade mark
of Union Carbide Corporation

EPA Est. No. 10352-WV-2

UCC No. 4127-1C

Made in U.S.A.

DOT SHIPPING NAME	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (GLUTARALDEHYDE SOLUTION)	UN 2924 ID NUMBER	90270	CONTAINER SIZE 55 GALLONS
IMO SHIPPING NAME	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (GLUTARALDEHYDE SOLUTION)	2924 UN NUMBER	PRODUCT CODE	504 POUNDS NET WEIGHT

IN CASE OF EMERGENCY, TELEPHONE (24 HOURS PER DAY) IN USA 1-800-UCC-HELP.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with these directions.

AIR WASHERS AND RECIRCULATING COOLING

This product may be used only in industrial air washers and air washer systems. AQUACAR "545" Water Treatment Microbicide should be added below, to a water treatment system at a convenient point of uniform mixing. May be made intermittently (SLUG DOSE) or continuously. Badly fouled AQUACAR "545" Under these conditions, blowdown should be discontinued.

INTERMITTENT (SLUG DOSE) METHOD

Initial Dose: When the system is noticeably fouled, apply 12.7-25.5 fluid gallons of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 5.1-12.7 fluid gallons of water to the system weekly, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, apply 12.7-25.5 fluid gallons of water in the system.

Subsequent Dose: Maintain this treatment level by starting a continuous AQUACAR "545" per 1000 gallons of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

PASTEURIZER COOLING WATER

AQUACAR "545" should be used at the same application rates, and in the same manner, as described above. It should be added to the closed recirculating system at a convenient point, area, sump area, or other reservoir or collecting area from which the treated water is circulated throughout the pasteurizer cooling water system.

LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants (a) that this product conforms to the chemical description on the label, (b) that the product is reasonably fit for the purposes set forth in the directions for use, (c) that the directions, warnings and other statements of responsible experts' evaluation of reasonable tests of effectiveness and of safety have not been made on all varieties or in all states or under all conditions. IT MAKES NO WARRANTY, EXPRESS OR IMPLIED, AND IT EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. The warranty does not extend to, and the Buyer shall be solely responsible for, any results from the use of this product in any manner which is inconsistent with the directions.

BUYER'S EXCLUSIVE REMEDY AND MANUFACTURER'S OR SELLER'S AND ALL CLAIMS, LOSSES, DAMAGES, OR INJURIES RESULTING FROM THE USE OF THIS PRODUCT, WHETHER OR NOT SUCH LIABILITY IS BASED ON CONTRACT, TORT, OR OTHERWISE, SHALL BE LIMITED AT THE MANUFACTURER'S OR SELLER'S SOLE OPTION TO THE REPAIR, REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRICE FOR THE PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED. IN NO EVENT SHALL THE MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR HANDLING OF THIS PRODUCT.