

...
...
...
...
...

...
...

...

...	10000-10
...	10000-11
...	10000-12
...	10000-13
...	10000-14
...	10000-15
...	10000-16
...	10000-17
...	10000-18
...	10000-19
...	10000-20
...	10000-21
...	10000-22
...	10000-23
...	10000-24
...	10000-25
...	10000-26
...	10000-27
...	10000-28
...	10000-29
...	10000-30
...	10000-31
...	10000-32
...	10000-33
...	10000-34
...	10000-35
...	10000-36
...	10000-37
...	10000-38
...	10000-39
...	10000-40

BEST AVAILABLE COPY

294

-2-

The amendment referred to above, submitted in connection with registration under FIFRA to make changes in the precautionary statements, is acceptable provided that you:

1. Make the following labeling listed below before you release the product for shipment bearing the amended labeling:

a. In lieu of supporting data delete the following statement: "Harmful if inhaled".

Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy at (703)-557-3966.

Sincerely yours,

John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

BEST AVAILABLE COPY

See MSDS for exposure limits of components.

PRECAUTIONARY STATEMENTS
HAZARDS TO MAN

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes reversible eye damage. Causes skin burns. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. May cause birth defects.

Do not get in eyes or skin on anything.
Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.
Wash thoroughly with soap and water after handling.
Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This product is highly toxic to aquatic organisms. It is also highly toxic to birds and mammals. It is highly flammable and may cause fire or explosion. It is highly volatile and may cause air pollution. It is highly persistent and may cause long-term environmental damage.

PHYSICAL PROPERTIES

Appearance: Colorless liquid
Odor: Pungent
Boiling Point: 100°C
Melting Point: -10°C
Density: 1.0 g/cm³

STORAGE AND HANDLING

Store in a cool, dry place away from heat and light. Keep container tightly closed. Do not use damaged containers. Handle with care to avoid spills. Use appropriate PPE. Dispose of waste properly.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Follow local, state, and federal regulations. Do not dump into water or land.
CONTAINER DISPOSAL: Metal Containers or Plastic Containers. Do not reuse. Recycle if possible.



JUN 2

10352-
IF IN EYE
IF ON SK
IF INHAL
IF SWALI
Note to F
gastro di

UNION C

Dantury CT 06
EPA Reg No 1
OCARCID 15
of Union Carb
Net Weight 500

IN CASE OF

BE

394

H
A
H

Ucarbide

UNION
CARBIDE

EPA
JUN 21 1980

Active Ingredient	Glutaraldehyde	50.0%
Inert Ingredients		50.0%
		100.0%

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF ON SKIN: Immediately wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency. **Report to Physician.** Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

UNION CARBIDE CORPORATION • SPECIALTY CHEMICALS DIVISION

Wilmington, CT 06817 • Offices in Principal Cities

Reg. No. 10352-24

Ucarbide is a registered trademark of Union Carbide Corporation.
Net Weight 500 Lbs. (227 KG)

FPA Est. No. 10352-W

UCC L 90228 (10)

Made in U.S.A.

DOT H260, H314	CORROSIVE LIQUID, N.O.S. GLUTARALDEHYDE	UN 1760 CORROSIVE LIQUID, N.O.S.	90228	HAZARDOUS MATERIALS
IMO H260, H314	CORROSIVE LIQUID, N.O.S. GLUTARALDEHYDE	1760 CORROSIVE LIQUID, N.O.S.		HAZARDOUS MATERIALS

IN CASE OF EMERGENCY, TELEPHONE (24 HOURS PER DAY) IN USA 1-800-UCC-HELP.