### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

FEB | 4 1995

Union Carbide Corporation P. O. Box 670 Bound Brook, NJ 08805

Attention: Ms. Joan E. Young,

Regulatory Affairs Manager

Subject: UCARSAN 4128 Sanitizer

EPA Registration Number 10352-26

Your Submission Dated January 3, 1994 EPA Received Date January 13, 1994

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to amend the Hazards Warning Statements, is acceptable provided that you make the following labeling revisions:

The heading "Hazards to Humans and Domestic Animals" is acceptable.

Revise the statement " May cause allergic skin reaction" to read " Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals."

The addition of the statement "Causes asthmatic signs and symptoms in hyper-reactive individuals" to the product labeling is acceptable.


A stamped copy of the labeling is enclosed for your records. Submit one (1) final printed label prior to release of the product for shipment.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-305-6966.

Sincerely,

W

Walter C. Francis Acting Product Manager (31) Antimicrobial Program Branch Registration Division(7505C)



EPA Form 1320 1A (1/90)

Printed on Recycled Paper

4) S GPO 1994-522 503/82085

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

## DANGER KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin, May cause allergic skin reaction. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing.

Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

#### **ENVIRONMENTAL HAZARDS**

This posticide is toxic to flah. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a Nazional Poliutant Discharge Elimination System (NPDES) permit and the premitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

#### STORAGE AND HANDLING

UCARCIDE® 225 Preservative solutions are incompatible with many commonly used materials of construction such as steet, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenošo-lined steet, polyethylene, stainless steet, or reinforced epoxy-plastic equipment. This product freezes at about 14°F (-10°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C). A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON® is suitable for gaskets and packing.

#### LIMITED WARRANTY AND DISCLAIMER

The manufacturer wai rants (a) that this product conforms to the chemical description on the label; (b) that this product is easonably fit for the purposes set forth in the directions for use when it is used in accordance with such directions; and (c) that the directions, warnings and other statements or this label are based upon responsible experts' evaluation of reasonable tests of effectiveness and of toxicity to laboratory animals. Tests have not been made on all varieties or in all states or under all conditions. THE MANUFACTURER NEITHER MAKES NOR INTENDS, NOR DOES IT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE, ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED, AND IT EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. This warranty does not extend to, and the Buyer shall be solely responsible for, any and all loss or darrage which results from the use of this product in any manner which is inconsistent with the label directions, warnings or cautions.

BUYER'S EXCLUSIVE REMEDY AND MANUFACTURER'S OR SELLER'S EXCLUSIVE LIABILITY FOR ANY AND ALL CLAIMS, LOSSES, DAMAGES, OR INJURIES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, WHETHER OR NOT SUCH LIABILITY IS BASED IN CONTRACT, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE, SHALL BE LIMITED. AT THE MANUFACTURER'S OPTION, TO REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRICE FOR, THE OUANTITY OF PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED. IN NO EVENT SHALL MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSCOURTING DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

BEFORE HANDLING OR USING, READ AND UNDERSTAND CURRENT UNION CARBIDE MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.



Active Ingredient: Glutaraldehyde \_\_\_\_\_\_ 25.0
Inert Ingredients: \_\_\_\_\_\_ 75.0

100

# DANGER

#### STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medic

IF ON SKIN: 'Mash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persi IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical a urgency.

NOTE TO PHYSICIAN; Aspiration may cause lung damage. Probable mucosal damage may co the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMEN

#### UNION CARBIDE CORPORATION

39 Old Ridgebury Road • Danbury, CT 06817-0001 EPA Reg. No. 10352-39 UCARCIDE is a registered trademark of Union Carbide Net Cuntents 55 gallons

EPA Est. I

90289 CONTAINER SIZE
90289 SS GALLONS
PRODUCT CUDE 486 POUNDS
ICT WEIGHT

EMERGENCY CONTACT (24 HOURS PER CAY): IN USA 1-800-UCC-HELP (1-OUTSIDE USA 01-304-744-3

BEST AVAILABLE COPY