

JUN 21 1990

Union Carbide Corporation
 Speciality Chemicals Division
 P.O. Box 670
 Bound Brook, NJ 08805

Attention: Joan F. Young

Gentleman:

Subject: Amended Application Dated: 11/20/88

UCARCIDE® 125 Antimicrobial	10325-17
UCAPSA® 420 Sanitizer	10325-19
UCARCIDE® 225 Antimicrobial	10325-20
UCARCIDE® 250 Antimicrobial	10325-21
AOUCAP® 545 Water Treatment Microbicide	10325-22
AOUCAP® 515 Water Treatment Microbicide	10325-23
UCARCIDE® 150 Antimicrobial	10325-24
UCARCIDE® 145LT Antimicrobial	10325-25
UCAPSA® 4120 Sanitizer	10325-26
UCONEX® 315 Antimicrobial	10325-27
UCONEX® 345 Antimicrobial	10325-28
UCARCIDE® 602 Sterilizing & Disinfecting Solution	10325-29
UCARCIDE® 114 Antimicrobial	10325-30
AOUCAP® 514 Water Treatment Microbicide	10325-31
UCARCIDE® 142 Antimicrobial	10325-32
AOUCAP® 542 Water Treatment Microbicide	10325-33
UCARCIDE® 750 Antimicrobial	10325-35
PIROR® 850 Slicicide	10325-37
UCARCIDE® 250 Preservative	10325-38
UCARCIDE® 225 Preservative	10325-39
AOUCAP® 504 Water Treatment Microbicide	10325-40

BEST AVAILABLE COPY

The amendment referred to above, submitted in connection with registration under FIFRA to make changes in the precautionary statements, is acceptable provided that you:

1. Make the following labeling listed below before you release the product for shipment bearing the amended labeling:

a. In lieu of supporting data delete the following statement: "Harmful if inhaled".

Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen H. Leavy at (703)-557-3966.

Sincerely yours,

John W. Lee
Product Manager (31)
Antimicrobial Program, Insect
Registration Division (975050)

BEST AVAILABLE COPY

PN # 120 1000 10-0

BEST AVAILABLE COPY

See MSDS for exposure limits of components.

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS**

DANGER

KEEP OUT OF REACH OF CHILDREN

Irritant. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. May cause skin sensitization.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluents containing this active ingredient into lakes, streams, ponds, reservoirs, oceans, or other waters unless this product is specifically labeled and addressed in an approved permit. Do not discharge effluents containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

UCCONE 71 is 245 pounds per container in many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These materials can be coated and handled in coated plastic, metal, wood, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 12°C (54°F). Therefore, unless the storage tank is inside or underground, heating and expansion may be required if heating is needed, exposure to high temperatures should be avoided. For short-term use up to about 1 degree, temperatures of up to 100°F can be tolerated and the preferred maximum storage temperature is 60°C (140°F).

A plastic over container opening is suggested for transfer services. Special hazard placards must be used in a vehicle for transport and storage.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray material, or empty containers is prohibited. If these wastes cannot be disposed of by use according to label directions, contact your State Pesticide Control or Environmental Control Agency, or the nearest State representative of the national EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or burn/incinerate in a certified facility or other procedures approved by State and local authorities. Do not burn, or use for or store food, feed, or other products. Plastic Containers: May be recycled if allowed by state and local authorities. If burned, stay out of pits. Metal Containers: Must not be recycled.



Active Ingredient: Glutaraldehyde 45.0%
Inert Ingredients 55.0%
100.0%

JUN 21 1990

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

10352-28

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.
IF ON SKIN: Immediately wash with plenty of soap and water. Get medical attention.
IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.
IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency.
Note to Physician: Aspiration may cause lung damage. In fatal, mucosal damage may contraindicate the use of gastric lavage.

UNION CARBIDE CORPORATION • SPECIALTY CHEMICALS DIVISION

Danbury, CT 06817 • Offices in Principal Cities
EPA Reg. No. 10352-28
UCCONE 71 is a registered trademark of Union Carbide Corporation.
Net Weight 504 Lbs. (229 KG)

EPA Est. No. 10352 WY 2
UCC L 90270 (10/88)
Made in U.S.A.

NET SHIPPING WEIGHT	CORROSIVE LIQUID N.O.S. (GLUTARALDEHYDE SOLUTION)	UN 1700	30270	CONTAINER SIZE
504	CORROSIVE LIQUID N.O.S. (GLUTARALDEHYDE SOLUTION)	1700	30270	55 GALLONS
				NET WEIGHT

IN CASE OF EMERGENCY, TELEPHONE (24 HOURS PER DAY) IN USA 1-800-UCC-HELP.

UCCONE 71 is 245 pounds per container in many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These materials can be coated and handled in coated plastic, metal, wood, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 12°C (54°F). Therefore, unless the storage tank is inside or underground, heating and expansion may be required if heating is needed, exposure to high temperatures should be avoided. For short-term use up to about 1 degree, temperatures of up to 100°F can be tolerated and the preferred maximum storage temperature is 60°C (140°F).

Special Gravity at 20°C/68°F
Vapor Pressure at 20°C/68°F
Freezing Point

LIABILITY
The manufacturer warrants that the product is reasonably fit for use in such operations, and that the manufacturer accepts no liability for any loss or damage, whether or not caused by the use of this product, which is not intended or authorized by the manufacturer. THE WARRANTY IS LIMITED TO THE DEFECTS IN THE PRODUCT AND DOES NOT COVER THE USER'S NEGLIGENCE OR MISUSE OF THE PRODUCT. THE USER SHALL BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OR HANDLING OF THIS PRODUCT.