Union Carbide Corporation P. O. Box 670 Bound Brook, NJ 08805

· FEB | 4 1995

Attention: Ms. Joan E. Young,

Regulatory Affairs Manager

Subject: UCARCIDE 225 Preservative

EPA Registration Number 10352-39

Your Submission Dated February 25, 1994

EPA Received Date March 8, 1994

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, to amend the Hazard Warnings Statement, is acceptable provided that you make the following labeling revisions:

The heading " Hazards to Humans and Domestic Animals" is acceptable.

Revise the statement "May cause allgeric skin reaction" to read " Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals."

The addition of the statement "Causes asthmatic signs and symptoms in hyper-reactive individuals" to the product labeling is acceptable.


A stamped copy of the product labeling is enclosed for your records. Submit one (1) copy of the final printed labeling prior to release of the product for shipment.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-305-6966.

Sincerely yours,

US

Walter C. Francis
Acting Product Manager(31)
Antimicrobial Program Branch
Registration Division(7505C)



EPA Form 1320-1A (1/90)

Printed on Recycled Paper

OFFICIAL FILE COPY

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. May cause allergic skin reaction. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on dothing.

Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENV RONMENTAL HAZARDS

This precide is toxic to fish. Do not discharge effluent containing this product into takes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (MPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems within it previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

UCARCIDE® 225 Preservative solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, atuminum, tin, and zinc. These solutions can be stored and handled in baked phenoScilined steel, polyerhylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezee at about 14°F (-10°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON® is suitable for gaskets and packing.

LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants (a) that this product conforms to the chemical description on the fabel, (b) that this product is reasonably fit for the purposes set forth in the directions for use when it is used in accordance with such directions; and (c) that the directions, warnings and other statements or this table are based upon responsible experts' evaluation of massonable tests of effectiveness and of toxicity to liaboratory animals. Tests have not been made on all varieties or in all states or under all conditions. THE MANUFACTURER NEITHER MAKES NOR INTENDS, NOR DOES IT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE, ANY OTHER WARRANTIES, EXPRESSED OR MPLIED, AND IT EXPRESSLY EXCLUDES AND DISCLAIMS ALL MPLIED WARRANTIES OF MERCHARDILITY AND FITNESS FOR PARTICULAR PURPOSE. This warranty does not extend to, and the Buyer shall be solely responsible for, any and all loss or darrange which results from the use of this product in any manner which is in consistent with the label directions, warnings or cautions

BUYER'S EXCLUSIVE REMEDY AND MANUFACTURER'S OR SELLER'S EXCLUSIVE LIABILITY FOR ANY AND ALL CLAIMS, LOSSES. DAMAGES, OR INJURIES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, WHETHER OR NOT SUCH LIABILITY IS BASED IN CONTRACT, NEGLIGENCE. STRICT LIABILITY IN TORT OR OTHERWISE, SHALL BE LIMITED, AT THE MANUFACTURER'S OPTION, TO REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRICE FOR, THE QUANTITY OF PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED. IN NO EVENT SHALL MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

BEFORE HANDLING OR USING, READ AND UNDERSTAND
CURRENT UNION CARBIDE MATERIAL SAFETY DATA
SHEET FOR THIS PRODUCT.



Active Ingredient: Glutaraldehyde ______ 25.0
Inert Ingredients: _____ 75.0

----<u>/5.0</u> 100.0

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 initiates. Get immediate media. IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms pers IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may or the use of gastric lavage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMEN

UNION CARBIDE CORPORATION

39 Old Ridgebury Road • Danbury, CT 06817-0001 EPA Reg. No. 10352-39 UCARCIDE is a registered trademark of Union Carbide Net Contents 55 gallons EPA Est UCC-I

90289 CONTAINER SIZE

90289 SS GALLONS

PRODUCT CLOE LET MEIGHT

EMERGE LOY CONTACT (24 HOURS PER CAY): IN USA 1-800-UCC-HELP (1 OUTSIDE USA 01-304-744-

BEST AVAILABLE COPY