17712 10352-44 Please reed instructions on reverse before OMB No. 2070-0060. Approval expires 2-28-95 OPP Identifier Number Registration United States **Environmental Protection Agency Amendment** 227434 Washington, DC 20460 Other Application for Pesticide - Section I 2. EPA Product Manager 3. Proposed Classification 1. Company/Product Number

| 10352-44 | Marion Johnson X None Restricted |
|--|---|
| 4. Company/Product (Name) UCARSAN 4256 Sanitizer | PM# 31 Restricted |
| 5. Name and Address of Applicant (Include ZIP Code) Union Carbide Corporation P. 0. Box 670 Bound Brook, NJ 08805 Check if this is a new address | 6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical algorithms in and labeling to: NOTIFICATION EPA Reg. No. MAR 2 5 1997 Product Name |
| Section - II | |
| Amendment - Explain below. Resubmission in response to Agency letter dated X Notification - Explain below. | Final printed labels in response to Agency letter dated "Me Too" Application. Other - Explain below. |
| Explanation: Use additional page(s) if necessary. (For section I and Section II.) Notification per PR Notice 95-2 of minor label change. A minor wording change has been made in the Storage and Handling section of the label. This notification is consistent with the provisions of PR Notice 95-2 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or confidential statement of formula of this product. Union Carbide understands that it is a violation of (Continued | |
| | Section - III on attached sheet. |
| 1. Material This Product Will Be Packaged In: | |
| Yes Yes Yes X No If "Yes" No. per If | /ater Soluble Packaging Yes X No "Yes" No. per ackage wgt container 2. Type of Container X Metal Plastic Glass Paper Other (Specify) |
| Contains 5 | gal., bulk X On Label On Labeling accompanying product |
| 6. Manner in Which Label is Affixed to Product Paper glued Stenciled Other Other | |
| Section - IV | |
| Name Title | Telephone No. (Include Area Code) anager, Regulatory Affairs 908-563-56-44 |
| Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment of both under applicable law. 6. Date Application Received (Stamped) | |
| 4. Typed Name 5. D | anager, Regulatory Affairs |
| Jøan E. Young | 2/17/97 |

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing.

Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sever systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Recional Office of the EPA.

STORAGE AND HANDLING

UCARSAN® 4256 Sanitizer is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. This product can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 21°F (-6°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON® is suitable for gaskets and packing.


LIMITED WARRANTY AND DISCLAIMER

The manufacturer warrants (a) that this product conforms to the chemical description on the label; (b) that this product is reasonably lift for the purposes set forth in the directions for use when it is used in accordance with such directions; and (c) that the directions, warnings and other statements on this label are based upon responsible experts' evaluation of reasonable tests of effectiveness and of toxicity to laboratory animals. Tests have not been made on all varieties or in all states or under all conditions. THE MANUFACTURER NEITHER MAKES NOR INTENDS, NOR DOES IT AUTHORIZE ANY AGENT OR REPRESENTATIVE TO MAKE, ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED, AND IT EXPRESSLY EXCLUDES AND DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. This warranty does not extend to, and the Buyer shall be solely responsible for, any and all loss or damage which results from the use of this product in any manner which is inconsistent with the label directions, warnings or cautions.

BUYER'S EXC, I/S/VE, REMEDY AND MANUFACTURER'S OR SELLER'S EXCLUSIVE LIABILITY FOR ANY AND ALL CLAIMS, LOSSES, DAMAGES, OR INJURIES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, WHETHER OR NOT SUCH LIABILITY IS BASED IN CONTRACT, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE, SHALL BE LIMITED, AT THE MANUFACTURER'S CPRION, TO REPLACEMENT OF, OR THE REPAYMENT OF THE PURCHASE PRIOE FOR, THE QUANTITY OF PRODUCT WITH RESPECT TO WHICH DAMAGES ARE CLAIMED, IN NO EVENT SHALL MANUFACTURER OR SELLER BE LIABLE FOR SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

BEFORE HANDLING OR USING, READ AND UNDERSTAND
CURRENT UNION CARBIDE MATERIAL SAFETY DATA
SHEET FOR THIS PRODUCT.

Modified Language



DANGER

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency,

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric layage.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

UNION CARBIDE CORPORATION

39 Old Ridgebury Road • Danbury, CT 06817-0001

EPA Reg. No. 10352-44

· UDARSAN® is a registered trademark

ຳວຽປnion Carbide

Not Contents 55 gallons

EPA Est. No. 10352-WV-2 UCC-L90266 (a01/97) Made In USA PE0197

90266 CONTAINER SIZE

90266 55 GALLONS

PRODUCT CODE 473 POUNDS

NET WEIGHT

EMERGENCY GONTACT (24 HOURS PER DAY): IN USA 1-800-UCC-HELP (1-800-822-4357)
OUTSIDE USA 01-304-744-3487

It is a violation of Feder

DO NOT U

This product is for us

SANITIZING FARM, ANIMA

Remove all poultry and ot equipment. Remove all lift water troughs and feed sa equipment until treatment waterers must be thorough prior to re-use. Ventilate t

To sanitize vegetative patt typhi, Staphylococcus aun Avian rotavirus, Avian infe gastroenteritis virus, and (influenza.

- Thoroughly saturate all by mixing one ounce of produces a solution con
- 2. Allow to set for at least :
- 3. Ventilate thoroughly bef
- Fresh solution should be diluted or soiled.

S

PESTICIDE DISPOSAL: Do no is prohibited. Pesticide wastes a is a violation of Federal law. If it contact your State Pesticide or y representative at the nearest EP CONTAINER DISPOSAL: Meta offer for recycling or reconditioni approved by state and local authanties, by burning incinerated. Do not cut or weld to