

10356-8

3-26-1990

1/2

**COPIY**  
**COPY**

MAR 26 1990

|        |     |
|--------|-----|
| 260954 | 300 |
| 8      | 17  |

Ms. Deborah E. Barker  
 CS1  
 One Woodlawn Green  
 Charlotte, NC 28217

Dear Ms. Barker:

Subject: Additional Brand Name  
 Oxcel 508 CCA Type C  
 EPA File Symbol 10356-8  
 Your Submission Dated February 27, 1990

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. A stamped copy of the label is enclosed for your records.

Sincerely yours,

*Susan T. Lewis*

Susan T. Lewis  
 Product Manager (21)  
 Fungicide-Herbicide Branch  
 Registration Division (H7505C)

Enclosure

H7505C:J.Fairfax:jf:3/20/90

CONCURRENCES

|         |  |  |  |  |  |  |  |
|---------|--|--|--|--|--|--|--|
| SYMBOL  |  |  |  |  |  |  |  |
| SURNAME |  |  |  |  |  |  |  |
| DATE    |  |  |  |  |  |  |  |

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS & DOMESTIC ANIMALS**

**DANGER**

Corrosive. Causes irreversible eye damage, skin or mucous membrane irritation. Harmful or fatal if swallowed, inhaled or absorbed through skin. Handle in a well ventilated area. Do not get on skin, in eyes or on clothing. Keep container closed when not in use.

Individuals in the work area of an arsenical wood treatment plant must wear properly fitting, well-maintained high efficiency filter respirators, MSHA/NIOSH approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 microgram per cubic meter of air (10 ug/m<sup>3</sup>) averaged over an 8 hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Refer to label attachment, "Permissible Exposure Limit (PEL) Monitoring Program" for additional information concerning the use of this product.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

**PHYSICAL AND CHEMICAL HAZARDS**

Do no use or store near heat or open flame.

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**STORAGE**

This product must be stored in closed tanks or drums which display a label properly identifying the product and its concentration.

**PESTICIDE DISPOSAL**

Pesticides wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinseate is a violation of Federal law. If this waste cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL**

Triple rinse (or equivalent) and offer for recycling or reconditioning or dispose of in a sanitary landfill or by other approved State and local procedures.

**SPILLS**

- Avoid contact with eyes, skin or clothing
- Dilute to contain with sand or soil
- Collect usable liquid and return to work tank or drum
- Neutralize any uncollected liquid

**50% Concentrate**

Apply 200 pounds of lime or 800 pounds of cement per 50 gallons of 50% concentrate

**Working Solutions (up to 10% solution)**

Apply 40 pounds of lime or 160 pounds of cement per 50 gallons 90% solution of 10% or less.

-Collect and enclose in steel drums, any contaminated soil, sand or absorbent and dispose in accordance with local, state and Federal regulations for hazardous waste

-Contact chemical manufacturer, state environmental agency or U.S. EPA for assistance and instructions for control of spilled chemicals

**RESTRICTED USE PESTICIDE**

For sale to and use by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

**CSI WOOD PRESERVATIVE**

**CHROMATED COPPER ARSENATE**

**CCCA-C 50% CONCENTRATE**

|   |                |
|---|----------------|
| <b>ACTIVE INGREDIENTS</b>                           | <b>Oxide</b>   |
| Chromic Acid (CrO <sub>3</sub> )                    | 23.75%         |
| Cuprous Oxide (CuO)                                 | 9.25%          |
| Arsenic Pentoxide (As <sub>2</sub> O <sub>5</sub> ) | 17.00%         |
| <b>INERT INGREDIENTS</b>                            | <b>50.00%</b>  |
| <b>TOTAL</b>  | <b>100.00%</b> |

Total arsenic, all in water soluble form, expressed as metallic - 11.10%  
This product contains 6.8 lbs. oxide per gallon  
This product weighs 13.6 lbs. per gallon

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 10356-8.

MAR 2 1990

**KEEP OUT OF THE REACH OF CHILDREN**

**DANGER**  **POISON**

**STATEMENT OF PRACTICAL TREATMENT**

**IF SWALLOWED:**

Call a physician or Poison control center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

**IF IN EYES:**

Flush with plenty of water. Call a physician.

**IF ON SKIN:**

Wash with plenty of soap and water. Get medical attention.

Refer to additional precautionary statements elsewhere on the label under the heading, "Precautionary Statements: Hazards to Humans and Domestic Animals".

**CSI**  
One Woodlawn Green  
Charlotte, NC 28217

EPA ESTABLISHMENT NO.: 10465-NC-1

EPA REGISTRATION NO.: 10356-8

NET CONTENTS \_\_\_\_\_ Lbs.

**SPECIFIC USE INSTRUCTIONS**

Contents for use only in pressure treating vessel for forest products. cannot be used in concentrated form. Do not attempt to use without implementing the necessary safety equipment. To be used only in impregnation of forest products utilizing water solutions having concentrations ranging from 0.5% to 10% by weight. Impregnations procedures must rigidly adhere to the current specifications of the American Wood Preservers Association. Treated wood is provided protection against termites, ascomycetes, brown rot, dry rot and white rot.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., banding freshly treated wood and manually opening cylinder doors.)

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to wood treatment formulation. In addition, individuals who enter pressure-treatment cylinders must wear properly fitting, well maintained, high efficiency respirators, MSHA/NIOSH approved for inorganic arsenic, if level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10ug/m<sup>3</sup>) averaged over an 8-hour work period. Air monitoring programs, procedures and record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Applicators must not eat, drink or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals and handling freshly treated wood). Wash thoroughly after skin contact and before eating, drinking, use of tobacco products or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant. Worn-out protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and federal regulations.

Processes used to apply inorganic arsenic formulations shall leave no visible surface deposits on the wood, as defined by AWPB Standard C-1 and AWPB Standards LP2 and LP22. (Visible Surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed)

**NOTE TO USER** Examples of acceptable materials for protective clothing (e.g., gloves, overalls, jackets and boots) required during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, NBR (Buna-N), rubber and polyethylene.

**WARRANTY STATEMENT**

Follow directions carefully. Buyer assumes all risks of use storage or handling of this material not in strict accordance with directions given herewith

2/2