### DIRECTIONS FOR USE

#### TERMITE CONTROL IN HOUSES:

When termites are known to exist in foundation structures such as supporting pillars, in steps and porches, as well as in house sidings and upper structures, the soil adjoining the wood or adjacent to termite runs should be treated. Since the termite nest is in the soil, the natural thing to control them is to cut them off from the nest. Open a trench around the foundation or the adjacent wood structures 30 inches deep, but not below the top of the footing if this is more shallow. Grass, trees and shrubs within three feet of the trench should be removed or protected by tar paper before the product is applied. Mix 1 part Penta 10:1 to 9 parts fuel oil or kerosene. Treat the bottom of the trench with the diluted material and then replace the soil in the trench and treat the soil. Apply at the rate of 1 gallon of diluted material for every 2 linear feet of trench if the trench is less than 15 inches deep. If the trench is over 15 inches deep, use 1 gallon of diluted material for each linear foot of trench. Inspect treated areas frequently for reinfestations.

Wood should be treated after all cuts are made and before use in the structure for protection against attack from termites.

#### SURFACES TO BE PAINTED:

Dilute 1 part Penta 10:1 with 9 parts Naphtha (sometimes called Paint and Varnish Maker's Naphtha), Oleum Spirits or Mineral Spirits. Treat the wood members as described under directions for use.

#### **OTHER USES:**

Dilute 1 part Penta 10:1 with 9 parts Distillate, Fuel Oil or Kerosene. Treat wood members as described under directions for use.

# WOOD PRESERVER

Protects Against Termites,
Wood Rotting Fungi, Lyctus
Powder Post Beetles and
Other Wood Degrading Organisms

## A Concentrate Penta Solution For Use in the Protection of Wood

Contains 40% Technical Pentachlorophenol as defined in Federal Specification TT-W-570.

### W A R N I N G ·

KEEP OUT OF REACH OF CHILDREN See Side Panels for Additional Warnings

May be harmful if swallowed or absorbed through the skin. Causes skin Irritation. Do not breathe vapor, fumes or spray mist. Do not get into eyes, on skin or on clothing. Wash thoroughly after using. Keep away from children, pets and livestock. Wear protective clothing and rubber gloves when handling freshly treated lumber.

Plants or shrubbery should be removed within 3 feet of treatment area or protect plants with tar paper. This formulation is combustible. Do not use or store near fire or flame. Keep container closed when not in use.

This product is toxic to fish and wildlife. Keep out of lakes, streams and ponds.

Rinse equipment and containers and dispose of wastes by burying in non-crop lands away from water supplies. Containers should be disposed by punching holes in them and burying them.

U.S.D.A. Reg. No. 10413-2

#### APPLY AS A SPRAY.

Use a hand-mist type or pressure sprayer. Two flowing coats of the diluted material are usually sufficient to protect joists, timbers and other wood from termites, lyctus powder post beetles and wood rotting organisms. Treat all structures which come in contact with the soil. Spray all ends and joints of wood for a distance of 3 to 4 feet, as well as sections around chimneys, cellar stairs, vent pipes and porches.

#### APPLY WITH A BRUSH:

When applying with a brush make sure that the material penetrates the wood. Make a second application to insure proper treatment. Allow the material to freely flow over the areas to be treated, paying special attention to the ends and joints for a distance of 3 to 4 feet.

#### **DIPPING OR SOAKING:**

To protect dry and well seasoned timbers, posts and other heavy wood members before construction or before placing wood in contact with the soil, dip each wood member for 12 to 48 hours to give effective penetration of the wood. Fabricated products such as door, windows, etc., should be dipped 3 to 30 minutes.

All wood members should be free of bank before receiving treatment.

#### NOTICE

muel-

Seller warrants that this product conforms to the ingredient statement on the label. Since conditions of use, such as weather, compatibility with other chemicals and condition of application equipment will vary, Seller makes no claims other than those stated on this label.

Net Contents

Gal.

LABEL 22

A PRODUCT OF

# SONFORD CHEMICAL COMPANY

P. O. BOX 127

PORT NECHES, TEXAS 77651

# ACCEPTED

JAN 2 5 1972

UNT O THE FEDERAL IMPRESSIONS

FUNGIGHE AND RESERVED AND RESIDENCE

FOR LOUNDER MO. SUBJECT

TO ATTACHED COMMENTS.

10413-2