

MICROBIOCIDE AW

ACCEPTED

THURS THE PEDERAL INSECTIONS PROGREEM: AND ROUSINTHING ACT POR BOLYGORD POISON RESISTER-ED UNDER HO.

ACTIVE INGREDIENT

Poly (oxyethylene (dimethyliminio) ethylene-(dimethyliminio) ethylene dichloride

30.0%

INERT INGREDIENT

70.0%

This product contains 2.67 lb of active ingredient per gallon and weights 8.90 lb per gallon.

EPA REG. NO. 10428-3

EPA EST. NO. 10428-WA-1

KEEP OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed Avoid breathing vapors. Avoid contact with skin, eyes, or clothing

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelat in solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

STORAGE & DISPOSAL:

Keep container closed when not in use. Do not contaminate water food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a lanufill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

DIRECTIONS FOR USE — GENERAL CLASSIFICATION

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

MICROBIOCIDE AW is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ozs. of MICROBIOCIDE AW per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of MICROBIOCIDE AW, based on the total weight of water in the system. is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.47 to 4.75 fluid ozs, of MICROBIOCIDE AW per 1000 gallons of water (4 to 40 parts per million of MICROBIOCIDE AW) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers. MICROBIOCIDE AW is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 7.1 to 11.9 fluid ozs, of MICROBIOCIDE AW per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 4.8 to 11.9 fluid ozs. of MICROBIOCIDE AW per 1000 gallons of water should be employed each 1 to 5 days or as needed. The frequency of addition depends upon the relative amount of blaedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection Arays of the air-wash system

MAY 15 1980

NET CONSTRUCTION POWER PROSTER GALLONS

ONS BATCH

WESMAR CO., INC. - 1451 - N.W. 46th - SEATTLE, WASH. 98107 - Phone 783-5344