


MICROBIOCIDE AW-15



ACTIVE INGREDIENT

Poly (axyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichtoride

15.0%

INERT INGREDIENT

85.0° o

This product contains 1.29 lb of active ingretie 1; erigallor and weights 8.58 lb per gallon.

EPA REG NO 10428-4

EPA ES1 1. 1 428 WA 1

KEEP OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing lapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed drink promptly a large quantity of milk legg whites gelatin solutions or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

STORAGE & DISPOSAL:

Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal, or cleaning of equipment. Do not reuse empty container. Triple rinse (or equivalent) and dispose of container in an incinerator or in an approved landfill, or bury in a safe place. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited

DIRECTIONS FOR USE - GENERAL CLASSIFICATION

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

MICROBIOCIDE AW-15 is used to control aigae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 4.0 to 10.0 fluid ozs of MICROBIOCIDE AW-15 per 1000 gallons of water to provide a concentration of 32 to 80 parts per million of MICROBIOCIDE AW-15, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident Subsequent slug additions of 10 to 100 fluid ozs. of MICROBIOCIDE AW-15 per 1000 gallons of water (8 to 80 parts per million of MICROBIOCIDE AW-15) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological probeem. Stug additions should be made in the sump of water cooling towers MICROPIOCIDE AW-15 is used to control bacteria in industrial air washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 14.8 to 24.7 fluid ozs, of MICROBIOCIDE AW-15 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 10.1 to 24.7 fluid ozs, of MICROBIOCIDE AW-15 per 1000 gallons of water should be employed each 1 to 5 days, or as need ed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the air-wash system

MAY 15 1980

MAY 15 1980

MICH THE PEDERAL DISECTIONS
NET CONTENTS

MAY 15 1980

MAY 15 1980

ED VIEDER NO.

BATCH

WESMAR CO., INC. - 1451 - N.W. 46th - SEATTLE, WASH, 98107 - Phone 783-5344