

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER**

Causes eye damage and skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. If product is swallowed, promptly drink 1 or 2 glasses of water. Contact a physician or Poison Control Center immediately. **DO NOT INDUCE VOMITING.**

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. **STORAGE:** Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer

(continued on right panel)



SUBSIDIARY OF WILCOX & CO., INC.

H-450

MICROBIOCIDES

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate 33.3%

INERT INGREDIENTS 66.7%

This product contains 3.2 lb. of active ingredient per gallon and weighs 9.61 lb. per gallon.

**KEEP OUT OF REACH
OF CHILDREN
DANGER**

See left side panel for additional cautions

EPA Registration No. 10445-58

- | | |
|---------------------------------------|---------------------------------------|
| [] EPA Establishment No. 10445 PA 01 | [] EPA Establishment No. 10445 TX 01 |
| [] EPA Establishment No. 10445 NJ 01 | [] EPA Establishment No. 10445 MO 01 |
| [] EPA Establishment No. 10445 CA 01 | [] EPA Establishment No. 45359 CT 01 |

For information regarding incidents involving human and environmental exposure, call (412) 777-8000 and ask for the Regulatory and Trade Affairs Department.

Net Weight 515 Lbs. (233 Kg.)

Manufactured by

CALGON CORPORATION

CALGON CENTER • PITTSBURGH, PA. 15230

ACCEPTED

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 10445-58

(continued from left panel)

for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL: Consult Federal, State, or Local disposal authorities for approved alternative procedures.

DIRECTIONS FOR USE

METHOD OF FEEDING

H-450 may be diluted to any desired lower concentration if necessary. Preferably the biocide should be fed as received using a metering pump to minimize handling.

Any additions of H-450 should be made to the cooling tower sump or in a turbulent area which provides good mixing.

Feed Requirements

Badly fouled systems must be cleaned before treatment is begun.

INDUSTRIAL RECIRCULATING WATER

INITIAL DOSE: When the system is noticeably fouled, slug feed 44.66 fluid ounces of H-450 per 1,000 gallons of water (10.45 ppm) in the system. Repeat initial dosage until control is evident.

SUBSEQUENT DOSE: When microbial control is evident, slug feed 22.66 fluid ounces of H-450 per 1,000 gallons of water (15.45 ppm) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem.

Algae Control

Heavy algae can be controlled and/or eliminated by slug feeding 14.7 fluid ounces of H-450 per 1,000 gallons of water (100 ppm H-450) daily until control is achieved.

AIR WASHER SYSTEMS

Slug additions of H-450 may be made to the sump or the water collection trays of the air washer system. Only apply H-450 in air washing systems that maintain effective mist eliminating components.

INITIAL DOSE: When the system is noticeably fouled, slug feed 74 to 147 fluid ounces of H-450 per 1,000 gallons of water (50 to 100 ppm H-450) in the system. Repeat initial dose until control is evident.

SUBSEQUENT DOSE: When microbial control is evident, slug feed 44 to 147 fluid ounces of H-450 per 1,000 gallons of water (30 to 100 ppm H-450). The frequency of addition depends upon the severity of the microbiological problem.

9M31

10445-58

1901