

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIM

CORROSIVE.

CAUSES EYE DAMAGE AND SKIN DANGER: CAUSES ALLERGIC SKIN REACTIC HARMFUL IF INHALED.

MAY BE FATAL IF SWALLOWED O

Do not betain eyes, suskin on clothing. Wear goggles or face subberrolleves when shandling. Avoid breathing vapor or incontamiliation of 100d. Do fic. take internally. Wash thoro handling.

ENVIRONMENTAL HAZARDS:

This pesticide is toxic to fish and .. Idlife Do not discharge effluer this preduct into lakes, streams ponds, estuaries, oceans or c ualess in accordance with the requirements of a National Pollutar Emnination System (NPDES) permit and the permitting authori notified in writing prior to discharge. Do not discharge effluent coproduct to sewer systems without previously notifying the sewac plant authority. For guidance, contact your State Water Board Office of the EPA.

STORAGE AND DISPOSAL PROHIBITIONS:

This product is corrosive to mile steel. Do not store or transp unlined metal containers. Do not contaminate food or fer storage, disposal, or cleaning of equipment

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposexcess pesticide or rinsate is a violation of Federal Law. If wastes cannot be disposed of by use according to label instruccontact your State Pesticide or Environmental Control Agent the Hazardous Waste representative at the nearest EPA Reg Office for guidance.

CONTAINER DISPOSAL:

METAL CONTAINERS: Tripl. rinse (or equivalent). Then offe recycling or reconditioning or puncture and dispose of sanitary landfill, or by other procedures approved by state local authorities

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer recycling or reconditioning, or puncture and dispose of sanitary landfill, or incineration, or, if allowed by state and I authorities, by burning. If burned, stay out of smoke.

Consult federal, state or local disposal authorities for appro alternative procedures.

Information concerning human and environmental exposure reviewed on the Material Safety Data Sheet for this product For additional information regarding incidents involving hum. Univergnmental exposure, call 412-777-8000 and ask for the Hea Environmental Affairs Department

BEST AVAILABLE COPY

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

CORROSIVE.

CAUSES EYE DAMAGE AND SKIN BURNS.

DANGER: CAUSES ALLERGIC SKIN REACTION. HARMFUL IF INHALED.

MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, greskin on clothing. Wear googles or face shield and subberegloves when handling. Avoid breathing vapor or mist. Avoid contamination of 16od. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS:

This perticule is toxic to fish and withlife Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters upless in appropriate with the requirements of a National Pollutant Discharge Emination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL PROHIBITIONS:

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL:

Consult federal, state or local disposal authorities for approved alternative procedures.

Information concerning human and environmental exposure may be reviewed on the Material Safety Data Sheet for this product. For additional information regarding incidents involving human and univeronmental exposure, call 412-777-8000 and ask for the Health and Environmental Affairs Department.



H-516 MICROBIOC

INDUSTRIAL MICROBIOCIDE FOR USE IN RICCOOLING TOWERS AND AIR WASH

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of egg v. available, drink large quantities of water. Avoid alcohol. Call a physician immediunconscious person.

IF INHALED. Remove immediately to fresh air. If not breathing, apply artificial oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contamir IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. Measur depression and convulsions may be needed.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.	.15%
2-Methyl-4-isothiazolin-3-one	0	.35%
INERT INGREDIENTS:	<u>9</u> 8	.50%
TOTAL	100	.00%

BULK

EPA Registration No. 10445-66

☐ EPA Establishment No. 10445-PA-01

	El
	FI

CALGON CORPO

quid, n.o.s. loro-2-Methyl in-3-One) i0, Il



NOV 23 1994 IDE ECIRCULATING WATER ER SYSTEMS

thes or gelatin solution or if these are not a tely. Never give anything by mouth to an

respiration. If breathing is difficult, give

aled clothing before reuse.

s against circulatory shock, respiratory

EEP OUT OF REACH OF CHILDREN

See Side Panel For Additional Precautionary Statements.

Lestablishment No. 10445-CA-01 Establishment No. 10445-TX-01

RATION GH, PA. 15230

00-6609-08

DIRECTIONS FOR USE

GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi add H-510 Microbiocide to the tower basin, distribution box or some other μ at to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm H-510 Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510 Microbiocide per 1000 gallons of water in the system). Repeat until control is achieved.

the system). Repeat until control is achieved. SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm H-510 Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510 Microbiocide per 1000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure unitorm mixing, 35 to 883 ppm H-510 Microbiocide (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of H-510 Microbiocide per 1000 gallons of water in the system) depending on the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled apply 148 to 883 ppm H-510 Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510 Microbiocide per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm H-510 Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510 Microbiocide per 1000 gallons of water) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is just not liceably fouled, apply 148 to 883 ppm H-510 Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510 Microbiocide per 1000 gallons of water in the system).

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm H-510 Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510 Microbiocide per 1000

gallons of makeup water).

Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in industrial air washer systems that maintain effective mist eliminating components.

H-510 Microbiocide weighs 8.4 lbs. per gallon.

