

010445-00066-052599

Printed: 09:43:38 Thursday, 24 Jun, 1999 # 26 / 3426

Systems Integration Group, Inc.



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

MAY 2 5 1999

OFFICE OF PREVENTION, PESTICIDES AND TOXIC SUBSTANCES

Calgon Corporation P. O. Box 1346 Pittsburgh, PA 15230

Attention: Henry P. Kastra

Subject: H-510-M

EPA Registration Number 10445-66 Your Submission Dated April 29, 1999 EPA Received Date May 5, 1999

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), to add Building Material Preservative to the product labeling, is acceptable provided that you:

- 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) and sec. 4 when the Agency requires all registrants of similar products such data.
- Make the following labeling changes:
 - a. ".....in Building materials such as..." to read "...in the following Building Materials: mastics, caullk...".
- 3. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If you these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703)-308-6237.

Sincerely yours,

Marshall Swindell

Product Manager 33

Regulatory Management Branch I Antimicrobial Division (7505C)

H-510-M Microbiocide

INDUSTRIAL MICROBIOCIDE FOR USE IN RECIRCULATING WATER COOLING TOWERS, AIR WASHER SYSTEMS, OILFIELD INJECTION WATERS, ELECTRODEPOSITION SYSTEMS, PAPERMILL SLIMICIDE AND BUILDING MATERIAL PRESERVATION.

FIRST AID

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of egg whites or gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. Never give anything by mouth to an unconscious person.

FINHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS	98.50%
ΤΟΤΔΙ	100.00%

ACCEPTED with COMMENTS in EPA Letter Dated:

MAY 2 5 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

KEEP OUT OF REACH OF CHILDREN DANGER

See Side Panel for Additional Precautionary Statements

EPA Registration No. 10445-66

EPA Establishment No. 10445-PA-01

EPA Establishment No. 10445-CA-01

EPA Establishment No. 10445-TX-01

EPA Establishment No. 69891-GA-1

Calgon Corporation Calgon Center Pittsburgh, PA 15230

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING COOLING WATER TOWERS

For the control of bacteria, algae and fungi add H-510-M Microbiocide to the tower basin, distribution box or some other point to insure uniform mixing.

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm

H-510-M Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm

H-510-M Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 to 883 ppm H-510-M Microbiocide (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system) depending on the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

ELECTRODEPOSITION SYSTEMS

For control of bacteria and fungi in Electrodeposition Systems such as automotive or industrial equipment systems, slug feed H-510-M Microbiocide at a rate of 1 gallon per 1000 gallons of paint in the system (1000 ppm) as needed, depending upon results of cultures taken from the system.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm H-510-M Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm H-510-M Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system) weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm H-510-M² Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of H-510-M Microbiocide per 1000 gallons of water in the system).

Subsequent Dose: Maintain this treatment level by adding a continuous feed or 35 to 219 ppm H-510-M Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of H-510-M; Microbiocide per 1000 gallons of makeup water).

ACCEPTED

Badly fouled systems must be cleaned before initial treatment.

with COMMENTS in EPA Letter Dateo:

MAY 2 5 1999 :....

Under the Federal Insecticide, Pungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

10445-66

OILFIELD INJECTION WATERS

For the control of slime-forming and sulfate-reducing bacteria in oil and gas field water systems including enhanced recovery injection fluids, drilling, fracturing and completion fluids, slug treat with 67-332 ppm H-510-M Microbiocide depending on the contamination.

Initial Dose: Add 116-332 ppm H-510-M Microbiocide (6.9-13.9 gallons of 58.0-116.8 H-510-M Microbiocide per 1,000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

Subsequent Dose: Add 67-166 ppm H-510-M Microbiocide (2.8-6.9 gallons or 23.5-58.0 lbs. H-510-M Microbiocide per 1,000 barrels of water) every seven days or as needed to maintain control.

NOTE: For use in industrial air washer systems that maintain effective mist eliminating components.

PAPERMILL SLIMICIDE

H-510-M Microbiocide is recommended for the control of bacterial and fungal slime in the production of paper. This product is approved by the Food and Drug Administration for use as a slimicide (21 CFR 176.300) and as an antimicrobial agent for fillers, binders, pigment slurries, sizing solutions, and coating formulations used in the manufacturing of paper and paperboard that contacts food. (21 CFR 176.170)

Point of Addition: H-510-M Microbiocide should be added to a point in the system to insure mixing such as the beater, hydropulper, or fan or broke storage pumps.

DOSAGE: H-510-M Microbiocide is recommended for the control of bacteria and fungi for water-based paper coating formulations and additives used in the manufacture of paper and paperboard such as fillers, binders, clay slurries, calcium carbonate slurries, titanium dioxide Jurries, pigment slurries, and sizing solutions. Add 0.43-1.65 lbs. of H-510-M Microbiocide (195-750 g) to each 1000 lbs. (453 kg) of fluid to provide 425 to 1675 ppm of product (6.25 to 25 ppm active isothiazolin). As a papermill slimicide, apply 0.44 to 1.5 lbs. (7-23 fl.oz.) of H-510-M Microbiocide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.

BUILDING MATERIAL PRESERVATION

H-510-M Microbiocide is recommended as an in-container preservative for the control of bacteria and fungi in building materials such as mastics, caulks, joint cements, spackling, and grouting. Add 0.43 - 1.65 pound of H-510-M Microbiocide (195-750 gram) to each 1000 pound (453 kilogram) of fluid to provide 425-1675 ppm product (6.25 to 25 ppm active isothiazolones).

with COMMENTS in EPA Letter Dated:

MAY 2 5 1999

H-510-M Microbiocide weighs 8.4 lbs. per gallon.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. WARRANT: Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller and Buyer assumes the risk of any

such use.

ACCEPTED with COMMENTS in EPA Letter Dated:

MAY 2 5 1999 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

10445-66

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER!

CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS.

CAUSES ALLERGIC SKIN REACTION.

HARMFUL IF INHALED.

MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, on skin, on clothing.

Wear goggles or face shield and rubber gloves when handling.

Avoid breathing vapor or mist.

Avoid contamination of food.

Do not take internally.

Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, steams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Eliminating System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

PROHIBITIONS:

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and iocal authorities, by burning. If burned, stay out of smoke.

GENERAL:

Consult federal, state or local disposal authorities for approved alternative procedures.

For additional information regarding incidents involving human and environmental exposure, call 412-494-8000 and ask for the Health and Environmental Affairs Department.

ACCEPTED with COMMENTS in EPA Letter Dated:

MAY 2 5 1999
Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

10445-66