· PM 22 10445-113			
Please read instructions on reverse before completing form.	Form Approved, OMB No. 2070-0060, Approval expires 05-	31-98	
SEPA Environmental Protection Washington, DC 20460			
Application for Pesticide - Section I			
1. Company/Product Number	Z. EPA Product Manager 3. Proposed Classification		
10445-113	Cynthia Giles-Parker None Restric	ated	
4. Company/Product (Name) Metasol TK-25 A.D.	PM#		
5. Name and Address of Applicant (Include ZIP Code) Calgon Corporation P.O. Box 1346 Pittsburgh, PA 15230	6. Expedited Review. In accordance with FIFRA Section 3(c)(: (b)(i), my product is similar or identical in composition and labelin to: EPA Reg. No.		
Check if this is a new address	Product Name		
Section - II			
Amendment - Explain below. Resubmission in response to Agency letter dated Notification - Explain below.	Final printed labels in response to Agency letter dated "Me Too" Application. Other - Explain below.		
Under the heading"films, etc., change Levels vill range from 0.08% to 1.6% to 0.02% to 1.6%.			
Section - III			
1. Material This Product Will Be Packaged In:			
Yes No	Water Soluble Packaging 2. Type of Container Metal Plaetic Glass Paper		
Jertification must Unit Packaging wgt. container	Package wgt container Other (Specify)		
3. Location of Net Contents Information 4. Size(s) Retail Container 5. Location of Label Directions On Label			
Label Container	On Labeling accompanying product		
6. Manner in Which Label is Affixed to Product Lithograph Other Stenciled			
Section - IV			
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)			
Name Tit Stanley C. Oslosky Mg	Telephone No. (Include Area Cor., Product Regulations 412-494-8862,	de)	
Certification certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment of the statement of the st			
1 0 0 haladay	Title gr., Product Regulations		
/ /	1/12/96 51/5	197	

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS

CAUTION

DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

WASH HANDS WITH SOAP AND WATER AFTER HANDLING.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

KEEP CONTAINER CLOSED WHEN NOT IN USE. WASTES RESULTING FROM THE USE OF THIS PRODUCT MAY BE DISPOSED OF ON SITE OR AT AN APPROVED WASTE DISPOSAL FACILITY.

CONTAINER DISPOSAL - DO NOT REUSE EMPTY CONTAINER.

AL CONTAINERS - TRIPLE RINSE (OR EQUIVALENT). THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES.

PLASTIC CONTAINERS - DISPOSE AS FOR METAL CONTAINERS. MATALSOME ANCINERATED, OR IF ALLOWED BY STATE

DIRECTIONS FOR USE

(CONTINUED ON RIGHT PANEL)

PAINT

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

FILMS - EXTERIORS/INTERIORS (INCLUDING COATING FOR HEATING AND AIR CONDITIONING SYSTEMS)

METASOL TK-25 AD CAN BE ADDED AT ANY STAGE IN THE FORMULATION, PROVIDED THERE IS SUFFICIENT AGITATION TO PROPERLY DISPERSE IT THROUGHOUT THE FINISHED PRODUCT. LEVELS WILL RANGE FROM 0.02% TO 1.6% BY WEIGHT OF METASOL TK-25 AD DEPENDING ON THE APPLICATION. THIS CAN ONLY BE DETERMINED BY LABORATORY EVALUATION USING THE FOLLOWING GUIDELINES:

NTERIOR LATEX BASED PAINT	0.04 - 0.3%
EXTERIOR LATEX BASED PAINT	0.10 - 0.6%
EXTERIOR ZINC OXIDE LATEX PAINT	0.06 - 0.4%
ADHESIVES	المحادث المستخدم الم
LATEX BASED ADHESIVE	0.10-0.6%
STARCH BASED ADHESIVE	0.20 - 1.2%
DEXTRINE BASED ADHESIVE	0.20 - 1.2%
CASEIN BASED ADHESIVE	0.60 - 1.6%
PAPER PRODUCTS	
Based on finished paper weight	0.02 - 0.4%
NATURAL & SYNTHETIC FIBER	THE PAST TO THE PAST PAST OF THE PAST OF T
CANVAS TEXTILES	0.20 - 1.2%
NYLON AND OTHER SYNTHETICS	0.20 - 1.6%

NOTICE TO BUYER: SELLER'S GUARANTEE SHALL BE LIMITED TO THE TERMS SET OUT ON THE LABEL AND SUBJECT THEPETO, THE BUYER
ASSUMES THE RISK TO PERSONS OR PROPERTY ARISING FROM THE USE OR HANDLING OF THIS PRODUCT AND ACCEPTS THE PRODUCT ON THAT
CONDITION.

METASOL TK-25 AD

TO INHIBIT THE GROWTH OF MOLD AND MILDEW ON ADHESIVE FILMS, PAINT FILMS, PAPER PRODUCTS, AND NATURAL AND SYNTHETIC FIBERS.

THIS PRODUCT CONTAINS 9. I 8 LBS/METASOL TK-25 AD PER GALLON

KEEP OUT OF REACH OF CHILDREN

CAUTION

EPA REGISTRATION No. 10445-113

EPA ESTABLISHMENT No. 10445-PA-01

CALGON CORPORATION
CALGON CENTER
POST OFFICE BOX 1346
PITTSBURGH, PA 15230

PAPER PRODUCTS

METASOL TK-25 AD IS MOST EFFICIENTLY APPLIED VIA THE TUB OR WATER TROUGH. THE TUB-SIZE OR WATER-TROUGH SOLUTIONS SHOULD BE ADJUSTED TO A PH BELOW 4.O. THE METASOL TK-25 AD SHOULD THEN BE ADDED WITH THOROUGH AGITATION. EFFECTIVE DOSAGE LEVELS WILL RANGE FROM O.O8 TO O.4% METASOL TK-25 AD, BASED ON THE FINISHED PAPER WEIGHT.

NOTE: METASOL TK-25 AD IS A FUNGICIDE ONLY. OTHER CALGON PRESERVATIVES SHOULD BE INCORPORATED INTO SIZING SOLUTIONS TO INHIBIT ANY MICROBIAL DEGRADATION DURING SHELF LIFE. METASOL TK-25 AD SHOULD ONLY BE USED FOR NON-FOOD GRADE PAPER PRODUCTS.

CANVAS TEXTILES

The simplest treatment method is to prepare a trough with water at pH 3-4 and then add the Metasol TK-25 AD to obtain the desired concentration. The fabric is passed through the solution until the proper amount of solution is absorbed on the fabric. A wetting agent may be used to aid the solution in pt trating the fabric. The Metasol TK-25 AD should be applied at dosage levels from 0.2 to 1.2% based on finished fabric weight. The amount necessary to provide the desired protection against mold and mildew can then be determined. If deposition of Metasol TK-25 AD onto the canvas is desired, a subsequent wash with a 1% soda ash solution will suffice. This can be followed by normal processing steps of the canvas textile. Metasol TK-25 AD should be used for manufacture of canvas textiles only, such as tents and awnings.

NYLON CARPETING

USING CONVENTIONAL METHODS SUCH AS SPIN FINISH APPLICATION OR MELT BLENDING, APPLY O. I O% (SPIN FINISH) TO I O% (MELT BLENDING) OF METASOL TK-25 AD BASED ON TOTAL WEIGHT OF THE MATERIAL BEING USED.

FOR ADDITIONAL INFORMATION REGARDING INCIDENTS INVOLVING HUMAN AND ENVIRONMENTAL EXPOSURE, CALL (412) 494-8000 AND ASK FOR THE HEALTH AND ENVIRONMENTAL AFFAIRS DEPARTMENT.