

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS

WARNING

Product is toxic to humans and animals.
Harmful if product or treated wood is swallowed.
Causes eye irritation. Do not get in eyes. Wear goggles and face shield when handling this product.
Do not inhale dust, spray or sawdust.
Wear protective gloves and clothing when handling chemical or wet treated lumber.
Launder clothing if exposed to spill or sawdust.

ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water.

PHYSICAL OR CHEMICAL HAZARDS

This product may decompose under fire conditions emitting gases and vapors, i.e. hydrogen chloride which may be toxic and irritating to the respiratory tract.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

STORAGE This product must be stored in cool place. Protect from excessive heat.

PESTICIDE DISPOSAL Pesticide, spray mixture or rinsate that cannot be used according to label instructions must be disposed of according to applicable Federal, State or local procedures.

CONTAINER DISPOSAL Do not reuse empty container. Triple rinse (or equivalent), and then offer for recycling, or reconditioning, or dispose of in a sanitary landfill, or by incineration if allowed by State and local authorities.

SPILLS Remove (shovel up or sweep up) contaminated soil. Place in closed, labeled containers and store in a safe place to await proper disposal.

MOLD-EX™

FUNGICIDE FOR CONTROL OF SURFACE MOLDS ON FRESH- CUT OR UNSEASONED WOOD

ACTIVE INGREDIENT

1,1,1-Trichloro-2,2,2-trifluoroethane 40.4

INERT INGREDIENTS

59.6

TOTAL

100.0

This product contains 4.17 lbs. active ingredient per gallon. 500 grams per liter.

*US Patents 3,290,353; 3,331,735 and 3,948,636
Diaminyl Storage Corp.

KEEP OUT OF THE REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED—Seek medical attention.

IF IN EYES—Flush with plenty of water immediately for at least 15 minutes. Seek medical attention for eyes immediately.

IF ON SKIN—Avoid contact with skin or clothing. Wash exposed areas of skin with soap and warm water after handling or using.

NOTE MOLD-EX may produce temporary allergic side effects characterized by redness of the eyes, mild bronchial irritation, and redness or rash on exposed skin areas. Persons having allergic reaction should contact a physician. Affected persons respond to treatment with antihistamines or steroid creams and/or systemic steroids.

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

Distributed By:

Mineral Research & Development Corporation
P.O. Box 31711, Charlotte, NC 28231

EPA ESTABLISHMENT NO.: 677-TX-1

EPA REGISTRATION NO.: 10465-13

NET CONTENTS: 5 Gals./19.285 Liters

DIRECTIONS

On LUMBER Under extremely hot and humid conditions use the higher recommended rate.

The active ingredient of MOLD-EX is a fine suspension in water. It tends to settle out on prolonged standing. Agitate MOLD-EX before use by slowly inverting until it is a uniform mixture. Add the required amount of MOLD-EX slowly to the mixing tank while filling. Agitate the mixture during dipping or pressure treatment. Effective control of mold requires complete wood surface coverage by the fungicide. Mold control is a preventive treatment applied before mold organisms develop.

APPLY WITH CCA PRESSURE TREATMENT Add 1½ to 3½ pints MOLD-EX to 100 gals. of CCA treating solution ready to use. Pressure treat wood or lumber by the standard procedure of American Wood Preservers Association.

ALTERNATE TREATMENTS

DIP WOOD BEFORE PRESSURE TREATMENT Dip wood in a vat containing 1½ to 3½ pints MOLD-EX to 100 gals. water. This is to control mold while wood is air drying. CCA pressure treatment may be done immediately following the dip treatment if desired.

DIP WOOD AFTER CCA PRESSURE TREATMENT Dip CCA treated wood in a vat containing 1½ to 3½ pints MOLD-EX to 100 gals. water. This may be done as soon after pressure treatment as desired.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants that this material conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with directions under normal conditions of use and Buyer assumes the risk of any use contrary to such directions. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO EXCEPT IN WRITING WITH A SPECIFIC REFERENCE TO THIS WARRANTY. In no event shall Seller's liability for any breach of warranty exceed the purchase price of the material as to which a claim is made.

