

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States
Environmental Protection Agency
Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number
245759

Application for Pesticide - Section I

1. Company/Product Number <i>10465-25</i>	2. EPA Product Manager <i>Leonard Cole</i>	3. Proposed Classification <input type="checkbox"/> None <input checked="" type="checkbox"/> Restricted
4. Company/Product (Name) <i>CSE 75% Sodium Dichromate Solution</i>	PM# <i>21</i>	
5. Name and Address of Applicant (Include ZIP Code) <i>Chemical Specialties, Inc. One Woodlawn Green, STE 250 Charlotte, NC. 28217</i> <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

PR 95-1, PR 93-10

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input checked="" type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input checked="" type="checkbox"/> Other (Specify) <i>Bulk</i>		
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container		
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container <i>N/A</i>		5. Location of Label Directions <input checked="" type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled				<input checked="" type="checkbox"/> Other <i>With Shipping Papers</i>	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name <i>Jim Saur</i>	Title <i>V.P. Regulatory Affairs</i>	Telephone No. (Include Area Code) <i>704-522-0825</i>
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>Jim Saur</i>	3. Title <i>V.P. Regulatory Affairs</i>	
4. Typed Name <i>Jim Saur</i>	5. Date <i>1-26-96</i>	

**PRECAUTIONARY STATEMENTS
DANGER - POISON**

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Fatal (poisonous) if swallowed or absorbed through skin. Do not breathe vapor, dust or spray mist. Do not get in eyes, on skin or on clothing. Corrosive, causes eye and skin damage. Wear goggles or a face shield and rubber gloves when handling.

Use of this product may be hazardous to your health. This product contains chromium compounds which have been determined to cause tumors in humans. Risks can be reduced by closely following the use directions and precautions, and by properly using the protective clothing and equipment listed elsewhere on this label.

PRECAUTIONS

Use adequate ventilation. Ventilation should be sufficient to limit employee exposure to sodium dichromate below the OSHA permissible exposure limit (0.5 mg/m³ as Cr-8-hour TWA). Where ventilation is not adequate, use a NIOSH/MSHA-approved respirator. Wear goggles or a face shield, rubber gloves, rubber boots and a rubber apron when handling. Protective clothing should be worn and changed at least daily. Wash contaminated clothing with soap and water and dry before reuse. Wash thoroughly after handling. Take a shower after work using plenty of water.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewerage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

SPECIFIC USE INSTRUCTIONS

EPA-use CCA solutions are for use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicator's certification.

Contents for use only in pressure treating cylinders for forest products. Cannot be used in concentrated form. Do not attempt to use without implementing the necessary safety equipment. To be used only in the impregnation of forest products utilizing water solutions of chromated copper arsenate having oxide equivalent concentrations ranging from 0.5% to 10% by weight. Impregnation procedures must rigidly adhere to the current specifications of the American Wood Preservers Association. Treated wood is provided protection against termites, ascomycetes, brown rot, dry rot and white rot.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to the wood treatment formulation. In addition, individuals who enter pressure-treatment cylinders must wear properly fitting, well-maintained, high efficiency filter respirators (MSHA/NIOSH-approved for inorganic arsenic). If the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10 ug/m³) averaged over an 8-hour work period. Air monitoring programs, procedures, record retention and submission must be conducted in accordance with the instructions provided with the inorganic arsenical component.

Applicators must not eat, drink or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinder, making chemicals and handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking, use of tobacco products, or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with state and federal regulations.

Processes used to apply CCA formulations shall leave no visible surface deposits on the wood, as defined by AWPFA Standard C-1 and AWPB Standards LP2 and LP22. (Visible surface deposits means a surface residue or crystallization on the treated wood. Small isolated or infrequent spots of chemical on otherwise clean wood shall be allowed.)

Individuals in the work area of a CCA wood treatment plant must wear properly-fitting, well-maintained, high-efficiency respirators, MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10 ug/m³) averaged over an 8-hour work period.

Note to user-Example of acceptable materials for protective clothing (e.g., gloves, boots, overalls and jacket) required during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, NBR (Buna-N), rubber and polyethylene.

Restricted Use Pesticide

DUE TO ACUTE TOXICITY AND BECAUSE THIS PRODUCT CONTAINS ARSENIC AND/OR CHROMIUM COMPOUNDS SOME TYPES OF WHICH HAVE BEEN ASSOCIATED WITH TUMOR DEVELOPMENT IN HUMANS
For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicators' certification.

**CSI 70% SODIUM
DICHROMATE
SOLUTION**

**For Use As A Wood Preservative In
Commercial Wood Treatment Plants**

ACTIVE INGREDIENTS:

Sodium Dichromate (Na ₂ Cr ₂ O ₇ • 2H ₂ O).....	70.0%
INERT INGREDIENTS:	30.0%
TOTAL	100.0%
WEIGHT OF SOLUTION	14.5 lbs./gal.

Before unloading, be sure hose is connected to the correct storage tank.

Keep Out Of Reach Of Children

DANGER  **POISON**

**STATEMENT OF PRACTICAL
TREATMENT-FIRST AID**

IF SWALLOWED:

Seek medical attention immediately. Never give anything by mouth to an unconscious person. Have conscious person drink several glasses of water and then induce vomiting by having person tickle back of throat with finger. Keep airway clear.

IF IN EYES:

Seek medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids apart to ensure flushing of the entire eye surface. Washing eyes within 1 minute is essential to achieve maximum effectiveness.

IF ON SKIN:

Seek medical attention immediately. Wash contaminated area with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and footwear and wash clothing before reuse. Discard footwear that cannot be decontaminated.

IF INHALED:

Seek medical attention immediately. Get person out of contaminated area to fresh air. If breathing has stopped, artificial respiration should be started. Oxygen may be administered, if readily available. If conscious, irrigate nasal passages and mouth with water.



Manufactured By:

Chemical Specialties, Inc.
One Woodlawn Green, Suite 250
Charlotte, North Carolina 28217

Phone 704/455-5181 in case of emergency.

EPA Reg. No. 10465-25

EPA Est. No. 10465-NC-1

EPA Est. No. 10465-GA-1

EPA Est. No. 10465-TX-1

Net Contents _____ Lbs.

POST A COPY OF THIS LABEL IN THE WORK AREA

DIRECTION

It is a violation of Federal Law inconsistent with its labeling.

DIREC

CSI 70% Sodium Dichromate solution when mixed with CSI Copper Sulfate Solution (10465-31) and CSI Arsenic Acid Solution (10465-32) are to be impregnated in a pressure system.

TYPE C INS

Using CSI Copper Sulfate Solution (10465-31) 2,510 gallons of water, add 4,800 gallons of CSI Arsenic Acid Solution (10465-32). The final component to be added

TYPE A INS

Using CSI Copper Sulfate Solution (10465-31) 2,558 gallons of water, add 4,800 gallons of CSI Arsenic Acid Solution (10465-32). The final step is to add 341 gallons of

STORAGE A

Do not contaminate water; food or feed. **STORAGE:** Do not store in close proximity to food. Store in tightly closed containers.

PESTICIDE DISPOSAL: Pesticide disposal is a violation of Federal Law. Improper disposal of excess pesticide is a violation of Federal Law. If these wastes are not disposed of according to label instructions, the user is liable for any damage to the environment. Contact your Environmental Control Agency, or the nearest EPA Regional Office for more information.

CONTAINER DISPOSAL: Triple rinse container, or equivalent, before recycling or reconditioning, or prior to disposal by other procedures approved by local, state, or federal authorities.

SPILLS: Follow precautionary statements on label. Do not transfer material into a plastic or steel container unless it is an approved chemical waste disposal container. Do not use approved chemical waste disposal agent (e.g., sodium bisulfite), then remove to an approved chemical waste disposal facility. NEVER FLUSH TO SEWER.

WARN

CSI warrants that the product conforms to the label directions and is reasonably fit for the purpose stated. The user assumes all responsibility for the use of this product in accordance with the label directions. **CSI MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.** Handling, storage and use of this product beyond the control of CSI. Risks of unintended consequences resulting from the use of this product follow label directions will be assumed by the user. **CASE WILL CSI BE HELD LIABLE FOR ANY DIRECT, SPECIAL OR INDIRECT DAMAGES, INCLUDING REASONABLE ATTORNEY'S FEES, ARISING FROM THE HANDLING, STORAGE OR USE OF THIS PRODUCT.**