

PM-21

Reg # 10465-28

193

Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060. Approval expires 05-31-98



United States
Environmental Protection Agency
Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number
245761

Application for Pesticide - Section I

1. Company/Product Number <i>10465-28</i>	2. EPA Product Manager <i>Leonard Cole</i>	3. Proposed Classification <input type="checkbox"/> None <input checked="" type="checkbox"/> Restricted
4. Company/Product (Name) <i>CCA Type C Wood Preservative 60%</i>	PM# <i>21</i>	
5. Name and Address of Applicant (Include ZIP Code) <i>Chemical Specialties, Inc. One Woodlawn Green, Ste. 250 Charlotte, NC. 28217</i>		6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____

Check if this is a new address

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

PR 95-1, PR 93-10

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		<input type="checkbox"/> Metal	
				<input type="checkbox"/> Plastic	
				<input type="checkbox"/> Glass	
				<input type="checkbox"/> Paper	
				<input checked="" type="checkbox"/> Other (Specify) <i>Bulk</i>	
* Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt.	No. per container
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container <i>N/A</i>		5. Location of Label Directions <input checked="" type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled		<input checked="" type="checkbox"/> Other <i>With Shipping Papers</i>			

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name <i>Jim Saur</i>	Title <i>V.P. Regulatory Affairs</i>	Telephone No. (include Area Code) <i>704-522-0825</i>
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature <i>Jim Saur</i>	3. Title <i>V.P. Regulatory Affairs</i>	
4. Typed Name <i>Jim Saur</i>	5. Date <i>1-26-96</i>	

M
2
67

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
DANGER**

Corrosive. Causes irreversible eye damage, skin or mucous membrane irritation. Harmful or fatal if swallowed, inhaled or absorbed through skin. Handle in a well ventilated area. Do not get on skin, in eyes or on clothing. Keep container closed when not in use.

Individuals in the work area of an arsenical wood treatment plant must wear properly fitting, well-maintained, high efficiency respirators, MSHA/NIOSH-approved for inorganic arsenic, if the level of inorganic arsenic in the plant is unknown or exceeds 10 micrograms per cubic meter of air (10 ug/m³) averaged over an 8-hour work period. Air monitoring programs, procedures, record retention and submission must be conducted in accordance with the instructions on the attached labeling material.

Refer to label attachment, "Permissible Exposure Limit (PEL) Monitoring Program" for additional information concerning the use of this product.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

STORAGE

This product must be stored in closed tanks or drums which display a label properly identifying the product and its concentration.

PESTICIDE DISPOSAL

Pesticides wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If this waste cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent) and offer for recycling or reconditioning or dispose of in a sanitary landfill or by other approved State and local procedures.

SPILLS

- Avoid contact with eyes, skin or clothing.
- Dike to contain with sand or soil.
- Collect usable liquid and return to work tank or drum.
- Neutralize any uncollected liquid.

60% Concentrate

Apply 200 pounds of lime or 800 pounds of cement per 40 gallons of 60% concentrate.

Working Solutions (up to 10% solution)

Apply 40 pounds of lime or 160 pounds of cement per 50 gallons of solution of 10% or less.

- Collect and enclose in steel drums, any contaminated soil, sand or absorbent and dispose in accordance with local, state and federal regulations for hazardous waste.
- Contact chemical manufacturer, state environmental agency or U.S. E.P.A. for assistance and instructions for control of spilled chemicals.

RESTRICTED USE PESTICIDE

DUE TO ACUTE TOXICITY AND BECAUSE THIS PRODUCT CONTAINS ARSENIC AND/OR CHROMIUM COMPOUNDS SOME TYPES OF WHICH HAVE BEEN ASSOCIATED WITH TUMOR DEVELOPMENT IN HUMANS
For retail sale to and use only by certified applicators or persons under their direct supervision and only for those uses covered by the certified applicator certification.

**CCA TYPE-C WOOD
PRESERVATIVE
FOR INDUSTRIAL USE ONLY
CHROMATED COPPER ARSENATE
60% CONCENTRATE**

Guarantee:

ACTIVE INGREDIENTS	Oxide
Chromic Acid (CrO ₃)	28.50%
Cupric Oxide (CuO)	11.40%
Arsenic Pentoxide (As ₂ O ₅)	20.10%
INERT INGREDIENTS	40.00%
TOTAL	100.00%

Total arsenic, all in water soluble form, expressed as metallic - 13.32%.
This product contains 9.34 lbs. oxide per gallon.
This product weighs 15.56 lbs. per gallon.

**KEEP OUT OF THE REACH OF CHILDREN
DANGER POISON**



STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED:

Contact a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

IF IN EYES:

Flush with plenty of water. Call a physician.

IF ON SKIN:

Wash with plenty of soap and water. Get medical attention.

Refer to additional precautionary statements elsewhere on the label under the heading, "Precautionary Statements: Hazards to Humans and Domestic Animals".



Manufactured By:

Chemical Specialties, Inc.
One Woodlawn Green
Charlotte, North Carolina 28217

Phone 704/455-5181 in case of emergency.

EPA Registration No. 10465-28
EPA Establishment No. 10465-NC-1
EPA Establishment No. 10465-GA-1
EPA Establishment No. 10465-TX-1
EPA Establishment No. 10465-WA-1

Net Contents _____ lbs

POST A COPY OF THIS LABEL IN WORK AREA

SPECIFIC

Contents for use only in p
Cannot be used in conce
implementing the necess
used only in impregnatio
having concentrations ra
nation procedures must r
the American Wood Preser
protection against termite
rot.

Applicators must wear g
formulation in all situatio
handling freshly treated w

Individuals who enter pre
equipment that is contam
cylinders that are in opera
must wear protective clo
boots, impervious to the
individuals who enter pre
erly fitting, well-maintaine
approved for inorganic ar
plant is unknown or excee
ug/m³) averaged over an 8
procedures, record reten
accordance with the instr

Applicators must not eat,
parts of the application p
treatment formulation (e.g.
moving trams out of cylind
treated wood).

Protective clothing must b
nation. Applicators must
boots and equipment at t
workshoes or boots must
manner approved for pest
state and federal regulati

Processes used to apply
leave no visible surface o
Standard C-1 (visible sur
crystallization on the treat
of chemical on otherwise

NOTE TO USER: Exam
clothing (e.g., gloves, ov
application and handling
chloride (PVC), neoprene

WAR

Follow directions carefull
handling of this material r
herewith.

IMPLEMENTATION OF THE PERMISSIBLE EXPOSURE LIMIT (PEL)

MONITORING PROGRAM

Each arsenical wood treatment plant employer shall require all employees potentially exposed to airborne inorganic arsenic to wear properly fitting, well maintained, high efficiency filter respirators. MSHA/NIOSH-approved for inorganic arsenic for the entire period that the employees are in the treatment application work area or engaged in any activity associated with the treatment process. Alternatively, to potentially relieve employees from the burden of wearing respirators, the employer may implement a Permissible Exposure Limit (PEL) Monitoring Program. This requirement became effective on July 10, 1986. Any plant which begins operation after April 10, 1986 will have 3 months from the date of initial operation to implement this program.

All wood treatment plant employees who elect to implement the PEL monitoring program must determine the current levels of airborne arsenic, averaged over an 8-hour period, to which their employees are exposed. Monitoring data must be obtained in the same manner as described below under "Monitoring and Measured Procedures". If the initial or subsequent monitoring demonstrates that airborne inorganic arsenic in a work area is greater than $10\mu\text{g}/\text{m}^3$, all employees working in that area are **required** to wear properly fitting, well-maintained, high efficiency filter respirators, MSHA/NIOSH-approved for inorganic arsenic. If in subsequent monitoring, at least two consecutive measurements taken at least 7 days apart, the inorganic arsenic levels are below $10\mu\text{g}/\text{m}^3$, employees in those areas may discontinue wearing the respirators except as discussed in the PEL Checklist below. However, if the employee exposure is below $10\mu\text{g}/\text{m}^3$ but above $5\mu\text{g}/\text{m}^3$, the employer shall repeat monitoring at least every 6 months until at least two consecutive measurements, taken at least 7 days apart, are $5\mu\text{g}/\text{m}^3$. The employer may then discontinue monitoring except as discussed in the PEL Checklist below.

If the monitoring reveals employees are exposed to airborne arsenic levels below $5\mu\text{g}/\text{m}^3$, monitoring need not be repeated except as discussed in the PEL Checklist below.

PEL CHECKLIST

In all cases where there has been a change in production, process, control, or employee handling procedures, or if any events in the PEL Checklist occurred, or if, for any other reasons an employer should suspect new or additional airborne inorganic arsenic, additional monitoring that complies with the requirements for initial monitoring shall be completed. Responses to the Checklist will become part of the monitoring records. Monitoring is required within 3 months if any of the following events/questions on the Checklist can be answered in the affirmative with respect to any events which may have occurred since the last monitoring report submitted to the Agency.

1. After the wood has been treated, have you changed from hand stacking to mechanical stacking or from mechanical stacking to hand stacking? If yes, when?
2. Has your production capacity increased significantly? If yes, when?
3. Have you changed from a ready-to-use or dilute concentrate to a mix-it-

yourself formulation? Has the proportional amounts of arsenic in solution increased, e.g., have you shifted from CCA Type A or C to Type B? If yes, when?

4. Has a significant (i.e., reportable under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (Superfund), 42 U.S.C. 960 et seq.) spill occurred? If yes, when?
5. Is treated wood being retained on the drip pad for less time? If yes, when?
6. Have there been any other production, process control or employee handling procedure changes which could result in new or additional airborne inorganic arsenic? Identify change and when it occurred.

MONITORING AND MEASUREMENT PROCEDURES

The Employer shall collect personal air samples, including at least one sample which is adequate to represent typical conditions for a full work shift (at least 7 hours) for each job classification in each work area. Sampling should be done using a personal sampling pump calibrated at a flow rate of 2 liters per minute. Samples should be collected on 0.8 micrometer pore size membrane filters (37 mm diameter). The method of sampling analysis should have an accuracy of not less than ± 25 percent (with a confidence limit of 95 percent) for 10 micrograms per cubic meter of air ($10\mu\text{g}/\text{m}^3$) and ± 35 percent (with a confidence limit of 95 percent) for concentrations of inorganic arsenic between 5 and $10\mu\text{g}/\text{m}^3$.

Monitoring may be conducted through a request made to the Occupational Safety and Health Administration (OSHA) for monitoring assistance, which may be provided free of charge under the terms of the OSHA consultation program as provided under section 7(c)(1) of the OSHA Act, or by the employees or contractors of the employer's choosing.

The Environmental Protection Agency (EPA) may direct that remonitoring take place at statistically selected establishments to assure that the checklist is effective in the identifying events which increase airborne arsenic. Selected employers will be notified by EPA/State enforcement representatives. The employer will be responsible for obtaining current air monitoring data within the time specified in the remonitoring notification and for submitting this data and report to the EPA as described below.

DATA SUBMISSION AND CERTIFICATION

The employer shall establish and maintain accurate records which include responses to the PEL Checklist and all monitoring reports. The annual record or copies thereof shall be submitted to the U.S. Environmental Protection Agency, Office of Pesticides and Toxic Substances, Office of Compliance Monitoring (EN-0342), 401 M Street, S.W., Washington, D.C. 20460. All records submitted will be certified by the employer as accurate and in compliance with all calibration analytical and sampling requirements outlined in this program. If the employer received assistance, from an OSHA 7(c)(1) consultant, that consultant's report to the employer will be an acceptable record of calibration, analysis, and monitoring requiring no additional certification.