#### PRECAUTIONARY STATEMENTS

Hazards to Humans to Domestic Animals

Danger. Corrosive. Causes irreversible eye damage. May be fatal
if swallowed. Do not get in eyes or on clothing. Wear goggles or
face shield. Applicators must wear gloves impervious to this
product and its treatment solutions. Wash thoroughly after
handling and before eating, drinking, using tobacco products or
using the toilet. Do not eat, drink, or use tobacco products during
those parts of the application process that may involve exposure to
this product or its treatment solutions.

Remove clothing immediately if pesticide gets inside. Then thoroughly wash and put on clean clothing. Remove protective clothing after handling this product or its treatment solutions. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. Applicators must leave protective clothing and workshoes or boots and equipment at the treatment plant. Keep and wash protective clothing separately from other laundry.

Individuals who enter pressure-treatment cylinders and other related equipment that are contaminated with this product or its treatment solutions (e.g. cylinders that are in operation or are not free of the treatment solution) must wear protective clothing including coveralls, jacket, gloves and boots. In addition, individuals who enter pressure treatment-cylinders must wear properly fitting, well-maintained, high-efficiency respirators, MSHA/NIOSH approved for ammonia. If the level of ammonia in the plant is unknown, or exceeds the short-term exposure limit (STEL) of 35 ppm, or the 8-hour time-weighted average of 25 ppm recommended by ACGIH, air-monitoring programs, procedures and record retention must be conducted in accordance with OSHA standards.

#### ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of

ACCEPTED

MAY 1 9 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 10465-33

### ACQ •- C

ACTIVE INGREDIENT	BY WEIGHT
Copper ammonium carbonate*	24.1%
Other Ingredients	75.9%
TOTAL	100.0%
*Metallic Copper equivalent	8%

Contains 0.784 lbs. copper per gallon.

# KEEP OUT OF REACH OF CHILDREN DANGER

#### FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. IF ON SKIN OR CLOTHING: take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. IF SWALLOWED: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. Note to Physician: Possible mucosal damage may contraindicate the use of gastric lavage.

## SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

CHEMICAL SPECIALITIES, INC. 200 E. Woodlawn Road, Suite 250 Charlotte, NC 28217 email: productinfo@chemspec.com

In Case of Emergency, Phone: 704-522-0825 EPA Reg. No. 10465-33 EPA Est. No. 10465-NC-1 EPA Est. No. 10465-GA-1 EPA Est. No. 10465-TX-1

Net Contents: Gallons

POST A COPY OF THIS LABEL IN WORK AREA

#### DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

#### FOR TREATMENT OF BURLAP

ACQ-C is a copper-based mildeweide specifically formulated to impart fungus resistance on burlap in accordance with Military Specifications MIL-F-46032A. The operational procedure to obtain a treated product that will pass the product specifications requires the use of a treating tank that is not constructed of or does not contain any brass or bronze materials. Dilute ACQ-C 1:1 with water in the treatment tank and immerse the burlap to be treated. Keep the burlap submerged in the tank until the burlap has obtained an analysis of 1.5% to 2.0% metallic copper measured on a dry basis.

#### INSTRUCTIONS FOR PRESSURE-TREATING WOOD

ACQ-C can only be used in conjunction with a vacuum pressure-treating vessel for impregnating forest products such as lumber, millwork, poles and piles. A treatment solution of ACQ-C must be prepared prior to use. Do not use when brass, bronze, or copper can be contacted. Impregnation procedures must follow the applicable specifications of the American Wood Preserver's Association. Treated wood is provided protection against termites, ascomycetes, brown rot and white rot.

Preparation of Treatment Solution
Use ACQ-C to make a 10% Ammoniacal Copper Quat
(ACQ) Type A or Type B Solution.

ACQ Type A Solution: To 1000 gallons of ACQ-C solution, add 168 gallons of a 50% active quaternary ammonium compound (Quat) product approved for wood preservation. The resulting treatment solution is 1168 gallons and contains 8.9% CuO and 8.9% Quat.

ACQ Type B Solution: To 1000 gallons of ACQ-C solution, add 84 gallons of a 50% active quaternary ammonium compound (Quat) product approved for wood preservation. The resulting treatment solution is 1084 gallons and contains 9.4% CuO and 4.7% Quat.

Revised 4/18/03 Page 1 of 2

5/19/2003

46

## INSTRUCTIONS FOR TREATMENT OF COMPOSITE WOOD COMPONENTS

For treatment of composite wood components, ACQ-C can be applied either neat (10% active copper) or as a 1:1 dilution in water (5% active copper). The solution concentration and amount applied should result in a retention of copper in wood of 0.1-0.5 pounds per cubic foot (pcf). Note that the amount of treatment solution applied may vary depending on the moisture content of the composite wood component and the desired distribution of ACQ-C in wood.

Apply the treatment solution by spraying the composite wood component with a low-pressure sprayer. A moderately fine spray, not an aerosol or fog, generally provides the best coverage. Apply in a commercial spray booth, with adequate ventilation and scrubbers to ensure the ambient ammonia levels do not exceed the levels noted in the Precautionary Statements section.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of the Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

### Container Disposal:

<u>Plastic</u>: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or if allowed by state and local authorities, by burning. If burned stay out of smoke.

Metal. Thinge tinse for equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

#### CONDITIONS OF SALE AND WARRANTY

Seller warrants that its product conforms in its standard specifications set forth on this label, SELLER MAKES NO OTHER REPRESENTATIONS OR WARRANTIES OF ANY KIND. AS TO THE MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE OR ANY OTHER MATTER WITH RESPECT TO THE PRODUCT. WHETHER USED ALONE OR IN COMBINATION WITH ANY OTHER MATERIAL BUYER ASSUMES ALL RISKS TO PERSONS OR PROPERTY ARISING OUT OF THE USE OR HANDLING AND ACCEPTS THE PRODUCT SUBJECT TO THE CONDITIONS SET FORTH ON THIS LABEL. BECAUSE TIME, GEOGRAPHICAL LOCATION, RATE OF APPLICATION, AND OTHER CONDITIONS ARE BEYOND THE SELLER'S LIABILITY FOR ANY LOSS OR DAMAGES ARISING OUT OF ANY CASE CAUSE INCLUDING STORAGE, HANDLING AND USE OF THIS PRODUCT SHALL IN NO EVENT EXCEED THE PURCHASE PRICE OF THE PRODUCT IN RESPECT TO WHICH SUCH CAUSE ARISES OR AT SELLER'S OPTION THE REPLACEMENT OF SUCH PRODUCT AND IN NO EVENT SHALL SELLER BE LIABLE FOR INCIDENTAL, SPECIAL. CONSEQUENTIAL OR PUNITIVE DAMAGES RESULTING FROM ANY CAUSE. No claim for any cause whatsoever shall be allowed unless Buyer gives Seller prompt written notice thereof. Failure to commence action with respect to such claim within a year from date of delivery of ACO-C for which a claim is alleged, shall constitute a waiver by Buyer of any such claim.