

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CONTAINS PETROLEUM DISTILLATE
AND COPPER NAPHTHENATE**

FIRST AID PROCEDURE

Harmful if swallowed. May be absorbed through skin. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Avoid breathing vapor or spray mist. Use in a well ventilated area.

Do not breath vapors or mist during brush, roll, spray or dip applications. Wear a NIOSH/MHSA-approved mist/vapor respirator when spraying for continued or prolonged use of this product or for frequent use of this product.

IF SWALLOWED: Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Flush with plenty of water and get immediate medical attention.

IF CLOTHING CONTAMINATED: Remove and wash thoroughly before reuse.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after each use.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Product will not freeze. Store at temperatures between 0° and 100°F. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then where applicable, wash area with detergent and water. Store product in original container only. Do not store with fertilizers, food and feed. Keep container closed and when not in use.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility in accordance with appropriate Federal, State, and local regulations.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

CSI

10-9-0 Green F.O.

WOOD PRESERVATIVE

EPA Reg. No. 10465-34
EPA Est. No. 54471-NB001

**WOOD EXTERIOR SURFACES
INCLUDING POLE TOP, BORE HOLE
POSTS, BEAMS LUMBER
AND STRUCTURAL WOOD**

KEEP OUT OF REACH OF CHILDREN

WARNING

COMBUSTIBLE

HARMFUL IF SWALLOWED

See other precautionary statements
on side panel.

**IN CASE OF MEDICAL QUESTIONS,
EMERGENCIES, OR ACCIDENTS
INVOLVING THIS PRODUCT, CALL
CHEM-TREC AT 1-800-424-9300.**

ACTIVE INGREDIENTS

| | |
|---|---------|
| Copper Naphthenate (2% Copper as metal) | 19.25% |
| INERT INGREDIENTS..... | 80.75% |
| TOTAL..... | 100.00% |

Net Contents:

☐ 2.5 U.S. Gallon ☐ 5 U.S. Gallon ☐ 55 U.S. Gallon

Weight per gallon - 7.4 lbs

ACCEPTED

FEB 12 1998

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 10465-34

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Exterior Use Only.

**FUNGICIDE
PLUS
WATER REPELLENT**

(Meets Federal Specification TT-W-572B)

10-9-0 WOOD PRESERVATIVE

10-9-0 Green F.O. is intended for use only on exterior wood surfaces as a wood preservative treatment. 10-9-0 Green F.O. provides protection against moisture, fungi rot, termite damage and mildew on any natural wood surface. Do not contaminate potable water with treated articles. Do not apply to live stock food or feed contact surfaces. This copper naphthenate wood preservative and insecticide will preserve, protect and seal wood surfaces that will be in contact with soil or concrete. Depending on climatic conditions, species of wood to which applied, moisture and humidity, treatment extends service life several years. Retreat when possible every 5 to 7 years for sound maintenance.

PREPARATION AND APPLICATION

Wood should be clean, dry, well seasoned and free of bark. 10-9-0 Green F.O. should be applied liberally by brush, roller or spray. DO NOT THIN. Material is supplied at proper application consistency. If no finish is to be used, apply two liberal coats within the hour. Thoroughly cover ends, joints, cracks, and any cuts or holes made after the initial treatment. Clean equipment with mineral spirits for quick clean up. Best results when applied at temperatures between 40° and 100°F.

Application of this product may produce a strong, lingering, unpleasant odor.

Statement of Coverage: One gallon will treat approximately 200-300 square feet.

Manufactured For:
CHEMICAL SPECIALTIES, INC.
One Woodlawn Green, Suite 250
Charlotte, NC 28217
(800) 801-0078/(800) 421-8661

Jan-98

PM 34
10465-34
2-12-98
1041