

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**CONTAINS PETROLEUM DISTILLATE  
AND COPPER NAPHTHENATE**

**FIRST AID PROCEDURE**

Harmful if swallowed. May be absorbed through skin. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Avoid breathing vapor or spray mist. Use in a well ventilated area.

Do not breath vapors or mist during brush, roll, spray or dip applications. Wear a NIOSH/MHSA - approved mist/vapor respirator when spraying for continued or prolonged use of this product or for frequent use of this product.

**IF SWALLOWED:** Do not induce vomiting. CALL PHYSICIAN IMMEDIATELY.  
**IF INHALED:** Remove to fresh air.  
**IF IN EYES:** Flush with plenty of water and get immediate medical attention.  
**IF CLOTHING CONTAMINATED:** Remove and wash thoroughly before reuse.

**ENVIRONMENTAL HAZARDS**

Do not discharge effluent containing this product into lakes, streams ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS**

Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after each use.

**STORAGE AND DISPOSAL**

Product will not freeze. Store at temperatures between 0° and 120°F. If the product has been spilled, spread absorbent, then pick up and place in containers. DO NOT STORE opened packages.  
**DISPOSAL:** Wrap any cut portion of CUNAP WRAP™ and put into trash collection.

**CUNAP WRAP™**

Patent No. 4,731,267

**WOOD PRESERVATIVE**

EPA Reg. No. 10465-35  
EPA Est. No. 54471-NB001

**WOOD EXTERIOR SURFACE  
WRAP FOR ABOVE OR BELOW  
GROUND TREATMENT FOR  
POLES, POSTS AND PILINGS**

KEEP OUT OF REACH OF CHILDREN  
**WARNING**  
COMBUSTIBLE  
HARMFUL IF SWALLOWED  
See other precautionary statements  
on side panel.

IN CASE OF MEDICAL QUESTIONS, EMERGENCIES,  
OR ACCIDENTS INVOLVING THIS PRODUCT, CALL  
CHEM-TREC AT 1-800-424-9300.

CONTAINS INGREDIENTS LISTED BELOW  
SATURATED IN SYNTHETIC ABSORBENT CLOTH  
ENCAPSULATED IN CHEMICAL AND VAPOR  
RESISTANT CONTAINERS WITH AN ADDITIONAL  
CHEMICAL RESISTANT VAPOR BARRIER CROSS  
LAMINATED BACKING.

**ACTIVE INGREDIENTS**  
Copper Naphthenate(2% Copper as metal) 19.25%  
**INERT INGREDIENTS**..... 80.75%  
**TOTAL**..... 100.00%



Manufactured For:

CHEMICAL SPECIALTIES, INC  
One Woodlawn Green, Suite 250  
Charlotte, NC 28217  
(800) 801-0078/(206)251-8275

**ACCEPTED**

FEB 12 1998

Under the Federal Insecticide, Fungicide, and  
Rodenticide Act as amended, for the  
pesticide, registered under  
EPA Reg. No. 10465-35

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Exterior Use Only.

CUNAP WRAP containing copper naphthenate is intended for use only on poles, posts and pilings as a wood preservative treatment. CUNAP WRAP containing copper naphthenate provides protection against moisture, fungal rot and termite damage. This copper naphthenate wood preservative and insecticide will preserve, protect and seal wood surfaces that will be in contact with soil or concrete. Depending upon climatic conditions, species of wood to which applied, moisture and humidity, treatment extends service life several years.

**PREPARATION AND APPLICATION**

Wood should be clean, dry, well seasoned and free of bark. When using CUNAP WRAP as a groundline treatment, excavate around wood to allow top of wrap to extend 2" above the groundline.

Protect eyes and skin from contact.

Wire brush area 3" above groundline and approximately 20" below groundline removing dirt and decayed material.

Lift CUNAP WRAP from carton and lay on ground. Unfold, exposing plastic envelopes. Cut open bags as shown by lines, exposing saturated pads. Avoid cutting through to backing.



Wrap proper length CUNAP WRAP around the pole with saturated pad against the pole and staple or tack firmly in place. Staple the short side of the backing first and overwrap with longer edge. Allow wrap to extend 2" above groundline. Backfill excavation, tamping firmly.

Application of this product may produce a strong, lingering, unpleasant odor.

Statement of Coverage: One gallon will treat approximately 200-300 square feet.

Jan-98

PM 34  
10465-35  
2-12-98  
1021