

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Use ACQ-C2 to control all types of fungal decay of wood products - brown, white and soft rot and wood eating insects including termites. ACQ-C2 should be used to treat any wood product that will be exposed to conditions favorable to rot, decay or insect attack both above ground and in ground or water. Types of products include lumber, timbers, landscape ties, fence posts, building and utility poles, land, freshwater and marine piling, sea walls, decking and wood shingles.

Tank mix ACQ-C2 with quaternary ammonium compounds approved for wood treatment. Apply the tank mixed solution by pressure impregnation. Follow the mixing instructions "Solution Mixing Table for ACQ-C2 (2 Component)" for obtaining the desired solution concentration. The percent solution to be used should be based on the retention, in lbs. per cubic foot (pcf), specified by the purchaser and by the treating process used.

A 3% solution can be used to field coat the cut ends of pressure treated wood by brush-on application.

ACCEPTED

MAY - 2 2000

10465-36

ACQ-C2

For the Control of Wood Damaging Fungi and Insects

ACTIVE INGREDIENT

Copper as elemental 9.0%

INERT INGREDIENTS 91.0%

TOTAL 100.0%

*From mixed Copper ethanolamine complexes.

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Promptly drink 1-2 glasses of water. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Call a physician immediately.

If on skin: Wash thoroughly with water. Get medical attention if irritation persists.

If in eyes: Flush with large quantities of water for 15 minutes. Get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Net Contents:

Chemical Specialties, Inc.
One Woodlawn Green
Suite 250
Charlotte, NC 28217

EPA Reg. No. 10465-36
EPA Est. No. 10465-NC-1

**PRECAUTIONARY STATEMENTS
Hazards To Humans And
Domestic Animals**

DANGER: Corrosive, causes eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed, absorbed through the skin or inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

ENVIRONMENTAL HAZARDS:

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public water unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal

Pesticide Disposal:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the hazardous Waste representative at the nearest EPA Regional Office for guidance.

Container Disposal:

Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill.

10465-36

S-2-2000

1/2

Solution Mixing Table for ACQ-C2 (2 Component)

Solution Strength % Active	Component Balance Actives Basis (%)		To Mix 1000 Gallons Solution Combine following Gallons of		
	CuO	Quat	ACQ-C2	Quat (50%)	Water
0.60%	0.400%	0.200%	28.4	4.38	967.2
0.65%	0.433%	0.217%	30.8	4.74	964.4
0.70%	0.467%	0.233%	33.2	5.11	961.7
0.75%	0.500%	0.250%	35.6	5.48	958.9
0.80%	0.533%	0.267%	38.0	5.85	956.1
0.85%	0.567%	0.283%	40.4	6.21	953.4
0.90%	0.600%	0.300%	42.8	6.58	950.6
0.95%	0.633%	0.317%	45.2	6.95	947.8
1.00%	0.667%	0.333%	47.6	7.32	945.1
1.10%	0.733%	0.367%	52.4	8.06	939.5
1.20%	0.800%	0.400%	57.2	8.80	934.0
1.30%	0.867%	0.433%	62.1	9.55	928.4
1.40%	0.933%	0.467%	66.9	10.29	922.8
1.50%	1.000%	0.500%	71.8	11.04	917.2
1.60%	1.067%	0.533%	76.6	11.79	911.6
1.70%	1.133%	0.567%	81.5	12.53	906.0
1.80%	1.200%	0.600%	86.4	13.28	900.3
1.90%	1.267%	0.633%	91.3	14.04	894.7
2.00%	1.333%	0.667%	96.2	14.79	889.1
2.10%	1.400%	0.700%	101.1	15.55	883.4
2.20%	1.467%	0.733%	106.0	16.30	877.7
2.30%	1.533%	0.767%	110.9	17.06	872.0
2.40%	1.600%	0.800%	115.8	17.82	866.3
2.50%	1.667%	0.833%	120.8	18.58	860.6
2.60%	1.733%	0.867%	125.7	19.34	854.9
2.70%	1.800%	0.900%	130.7	20.10	849.2
2.80%	1.867%	0.933%	135.7	20.87	843.4
2.90%	1.933%	0.967%	140.7	21.64	837.7
3.00%	2.000%	1.000%	145.7	22.40	831.9
3.10%	2.067%	1.033%	150.7	23.17	826.2
3.20%	2.133%	1.067%	155.7	23.94	820.4
3.30%	2.200%	1.100%	160.7	24.72	814.6
3.40%	2.267%	1.133%	165.7	25.49	808.8
3.50%	2.333%	1.167%	170.8	26.27	803.0
3.60%	2.400%	1.200%	175.8	27.04	797.1
3.70%	2.467%	1.233%	180.9	27.82	791.3
3.80%	2.533%	1.267%	185.9	28.60	785.5
3.90%	2.600%	1.300%	191.0	29.38	779.6

Solution Strength % Active	Component Balance Actives Basis (%)		To Mix 1000 Gallons Solution Combine following Gallons of		
	CuO	Quat	ACQ-C2	Quat (80%)	Water
0.60%	0.400%	0.200%	28.4	2.83	968.7
0.65%	0.433%	0.217%	30.8	3.07	966.1
0.70%	0.467%	0.233%	33.2	3.31	963.5
0.75%	0.500%	0.250%	35.6	3.55	960.8
0.80%	0.533%	0.267%	38.0	3.79	958.2
0.85%	0.567%	0.283%	40.4	4.03	955.6
0.90%	0.600%	0.300%	42.8	4.26	952.9
0.95%	0.633%	0.317%	45.2	4.50	950.3
1.00%	0.667%	0.333%	47.6	4.74	947.7
1.10%	0.733%	0.367%	52.4	5.22	942.4
1.20%	0.800%	0.400%	57.2	5.70	937.1
1.30%	0.867%	0.433%	62.1	6.18	931.7
1.40%	0.933%	0.467%	66.9	6.67	926.4
1.50%	1.000%	0.500%	71.8	7.15	921.1
1.60%	1.067%	0.533%	76.6	7.63	915.7
1.70%	1.133%	0.567%	81.5	8.12	910.4
1.80%	1.200%	0.600%	86.4	8.61	905.0
1.90%	1.267%	0.633%	91.3	9.09	899.6
2.00%	1.333%	0.667%	96.2	9.58	894.3
2.10%	1.400%	0.700%	101.1	10.07	888.9
2.20%	1.467%	0.733%	106.0	10.56	883.5
2.30%	1.533%	0.767%	110.9	11.05	878.0
2.40%	1.600%	0.800%	115.8	11.54	872.6
2.50%	1.667%	0.833%	120.8	12.04	867.2
2.60%	1.733%	0.867%	125.7	12.53	861.7
2.70%	1.800%	0.900%	130.7	13.02	856.3
2.80%	1.867%	0.933%	135.7	13.52	850.8
2.90%	1.933%	0.967%	140.7	14.02	845.3
3.00%	2.000%	1.000%	145.7	14.51	839.8
3.10%	2.067%	1.033%	150.7	15.01	834.3
3.20%	2.133%	1.067%	155.7	15.51	828.8
3.30%	2.200%	1.100%	160.7	16.01	823.3
3.40%	2.267%	1.133%	165.7	16.51	817.8
3.50%	2.333%	1.167%	170.8	17.01	812.2
3.60%	2.400%	1.200%	175.8	17.52	806.7
3.70%	2.467%	1.233%	180.9	18.02	801.1
3.80%	2.533%	1.267%	185.9	18.53	795.5
3.90%	2.600%	1.300%	191.0	19.03	789.9

2/2