EPA Form 8570-6 (Rev. 5-76)

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.



CAP-CIDE 15

1887 B 1987

Cir. 1. Proping Co. and Route. 67 annuals, for the professor and RAA

10595 -

ACTIVE INGREDIENT:

<u>8.58</u> b. per gallon.

This product contains 1.29 lb. of active ingredient per gallon and weighs

KEEP OUT OF REACH OF CHILDREN

i CAUTION

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, drink large quantities of water

gelatin solution, or, if these are not available, drink large quantities of water Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this

lakes, streams, or ponds. Permits may be required for discharges containing this peshode into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

DIRECTIONS FO

It is a violation of Federal law to use this pr

its labeling.

CAP-CIDE 15

and fungi in recirculating commercial and into its use, systems must be cleaned to rer slime, and other deposits. An initial slug add fluid ounces of <u>CAP-CIDE 15</u>

of water to provide a concentration of ____32 _____, CAP-CIDE 15 ______, in the system, is recommended. Repeat initial

Subsequent slug additions of 1.0

CAP-CIDE 15 per 10

80 parts per million of CAP-CIDE employed every 2 to 5 days, or as needed.

upon the relative amount of bleedoff and the lem. Slug additions should be made in the s

<u>CAP-CIDE 15</u> is to stays, or as needed.

to its use, systems should be cleaned to deposits. An initial slug dose of 14.8

CAP-CIDE 15

mended. Repeat initial dosage until control tions of 10.1 to 2/4.7 third appears

tions of 10,1 to 24.7 fluid ounces of per 1000 gallons of water should be employed frequency of addition depends upon the relation the bacterial problem. Slug additions may collection trays of the airwash system.

STORAGE AND

Do not contaminate water, look or feet by storage or disposing STORAGE: Do not stack more than four drums high. Leaking drums for disposal. Spails should be absorbed in sawdost or stainer closed when not in use.

PESTICIDE DISPOSAL. Australia resulting from the use of

Proved waste disposal lace by CONTAINER DISPOSAL

To PLASTIC Tople case to equiverso it or offer for recycle sandary hindful by or moretism or if thoseid by state and smoke.
(2) MCTAL Tuple mass to copy, cont. Then offer for recycle.

(2) METAL. Tuple raise to expore ent. Then other for recyclic sandary laudful or by other procedures, upmoved by state

CAPITAL & QUALITY PROPERTY AVE.

RICHMOND, VA 23230

EPA REG. NO.

NET CONTENTS ...