


ACCEPTED

* * ,

August 17, 1972



Poly oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride

INERT INGREDIENT:

100%

Weight per gallon 8.39 Lbs. Weight of active ingredient per gallon 0.42 Lbs.

EPA Reg. No. 10600-3



Manufactured By

SUHM LABORATORIES, INC.

Milwaukee, Wisconsin

CAUTION:

KEEP OUT OF REACH OF CHILDREN

> See Side Panel for Precautions

NET CONTENTS

GALLONS

Suhm EX-A(1) is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers, heat exchangers and water storage tanks.

APPLICATION

INITIAL DOSE. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits.

An initial slug addition of 11.4 to 28.5 fluid ounces of EX-A (1) per 1,000 gallons of water is recommended to provide a concentration of 4.8 to 12 parts per million of active ingredients based on the total weight of water in the system. Repeat until control is achieved.

SUBSEQUENT TREATMENT: Subsequent slug additions of 2.8 to 28.5 fluid ounces of EX-A(1) per 1,000 gallons of water (1.2 to 12 parts per million of active ingredients) should be employed every 2 to 5 days or as needed. The frequency of these slug additions depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION:

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Do not reuse container. Destroy when empty. Use only as directed on the label.

NOTICE: Supplier makes no warranty, expressed or implied, concerning the use of this product other than indicated on this label. The user assumes all risks of use and/or handling of this material when such use and/or handling is contrary to label instructions.